

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 July 2006 (27.07.2006)

PCT

(10) International Publication Number
WO 2006/079072 A2

(51) International Patent Classification:
E21B 19/00 (2006.01)

(21) International Application Number:
PCT/US2006/002449

(22) International Filing Date: 20 January 2006 (20.01.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/645,840 21 January 2005 (21.01.2005) US

(71) Applicant (for all designated States except US): **ENVEN-
TURE GLOBAL TECHNOLOGY** [US/US]; 15995 N.
Barkers Landing, Suite 350, Houston, TX 77079 (US).

(71) Applicant and

(72) Inventor: **DELUCIA, Frank** [US/US]; 11415 Lakewood
Estates, Houston, TX 77070 (US).

(74) Agent: **MATTINGLY, Todd**; Haynes and Boone, LLP,
901 Main Street, Suite 3100, Dallas, TX 75202-3789 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR EXPANDING A TUBULAR MEMBER

(57) Abstract: A method and apparatus for
expanding a tubular member.



BEST AVAILABLE COPY

127



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

METHOD AND APPARATUS FOR EXPANDING A TUBULAR MEMBER

[0001] This application claims the benefit of the filing date of US provisional patent application serial number 60/645,840, attorney docket number 25791.324, filed on January 21, 2005, the disclosure which is incorporated herein by reference.

[0002] This application is a CIP of U.S. utility patent application serial number 11/084,788, attorney docket number 25791.325, filed on 3/18/05, which is a continuation of U.S. utility patent application serial number 10/418,687, attorney docket no. 25791.228, filed on 4/18/2003, which is a continuation of U.S. utility patent application serial number 09/852,026, attorney docket no. 25791.56, filed on 5/9/2001, which is a division of U.S. utility patent application serial number 09/454,139, attorney docket no. 25791.3.02, filed on 12/3/1999, which claimed the benefit of the filing date of U.S. provisional patent application serial number 60/111,293, attorney docket number 25791.3, filed on 12/7/1998, the disclosures of which are incorporated herein by reference.

[0003] This application is related to the following co-pending applications: (1) U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (2) U.S. patent application serial no. 09/510,913, attorney docket no. 25791.7.02, filed on 2/23/2000, which claims priority from provisional application 60/121,702, filed on 2/25/99, (3) U.S. patent application serial no. 09/502,350, attorney docket no. 25791.8.02, filed on 2/10/2000, which claims priority from provisional application 60/119,611, filed on 2/11/99, (4) U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (5) U.S. patent application serial no. 10/169,434, attorney docket no. 25791.10.04, filed on 7/1/02, which claims priority from provisional application 60/183,546, filed on 2/18/00, (6) U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (7) U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (8) U.S. patent number 6,575,240, which was filed as patent application serial no. 09/511,941, attorney docket no. 25791.16.02, filed on 2/24/2000, which claims priority from provisional application 60/121,907, filed on 2/26/99, (9) U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on

6/7/99, (10) U.S. patent application serial no. 09/981,916, attorney docket no. 25791.18, filed on 10/18/01 as a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (11) U.S. patent number 6,604,763, which was filed as application serial no. 09/559,122, attorney docket no. 25791.23.02, filed on 4/26/2000, which claims priority from provisional application 60/131,106, filed on 4/26/99, (12) U.S. patent application serial no. 10/030,593, attorney docket no. 25791.25.08, filed on 1/8/02, which claims priority from provisional application 60/146,203, filed on 7/29/99, (13) U.S. provisional patent application serial no. 60/143,039, attorney docket no. 25791.26, filed on 7/9/99, (14) U.S. patent application serial no. 10/111,982, attorney docket no. 25791.27.08, filed on 4/30/02, which claims priority from provisional patent application serial no. 60/162,671, attorney docket no. 25791.27, filed on 11/1/1999, (15) U.S. provisional patent application serial no. 60/154,047, attorney docket no. 25791.29, filed on 9/16/1999, (16) U.S. provisional patent application serial no. 60/438,828, attorney docket no. 25791.31, filed on 1/9/03, (17) U.S. patent number 6,564,875, which was filed as application serial no. 09/679,907, attorney docket no. 25791.34.02, on 10/5/00, which claims priority from provisional patent application serial no. 60/159,082, attorney docket no. 25791.34, filed on 10/12/1999, (18) U.S. patent application serial no. 10/089,419, filed on 3/27/02, attorney docket no. 25791.36.03, which claims priority from provisional patent application serial no. 60/159,039, attorney docket no. 25791.36, filed on 10/12/1999, (19) U.S. patent application serial no. 09/679,906, filed on 10/5/00, attorney docket no. 25791.37.02, which claims priority from provisional patent application serial no. 60/159,033, attorney docket no. 25791.37, filed on 10/12/1999, (20) U.S. patent application serial no. 10/303,992, filed on 11/22/02, attorney docket no. 25791.38.07, which claims priority from provisional patent application serial no. 60/212,359, attorney docket no. 25791.38, filed on 6/19/2000, (21) U.S. provisional patent application serial no. 60/165,228, attorney docket no. 25791.39, filed on 11/12/1999, (22) U.S. provisional patent application serial no. 60/455,051, attorney docket no. 25791.40, filed on 3/14/03, (23) PCT application US02/2477, filed on 6/26/02, attorney docket no. 25791.44.02, which claims priority from U.S. provisional patent application serial no. 60/303,711, attorney docket no. 25791.44, filed on 7/6/01, (24) U.S. patent application serial no. 10/311,412, filed on 12/12/02, attorney docket no. 25791.45.07, which claims priority from provisional patent application serial no. 60/221,443, attorney docket no. 25791.45, filed on 7/28/2000, (25) U.S. patent application serial no. 10/, filed on 12/18/02, attorney docket no. 25791.46.07, which claims priority from provisional patent application serial no. 60/221,645, attorney docket no. 25791.46, filed on 7/28/2000, (26) U.S. patent application serial no. 10/322,947, filed on

1/22/03, attorney docket no. 25791.47.03, which claims priority from provisional patent application serial no. 60/233,638, attorney docket no. 25791.47, filed on 9/18/2000, (27) U.S. patent application serial no. 10/406,648, filed on 3/31/03, attorney docket no. 25791.48.06, which claims priority from provisional patent application serial no. 60/237,334, attorney docket no. 25791.48, filed on 10/2/2000, (28) PCT application US02/04353, filed on 2/14/02, attorney docket no. 25791.50.02, which claims priority from U.S. provisional patent application serial no. 60/270,007, attorney docket no. 25791.50, filed on 2/20/2001, (29) U.S. patent application serial no. 10/465,835, filed on 6/13/03, attorney docket no. 25791.51.06, which claims priority from provisional patent application serial no. 60/262,434, attorney docket no. 25791.51, filed on 1/17/2001, (30) U.S. patent application serial no. 10/465,831, filed on 6/13/03, attorney docket no. 25791.52.06, which claims priority from U.S. provisional patent application serial no. 60/259,486, attorney docket no. 25791.52, filed on 1/3/2001, (31) U.S. provisional patent application serial no. 60/452,303, filed on 3/5/03, attorney docket no. 25791.53, (32) U.S. patent number 6,470,966, which was filed as patent application serial number 09/850,093, filed on 5/7/01, attorney docket no. 25791.55, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (33) U.S. patent number 6,561,227, which was filed as patent application serial number 09/852,026, filed on 5/9/01, attorney docket no. 25791.56, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (34) U.S. patent application serial number 09/852,027, filed on 5/9/01, attorney docket no. 25791.57, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (35) PCT Application US02/25608, attorney docket no. 25791.58.02, filed on 8/13/02, which claims priority from provisional application 60/318,021, filed on 9/7/01, attorney docket no. 25791.58, (36) PCT Application US02/24399, attorney docket no. 25791.59.02, filed on 8/1/02, which claims priority from U.S. provisional patent application serial no. 60/313,453, attorney docket no. 25791.59, filed on 8/20/2001, (37) PCT Application US02/29856, attorney docket no. 25791.60.02, filed on 9/19/02, which claims priority from U.S. provisional patent application serial no. 60/326,886, attorney docket no. 25791.60, filed on 10/3/2001, (38) PCT Application US02/20256, attorney docket no. 25791.61.02, filed on 6/26/02, which claims priority from U.S. provisional patent application serial no. 60/303,740, attorney docket no. 25791.61, filed on 7/6/2001, (39) U.S. patent

application serial no. 09/962,469, filed on 9/25/01, attorney docket no. 25791.62, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (40) U.S. patent application serial no. 09/962,470, filed on 9/25/01, attorney docket no. 25791.63, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (41) U.S. patent application serial no. 09/962,471, filed on 9/25/01, attorney docket no. 25791.64, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (42) U.S. patent application serial no. 09/962,467, filed on 9/25/01, attorney docket no. 25791.65, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (43) U.S. patent application serial no. 09/962,468, filed on 9/25/01, attorney docket no. 25791.66, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (44) PCT application US 02/25727, filed on 8/14/02, attorney docket no. 25791.67.03, which claims priority from U.S. provisional patent application serial no. 60/317,985, attorney docket no. 25791.67, filed on 9/6/2001, and U.S. provisional patent application serial no. 60/318,386, attorney docket no. 25791.67.02, filed on 9/10/2001, (45) PCT application US 02/39425, filed on 12/10/02, attorney docket no. 25791.68.02, which claims priority from U.S. provisional patent application serial no. 60/343,674, attorney docket no. 25791.68, filed on 12/27/2001, (46) U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001, (now U.S. Patent 6,634,431 which issued 10/21/2003), which is a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (47) U.S. utility patent application serial no. 10/516,467, attorney docket no. 25791.70, filed on 12/10/01, which is a continuation application of U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001, (now U.S. Patent 6,634,431 which issued 10/21/2003), which is a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number

25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (48) PCT application US 03/00609, filed on 1/9/03, attorney docket no. 25791.71.02, which claims priority from U.S. provisional patent application serial no. 60/357,372, attorney docket no. 25791.71, filed on 2/15/02, (49) U.S. patent application serial no. 10/074,703, attorney docket no. 25791.74, filed on 2/12/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (50) U.S. patent application serial no. 10/074,244, attorney docket no. 25791.75, filed on 2/12/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (51) U.S. patent application serial no. 10/076,660, attorney docket no. 25791.76, filed on 2/15/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (52) U.S. patent application serial no. 10/076,661, attorney docket no. 25791.77, filed on 2/15/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (53) U.S. patent application serial no. 10/076,659, attorney docket no. 25791.78, filed on 2/15/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (54) U.S. patent application serial no. 10/078,928, attorney docket no. 25791.79, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (55) U.S. patent application serial no. 10/078,922, attorney docket no. 25791.80, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (56) U.S. patent application serial no. 10/078,921, attorney docket no. 25791.81, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (57) U.S. patent application serial no. 10/261,928, attorney

docket no. 25791.82, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (58) U.S. patent application serial no. 10/079,276, attorney docket no. 25791.83, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (59) U.S. patent application serial no. 10/262,009, attorney docket no. 25791.84, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (60) U.S. patent application serial no. 10/092,481, attorney docket no. 25791.85, filed on 3/7/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (61) U.S. patent application serial no. 10/261,926, attorney docket no. 25791.86, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (62) PCT application US 02/36157, filed on 11/12/02, attorney docket no. 25791.87.02, which claims priority from U.S. provisional patent application serial no. 60/338,996, attorney docket no. 25791.87, filed on 11/12/01, (63) PCT application US 02/36267, filed on 11/12/02, attorney docket no. 25791.88.02, which claims priority from U.S. provisional patent application serial no. 60/339,013, attorney docket no. 25791.88, filed on 11/12/01, (64) PCT application US 03/11765, filed on 4/16/03, attorney docket no. 25791.89.02, which claims priority from U.S. provisional patent application serial no. 60/383,917, attorney docket no. 25791.89, filed on 5/29/02, (65) PCT application US 03/15020, filed on 5/12/03, attorney docket no. 25791.90.02, which claims priority from U.S. provisional patent application serial no. 60/391,703, attorney docket no. 25791.90, filed on 6/26/02, (66) PCT application US 02/39418, filed on 12/10/02, attorney docket no. 25791.92.02, which claims priority from U.S. provisional patent application serial no. 60/346,309, attorney docket no. 25791.92, filed on 1/7/02, (67) PCT application US 03/06544, filed on 3/4/03, attorney docket no. 25791.93.02, which claims priority from U.S. provisional patent application serial no. 60/372,048, attorney docket no. 25791.93, filed on 4/12/02, (68) U.S. patent application serial no. 10/331,718, attorney docket no. 25791.94, filed on 12/30/02, which is a divisional U.S. patent application serial no. 09/679,906, filed on 10/5/00, attorney docket no. 25791.37.02, which claims priority from provisional patent

application serial no. 60/159,033, attorney docket no. 25791.37, filed on 10/12/1999, (69) PCT application US 03/04837, filed on 2/29/03, attorney docket no. 25791.95.02, which claims priority from U.S. provisional patent application serial no. 60/363,829, attorney docket no. 25791.95, filed on 3/13/02, (70) U.S. patent application serial no. 10/261,927, attorney docket no. 25791.97, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (71) U.S. patent application serial no. 10/262,008, attorney docket no. 25791.98, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (72) U.S. patent application serial no. 10/261,925, attorney docket no. 25791.99, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (73) U.S. patent application serial no. 10/199,524, attorney docket no. 25791.100, filed on 7/19/02, which is a continuation of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (74) PCT application US 03/10144, filed on 3/28/03, attorney docket no. 25791.101.02, which claims priority from U.S. provisional patent application serial no. 60/372,632, attorney docket no. 25791.101, filed on 4/15/02, (75) U.S. provisional patent application serial no. 60/412,542, attorney docket no. 25791.102, filed on 9/20/02, (76) PCT application US 03/14153, filed on 5/6/03, attorney docket no. 25791.104.02, which claims priority from U.S. provisional patent application serial no. 60/380,147, attorney docket no. 25791.104, filed on 5/6/02, (77) PCT application US 03/19993, filed on 6/24/03, attorney docket no. 25791.106.02, which claims priority from U.S. provisional patent application serial no. 60/397,284, attorney docket no. 25791.106, filed on 7/19/02, (78) PCT application US 03/13787, filed on 5/5/03, attorney docket no. 25791.107.02, which claims priority from U.S. provisional patent application serial no. 60/387,486, attorney docket no. 25791.107, filed on 6/10/02, (79) PCT application US 03/18530, filed on 6/11/03, attorney docket no. 25791.108.02, which claims priority from U.S. provisional patent application serial no. 60/387,961, attorney docket no. 25791.108, filed on 6/12/02, (80) PCT application US 03/20694, filed on 7/1/03, attorney docket no. 25791.110.02, which claims priority from U.S. provisional patent application serial no. 60/398,061, attorney docket no. 25791.110, filed on 7/24/02, (81) PCT application US 03/20870, filed on 7/2/03, attorney docket no. 25791.111.02, which claims priority from U.S.

provisional patent application serial no. 60/399,240, attorney docket no. 25791.111, filed on 7/29/02, (82) U.S. provisional patent application serial no. 60/412,487, attorney docket no. 25791.112, filed on 9/20/02, (83) U.S. provisional patent application serial no. 60/412,488, attorney docket no. 25791.114, filed on 9/20/02, (84) U.S. patent application serial no. 10/280,356, attorney docket no. 25791.115, filed on 10/25/02, which is a continuation of U.S. patent number 6,470,966, which was filed as patent application serial number 09/850,093, filed on 5/7/01, attorney docket no. 25791.55, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (85) U.S. provisional patent application serial no. 60/412,177, attorney docket no. 25791.117, filed on 9/20/02, (86) U.S. provisional patent application serial no. 60/412,653, attorney docket no. 25791.118, filed on 9/20/02, (87) U.S. provisional patent application serial no. 60/405,610, attorney docket no. 25791.119, filed on 8/23/02, (88) U.S. provisional patent application serial no. 60/405,394, attorney docket no. 25791.120, filed on 8/23/02, (89) U.S. provisional patent application serial no. 60/412,544, attorney docket no. 25791.121, filed on 9/20/02, (90) PCT application US 03/24779, filed on 8/8/03, attorney docket no. 25791.125.02, which claims priority from U.S. provisional patent application serial no. 60/407,442, attorney docket no. 25791.125, filed on 8/30/02, (91) U.S. provisional patent application serial no. 60/423,363, attorney docket no. 25791.126, filed on 12/10/02, (92) U.S. provisional patent application serial no. 60/412,196, attorney docket no. 25791.127, filed on 9/20/02, (93) U.S. provisional patent application serial no. 60/412,187, attorney docket no. 25791.128, filed on 9/20/02, (94) U.S. provisional patent application serial no. 60/412,371, attorney docket no. 25791.129, filed on 9/20/02, (95) U.S. patent application serial no. 10/382,325, attorney docket no. 25791.145, filed on 3/5/03, which is a continuation of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (96) U.S. patent application serial no. 10/624,842, attorney docket no. 25791.151, filed on 7/22/03, which is a divisional of U.S. patent application serial no. 09/502,350, attorney docket no. 25791.8.02, filed on 2/10/2000, which claims priority from provisional application 60/119,611, filed on 2/11/99, (97) U.S. provisional patent application serial no. 60/431,184, attorney docket no. 25791.157, filed on 12/5/02, (98) U.S. provisional patent application serial no. 60/448,526, attorney docket no. 25791.185, filed on 2/18/03, (99) U.S. provisional patent application serial no. 60/461,539, attorney docket no. 25791.186, filed on 4/9/03, (100) U.S. provisional patent application serial no. 60/462,750, attorney docket no. 25791.193, filed on 4/14/03, (101) U.S. provisional patent application serial no. 60/436,106, attorney docket no.

25791.200, filed on 12/23/02, (102) U.S. provisional patent application serial no. 60/442,942, attorney docket no. 25791.213, filed on 1/27/03, (103) U.S. provisional patent application serial no. 60/442,938, attorney docket no. 25791.225, filed on 1/27/03, (104) U.S. provisional patent application serial no. 60/418,687, attorney docket no. 25791.228, filed on 4/18/03, (105) U.S. provisional patent application serial no. 60/454,896, attorney docket no. 25791.236, filed on 3/14/03, (106) U.S. provisional patent application serial no. 60/450,504, attorney docket no. 25791.238, filed on 2/26/03, (107) U.S. provisional patent application serial no. 60/451,152, attorney docket no. 25791.239, filed on 3/9/03, (108) U.S. provisional patent application serial no. 60/455,124, attorney docket no. 25791.241, filed on 3/17/03, (109) U.S. provisional patent application serial no. 60/453,678, attorney docket no. 25791.253, filed on 3/11/03, (110) U.S. patent application serial no. 10/421,682, attorney docket no. 25791.256, filed on 4/23/03, which is a continuation of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (111) U.S. provisional patent application serial no. 60/457,965, attorney docket no. 25791.260, filed on 3/27/03, (112) U.S. provisional patent application serial no. 60/455,718, attorney docket no. 25791.262, filed on 3/18/03, (113) U.S. patent number 6,550,821, which was filed as patent application serial no. 09/811,734, filed on 3/19/01, (114) U.S. patent application serial no. 10/436,467, attorney docket no. 25791.268, filed on 5/12/03, which is a continuation of U.S. patent number 6,604,763, which was filed as application serial no. 09/559,122, attorney docket no. 25791.23.02, filed on 4/26/2000, which claims priority from provisional application 60/131,106, filed on 4/26/99, (115) U.S. provisional patent application serial no. 60/459,776, attorney docket no. 25791.270, filed on 4/2/03, (116) U.S. provisional patent application serial no. 60/461,094, attorney docket no. 25791.272, filed on 4/8/03, (117) U.S. provisional patent application serial no. 60/461,038, attorney docket no. 25791.273, filed on 4/7/03, (118) U.S. provisional patent application serial no. 60/463,586, attorney docket no. 25791.277, filed on 4/17/03, (119) U.S. provisional patent application serial no. 60/472,240, attorney docket no. 25791.286, filed on 5/20/03, (120) U.S. patent application serial no. 10/619,285, attorney docket no. 25791.292, filed on 7/14/03, which is a continuation-in-part of U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001, (now U.S. Patent 6,634,431 which issued 10/21/2003), which is a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (121) U.S. utility patent application serial no. 10/418,688, attorney docket no. 25791.257, which was filed on 4/18/03, as a division of U.S. utility patent application

serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99; (122) PCT patent application serial no. PCT/US2004/06246, attorney docket no. 25791.238.02, filed on 2/26/2004; (123) PCT patent application serial number PCT/US2004/08170, attorney docket number 25791.40.02, filed on 3/15/04; (124) PCT patent application serial number PCT/US2004/08171, attorney docket number 25791.236.02, filed on 3/15/04; (125) PCT patent application serial number PCT/US2004/08073, attorney docket number 25791.262.02, filed on 3/18/04; (126) PCT patent application serial number PCT/US2004/07711, attorney docket number 25791.253.02, filed on 3/11/2004; (127) PCT patent application serial number PCT/US2004/029025, attorney docket number 25791.260.02, filed on 3/26/2004; (128) PCT patent application serial number PCT/US2004/010317, attorney docket number 25791.270.02, filed on 4/2/2004; (129) PCT patent application serial number PCT/US2004/010712, attorney docket number 25791.272.02, filed on 4/6/2004; (130) PCT patent application serial number PCT/US2004/010762, attorney docket number 25791.273.02, filed on 4/6/2004; (131) PCT patent application serial number PCT/US2004/011973, attorney docket number 25791.277.02, filed on 4/15/2004; (132) U.S. provisional patent application serial number 60/495056, attorney docket number 25791.301, filed on 8/14/2003; (133) U.S. provisional patent application serial number 60/600679, attorney docket number 25791.194, filed on 8/11/2004; (134) PCT patent application serial number PCT/US2005/027318, attorney docket number 25791.329.02, filed on 7/29/2005; (135) PCT patent application serial number PCT/US2005/028936, attorney docket number 25791.338.02, filed on 8/12/2005; (136) PCT patent application serial number PCT/US2005/028669, attorney docket number 25791.194.02, filed on 8/11/2005; (137) PCT patent application serial number PCT/US2005/028453, attorney docket number 25791.371, filed on 8/11/2005; (138) PCT patent application serial number PCT/US2005/028641, attorney docket number 25791.372, filed on 8/11/2005; (139) PCT patent application serial number PCT/US2005/028819, attorney docket number 25791.373, filed on 8/11/2005; (140) PCT patent application serial number PCT/US2005/028446, attorney docket number 25791.374, filed on 8/11/2005; (141) PCT patent application serial number PCT/US2005/028642, attorney docket number 25791.375, filed on 8/11/2005; (142) PCT patent application serial number PCT/US2005/028451, attorney docket number 25791.376, filed on 8/11/2005, and (143). PCT patent application serial number PCT/US2005/028473, attorney docket number 25791.377, filed on 8/11/2005, (144) U.S. utility patent application serial number 10/546082, attorney docket number 25791.378, filed on 8/16/2005, (145) U.S. utility patent application serial number 10/546076, attorney docket number 25791.379, filed

on 8/16/2005, (146) U.S. utility patent application serial number 10/545936, attorney docket number 25791.380, filed on 8/16/2005, (147) U.S. utility patent application serial number 10/546079, attorney docket number 25791.381, filed on 8/16/2005 (148) U.S. utility patent application serial number 10/545941, attorney docket number 25791.382, filed on 8/16/2005, (149) U.S. utility patent application serial number 546078, attorney docket number 25791.383, filed on 8/16/2005, filed on 8/11/2005., (150) U.S. utility patent application serial number 10/545941, attorney docket number 25791.185.05, filed on 8/16/2005, (151) U.S. utility patent application serial number 11/249967, attorney docket number 25791.384, filed on 10/13//2005, (152) U.S. provisional patent application serial number 60/734302, attorney docket number 25791.24, filed on 11/7/2005, (153) U.S. provisional patent application serial number 60/725181, attorney docket number 25791.184, filed on 10/11/2005, (154) PCT patent application serial number PCT/US2005/023391, attorney docket number 25791.299.02 filed 6/29/2005 which claims priority from U.S. provisional patent application serial number 60/585370, attorney docket number 25791.299, filed on 7/2/2004, (155) U.S. provisional patent application serial number 60/721579, attorney docket number 25791.327, filed on 9/28/2005, (156) U.S. provisional patent application serial number 60/717391, attorney docket number 25791.214, filed on 9/15/2005, (157) U.S. provisional patent application serial number 60/702935, attorney docket number 25791.133, filed on 7/27/2005, (158) U.S. provisional patent application serial number 60/663913, attorney docket number 25791.32, filed on 3/21/2005, (159) U.S. provisional patent application serial number 60/652564, attorney docket number 25791.348, filed on 2/14/2005, (160) U.S. provisional patent application serial number 60/645840, attorney docket number 25791.324, filed on 1/21/2005, (161) PCT patent application serial number PCT/US2005/_____, attorney docket number 25791.326.02, filed on 11/29/2005 which claims priority from U.S. provisional patent application serial number 60/631703, attorney docket number 25791.326, filed on 11/30/2004, and (162) U.S. provisional patent application serial number _____, attorney docket number 25791.339, filed on 12/22/2005, the disclosures of which are incorporated herein by reference.

BACKGROUND

[0004] The disclosures herein relate generally to wellbore casings, and in particular to wellbore casings that are formed using expandable tubing expandable tubulars.

[0005] Conventionally, when a wellbore is created, a number of casings are installed in the borehole to prevent collapse of the borehole wall and to prevent undesired outflow of drilling fluid into the formation or inflow of fluid from the formation into the borehole. The borehole is drilled in intervals whereby a casing which is to be installed in a lower borehole interval is lowered through a previously installed casing of an upper borehole interval. As a

consequence of this procedure the casing of the lower interval is of smaller diameter than the casing of the upper interval. Thus, the casings are in a nested arrangement with casing diameters decreasing in downward direction. Cement annuli are provided between the outer surfaces of the casings and the borehole wall to seal the casings from the borehole wall. As a consequence of this nested arrangement a relatively large borehole diameter is required at the upper part of the wellbore. Such a large borehole diameter involves increased costs due to heavy casing handling equipment, large drill bits and increased volumes of drilling fluid and drill cuttings. Moreover, increased drilling rig time is involved due to required cement pumping, cement hardening, required equipment changes due to large variations in hole diameters drilled in the course of the well, and the large volume of cuttings drilled and removed.

[0006] The present disclosure is directed to overcoming one or more of the limitations of the existing procedures for forming new sections of casing in a wellbore.

SUMMARY

[0007] According to one aspect of the present disclosure, a method of forming a wellbore casing is provided that includes installing a tubular liner and a mandrel in the borehole, injecting fluidic material into the borehole, and radially expanding the liner in the borehole by extruding the liner off of the mandrel.

[0008] According to another aspect of the present disclosure, a method of forming a wellbore casing is provided that includes drilling out a new section of the borehole adjacent to the already existing casing. A tubular liner and a mandrel are then placed into the new section of the borehole with the tubular liner overlapping an already existing casing. A hardenable fluidic sealing material is injected into an annular region between the tubular liner and the new section of the borehole. The annular region between the tubular liner and the new section of the borehole is then fluidically isolated from an interior region of the tubular liner below the mandrel. A non hardenable fluidic material is then injected into the interior region of the tubular liner below the mandrel. The tubular liner is extruded off of the mandrel. The overlap between the tubular liner and the already existing casing is sealed. The tubular liner is supported by overlap with the already existing casing. The mandrel is removed from the borehole. The integrity of the seal of the overlap between the tubular liner and the already existing casing is tested. At least a portion of the second quantity of the hardenable fluidic sealing material is removed from the interior of the tubular liner. The remaining portions of the fluidic hardenable fluidic sealing material are cured. At least a portion of cured fluidic hardenable sealing material within the tubular liner is removed.

[0009] According to another aspect of the present disclosure, an apparatus for expanding a tubular member is provided that includes a support member, a mandrel, a

tubular member, and a shoe. The support member includes a first fluid passage. The mandrel is coupled to the support member and includes a second fluid passage. The tubular member is coupled to the mandrel. The shoe is coupled to the tubular liner and includes a third fluid passage. The first, second and third fluid passages are operably coupled.

[00010] According to another aspect of the present disclosure, an apparatus for expanding a tubular member is provided that includes a support member, an expandable mandrel, a tubular member, a shoe, and at least one sealing member. The support member includes a first fluid passage, a second fluid passage, and a flow control valve coupled to the first and second fluid passages. The expandable mandrel is coupled to the support member and includes a third fluid passage. The tubular member is coupled to the mandrel and includes one or more sealing elements. The shoe is coupled to the tubular member and includes a fourth fluid passage. The at least one sealing member is adapted to prevent the entry of foreign material into an interior region of the tubular member.

[00011] According to another aspect of the present disclosure, a method of joining a second tubular member to a first tubular member, the first tubular member having an inner diameter greater than an outer diameter of the second tubular member, is provided that includes positioning a mandrel within an interior region of the second tubular member. A portion of an interior region of the second tubular member is pressurized and the second tubular member is extruded off of the mandrel into engagement with the first tubular member.

[00012] According to another aspect of the present disclosure, a tubular liner is provided that includes an annular member having one or more sealing members at an end portion of the annular member, and one or more pressure relief passages at an end portion of the annular member.

[00013] According to another aspect of the present disclosure, a wellbore casing is provided that includes a tubular liner and an annular body of a cured fluidic sealing material. The tubular liner is formed by the process of extruding the tubular liner off of a mandrel.

[00014] According to another aspect of the present disclosure, a tie-back liner for lining an existing wellbore casing is provided that includes a tubular liner and an annular body of cured fluidic sealing material. The tubular liner is formed by the process of extruding the tubular liner off of a mandrel. The annular body of a cured fluidic sealing material is coupled to the tubular liner.

[00015] According to another aspect of the present disclosure, an apparatus for expanding a tubular member is provided that includes a support member, a mandrel, a tubular member and a shoe. The support member includes a first fluid passage. The mandrel is coupled to the support member. The mandrel includes a second fluid passage

operably coupled to the first fluid passage, an interior portion, and an exterior portion. The interior portion of the mandrel is drillable. The tubular member is coupled to the mandrel. The shoe is coupled to the tubular member. The shoe includes a third fluid passage operably coupled to the second fluid passage, an interior portion, and an exterior portion. The interior portion of the shoe is drillable.

[00016] According to another aspect of the present disclosure, an expansion apparatus is provided that includes an elongated base member comprising a first end, a second end opposite the first end, and an expansion member comprising an expansion diameter and extending from the base member between the first and second end, and a first sealing member coupled to the base member and extending out past the first end of the base member, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter.

[00017] According to another aspect of the present disclosure, an expandable tubular member is provided that includes a tubular member comprising an initial diameter, and an expansion apparatus positioned in the tubular member, the expansion apparatus including an elongated base member comprising a first end, a second end opposite the first end, and an expansion member comprising an expansion diameter and extending from the base member between the first and second end, and a first sealing member coupled to the base member and extending out past the first end of the base member, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter.

[00018] According to another aspect of the present disclosure, an expansion apparatus is provided that includes an elongated base member comprising a first end and a second end opposite the first end, means for expanding a tubular member extending from the base member between the first and second end, and first means for providing a seal, the first means for providing a seal extending out past the first end of the base member.

[00019] According to another aspect of the present disclosure, a method for expanding a tubular member is provided that includes providing a tubular member, positioning an expansion apparatus in the tubular member, the expansion apparatus comprising a first end, a second end opposite the first end, and a first sealing member extending out past the first end of the expansion apparatus, sealing the expansion apparatus with the tubular member, whereby the sealing comprises deflecting a portion of the first sealing member around the first end of the expansion apparatus by the tubular member, and expanding the tubular member by moving the expansion apparatus axially through the tubular member.

[00020] According to another aspect of the present disclosure, an expansion apparatus is provided that includes a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing volume defined by the base

member and adjacent the first end of the base member, an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter, and a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

[00021] According to another aspect of the present disclosure, an expansion apparatus is provided that includes a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing volume defined by the base member and adjacent the first end of the base member, a second sealing volume defined by the base member and adjacent the second end of the base member, an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter, a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions, and a substantially tubular second sealing member coupled to the base member and extending out past the second end, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter and operable to deflect around the second end of the base member and partially into the second sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

[00022] According to another aspect of the present disclosure, an expandable tubular member is provided that includes a tubular member comprising an initial diameter, and an expansion apparatus positioned in the tubular member, the expansion apparatus including a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing volume defined by the base member and tubular member and adjacent the first end of the base member, an expansion member extending

from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter and operable to expand the tubular member from the initial diameter to a diameter which is substantially equal to the expansion diameter, and a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

[00023] According to another aspect of the present disclosure, an expandable tubular member is provided that includes a tubular member comprising an initial diameter, and an expansion apparatus positioned in the tubular member, the expansion apparatus including a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing volume defined by the base member and tubular member and adjacent the first end of the base member, a second sealing volume defined by the base member and tubular member and adjacent the second end of the base member, an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter and operable to expand the tubular member from the initial diameter to a diameter which is substantially equal to the expansion diameter, a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions, and a substantially tubular second sealing member coupled to the base member and extending out past the second end, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter and operable to deflect around the second end of the base member and partially into the second sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

BRIEF DESCRIPTION OF THE DRAWINGS

[00024] Fig. 1 is a fragmentary cross-sectional view illustrating an exemplary embodiment of the drilling of a new section of a well borehole.

[00025] Fig. 2 is a fragmentary cross-sectional view illustrating an exemplary embodiment of the placement of an embodiment of an apparatus for creating a casing within the new section of the well borehole.

[00026] Fig. 3 is a fragmentary cross-sectional view illustrating an exemplary embodiment of the injection of a first quantity of a hardenable fluidic sealing material into the new section of the well borehole.

[00027] Fig. 3a is another fragmentary cross-sectional view illustrating an exemplary embodiment of the injection of a first quantity of a hardenable fluidic sealing material into the new section of the well borehole.

[00028] Fig. 4 is a fragmentary cross-sectional view illustrating an exemplary embodiment of the injection of a second quantity of a hardenable fluidic sealing material into the new section of the well borehole.

[00029] Fig. 5 is a fragmentary cross-sectional view illustrating an exemplary embodiment of the drilling out of a portion of the cured hardenable fluidic sealing material from the new section of the well borehole.

[00030] Fig. 6 is a cross-sectional view illustrating an exemplary embodiment of the overlapping joint between adjacent tubular members.

[00031] Fig. 7 is a fragmentary cross-sectional view illustrating a preferred embodiment of the apparatus for creating a casing within a well borehole.

[00032] Fig. 8 is a fragmentary cross-sectional view illustrating an exemplary embodiment of the placement of an expanded tubular member within another tubular member.

[00033] Fig. 9 is a cross-sectional view illustrating a preferred embodiment of an apparatus for forming a casing including a drillable mandrel and shoe.

[00034] Fig. 9a is another cross-sectional view illustrating an exemplary embodiment of the apparatus of Fig. 9.

[00035] Fig. 9b is another cross-sectional view illustrating an exemplary embodiment of the apparatus of Fig. 9.

[00036] Fig. 9c is another cross-sectional view illustrating an exemplary embodiment of the apparatus of Fig. 9.

[00037] Fig. 10a is a cross-sectional view illustrating an exemplary embodiment of a wellbore including a pair of adjacent overlapping casings.

[00038] Fig. 10b is a cross-sectional view illustrating an exemplary embodiment of an apparatus and method for creating a tie-back liner using an expandable tubular member.

[00039] Fig. 10c is a cross-sectional view illustrating an exemplary embodiment of the pumping of a fluidic sealing material into the annular region between the tubular member and the existing casing.

[00040] Fig. 10d is a cross-sectional view illustrating an exemplary embodiment of the pressurizing of the interior of the tubular member below the mandrel.

[00041] Fig. 10e is a cross-sectional view illustrating an exemplary embodiment of the extrusion of the tubular member off of the mandrel.

[00042] Fig. 10f is a cross-sectional view illustrating an exemplary embodiment of the tie-back liner before drilling out the shoe and packer.

[00043] Fig. 10g is a cross-sectional view illustrating an exemplary embodiment of the completed tie-back liner created using an expandable tubular member.

[00044] Fig. 11a is a fragmentary cross-sectional view illustrating an exemplary embodiment of the drilling of a new section of a well borehole.

[00045] Fig. 11b is a fragmentary cross-sectional view illustrating an exemplary embodiment of the placement of an embodiment of an apparatus for hanging a tubular liner within the new section of the well borehole.

[00046] Fig. 11c is a fragmentary cross-sectional view illustrating an exemplary embodiment of the injection of a first quantity of a hardenable fluidic sealing material into the new section of the well borehole.

[00047] Fig. 11d is a fragmentary cross-sectional view illustrating an exemplary embodiment of the introduction of a wiper dart into the new section of the well borehole.

[00048] Fig. 11e is a fragmentary cross-sectional view illustrating an exemplary embodiment of the injection of a second quantity of a hardenable fluidic sealing material into the new section of the well borehole.

[00049] Fig. 11f is a fragmentary cross-sectional view illustrating an exemplary embodiment of the completion of the tubular liner.

[00050] Fig. 12a is a perspective view illustrating an exemplary embodiment of an expansion device.

[00051] Fig. 12b is a cross sectional view illustrating an exemplary embodiment of the expansion device of Fig. 1a.

[00052] Fig. 13a is a cut away perspective view illustrating an exemplary embodiment of a sealing member used with the expansion device of Fig. 1a.

[00053] Fig. 13b is a cross sectional view illustrating an exemplary embodiment of the sealing member of Fig. 2a.

[00054] Fig. 14 is a cross sectional view illustrating an exemplary embodiment of tubular member.

[00055] Fig. 15 is a cross sectional view illustrating an exemplary embodiment of an expansion apparatus including the expansion device of Fig. 1a and the sealing member of Fig. 2a.

[00056] Fig. 16a is a flow chart illustrating an exemplary embodiment of a method for expanding a tubular member.

[00057] Fig. 16b is a cross sectional view illustrating an exemplary embodiment of the expansion apparatus of Fig. 4 expanding the tubular member of Fig. 3 using the method of Fig. 5a.

[00058] Fig. 17a is a flow chart illustrating an exemplary embodiment of a method for expanding a tubular member.

[00059] Fig. 17b is a cross sectional view illustrating an exemplary embodiment of the expansion apparatus of Fig. 4 expanding the tubular member of Fig. 3 using the method of Fig. 6a.

[00060] Fig. 18a is a perspective view illustrating an exemplary embodiment of an expansion device.

[00061] Fig. 18b is a cross sectional view illustrating an exemplary embodiment of the expansion device of Fig. 7a.

[00062] Fig. 19 is a cross sectional view illustrating an exemplary embodiment of an expansion apparatus including a plurality of the sealing members of Fig. 2a and the expansion device of Fig. 7a.

[00063] Fig. 20a is a flow chart illustrating an exemplary embodiment of a method for expanding a tubular member.

[00064] Fig. 20b is a cross sectional view illustrating an exemplary embodiment of the expansion apparatus of Fig. 8 expanding the tubular member of Fig. 3 using the method of Fig. 9a.

DETAILED DESCRIPTION

[00065] An apparatus and method for forming a wellbore casing within a subterranean formation is provided. The apparatus and method permits a wellbore casing to be formed in a subterranean formation by placing a tubular member and a mandrel in a new section of a wellbore, and then extruding the tubular member off of the mandrel by pressurizing an interior portion of the tubular member. The apparatus and method further permits adjacent tubular members in the wellbore to be joined using an overlapping joint that prevents fluid and or gas passage. The apparatus and method further permits a new tubular member to be supported by an existing tubular member by expanding the new tubular member into engagement with the existing tubular member. The apparatus and method further minimizes

the reduction in the hole size of the wellbore casing necessitated by the addition of new sections of wellbore casing.

[00066] An apparatus and method for forming a tie-back liner using an expandable tubular member is also provided. The apparatus and method permits a tie-back liner to be created by extruding a tubular member off of a mandrel by pressurizing an interior portion of the tubular member. In this manner, a tie-back liner is produced. The apparatus and method further permits adjacent tubular members in the wellbore to be joined using an overlapping joint that prevents fluid and/or gas passage. The apparatus and method further permits a new tubular member to be supported by an existing tubular member by expanding the new tubular member into engagement with the existing tubular member.

[00067] An apparatus and method for expanding a tubular member is also provided that includes an expandable tubular member, mandrel and a shoe. In a preferred embodiment, the interior portions of the apparatus is composed of materials that permit the interior portions to be removed using a conventional drilling apparatus. In this manner, in the event of a malfunction in a downhole region, the apparatus may be easily removed.

[00068] An apparatus and method for hanging an expandable tubular liner in a wellbore is also provided. The apparatus and method permit a tubular liner to be attached to an existing section of casing. The apparatus and method further have application to the joining of tubular members in general.

[00069] Referring initially to Figs. 1-5, an embodiment of an apparatus and method for forming a wellbore casing within a subterranean formation will now be described. As illustrated in Fig. 1, a wellbore 100 is positioned in a subterranean formation 105. The wellbore 100 includes an existing cased section 110 having a tubular casing 115 and an annular outer layer of cement 120.

[00070] In order to extend the wellbore 100 into the subterranean formation 105, a drill string 125 is used in a well known manner to drill out material from the subterranean formation 105 to form a new section 130.

[00071] As illustrated in Fig. 2, an apparatus 200 for forming a wellbore casing in a subterranean formation is then positioned in the new section 130 of the wellbore 100. The apparatus 200 preferably includes an expandable mandrel or pig 205, a tubular member 210, a shoe 215, a lower cup seal 220, an upper cup seal 225, a fluid passage 230, a fluid passage 235, a fluid passage 240, seals 245, and a support member 250.

[00072] The expandable mandrel 205 is coupled to and supported by the support member 250. The expandable mandrel 205 is preferably adapted to controllably expand in a radial direction. The expandable mandrel 205 may comprise any number of conventional commercially available expandable mandrels modified in accordance with the teachings of

the present disclosure. In a preferred embodiment, the expandable mandrel 205 comprises a hydraulic expansion tool as disclosed in U.S. Patent No. 5,348,095, the contents of which are incorporated herein by reference, modified in accordance with the teachings of the present disclosure.

[00073] The tubular member 210 is supported by the expandable mandrel 205. The tubular member 210 is expanded in the radial direction and extruded off of the expandable mandrel 205. The tubular member 210 may be fabricated from any number of conventional commercially available materials such as, for example, Oilfield Country Tubular Goods (OCTG), 13 chromium steel tubing/casing, or plastic tubing/casing. In a preferred embodiment, the tubular member 210 is fabricated from OCTG in order to maximize strength after expansion. The inner and outer diameters of the tubular member 210 may range, for example, from approximately 0.75 to 47 inches and 1.05 to 48 inches, respectively. In a preferred embodiment, the inner and outer diameters of the tubular member 210 range from about 3 to 15.5 inches and 3.5 to 16 inches, respectively in order to optimally provide minimal telescoping effect in the most commonly drilled wellbore sizes. The tubular member 210 preferably comprises a solid member.

[00074] In a preferred embodiment, the end portion 260 of the tubular member 210 is slotted, perforated, or otherwise modified to catch or slow down the mandrel 205 when it completes the extrusion of tubular member 210. In a preferred embodiment, the length of the tubular member 210 is limited to minimize the possibility of buckling. For typical tubular member 210 materials, the length of the tubular member 210 is preferably limited to between about 40 to 20,000 feet in length.

[00075] The shoe 215 is coupled to the expandable mandrel 205 and the tubular member 210. The shoe 215 includes fluid passage 240. The shoe 215 may comprise any number of conventional commercially available shoes such as, for example, Super Seal II float shoe, Super Seal II Down-Jet float shoe or a guide shoe with a sealing sleeve for a latch down plug modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the shoe 215 comprises an aluminum down-jet guide shoe with a sealing sleeve for a latch-down plug available from Halliburton Energy Services in Dallas, TX, modified in accordance with the teachings of the present disclosure, in order to optimally guide the tubular member 210 in the wellbore, optimally provide an adequate seal between the interior and exterior diameters of the overlapping joint between the tubular members, and to optimally allow the complete drill out of the shoe and plug after the completion of the cementing and expansion operations.

[00076] In a preferred embodiment, the shoe 215 includes one or more through and side outlet ports in fluidic communication with the fluid passage 240. In this manner, the shoe

215 optimally injects hardenable fluidic sealing material into the region outside the shoe 215 and tubular member 210. In a preferred embodiment, the shoe 215 includes the fluid passage 240 having an inlet geometry that can receive a dart and/or a ball sealing member. In this manner, the fluid passage 240 can be optimally sealed off by introducing a plug, dart and/or ball sealing elements into the fluid passage 230.

[00077] The lower cup seal 220 is coupled to and supported by the support member 250. The lower cup seal 220 prevents foreign materials from entering the interior region of the tubular member 210 adjacent to the expandable mandrel 205. The lower cup seal 220 may comprise any number of conventional commercially available cup seals such as, for example, TP cups, or Selective Injection Packer (SIP) cups modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the lower cup seal 220 comprises a SIP cup seal, available from Halliburton Energy Services in Dallas, TX in order to optimally block foreign material and contain a body of lubricant.

[00078] The upper cup seal 225 is coupled to and supported by the support member 250. The upper cup seal 225 prevents foreign materials from entering the interior region of the tubular member 210. The upper cup seal 225 may comprise any number of conventional commercially available cup seals such as, for example, TP cups or SIP cups modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the upper cup seal 225 comprises a SIP cup, available from Halliburton Energy Services in Dallas, TX in order to optimally block the entry of foreign materials and contain a body of lubricant.

[00079] The fluid passage 230 permits fluidic materials to be transported to and from the interior region of the tubular member 210 below the expandable mandrel 205. The fluid passage 230 is coupled to and positioned within the support member 250 and the expandable mandrel 205. The fluid passage 230 preferably extends from a position adjacent to the surface to the bottom of the expandable mandrel 205. The fluid passage 230 is preferably positioned along a centerline of the apparatus 200.

[00080] The fluid passage 230 is preferably selected, in the casing running mode of operation, to transport materials such as drilling mud or formation fluids at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to minimize drag on the tubular member being run and to minimize surge pressures exerted on the wellbore which could cause a loss of wellbore fluids and lead to hole collapse.

[00081] The fluid passage 235 permits fluidic materials to be released from the fluid passage 230. In this manner, during placement of the apparatus 200 within the new section 130 of the wellbore 100, fluidic materials 255 forced up the fluid passage 230 can be released into the wellbore 100 above the tubular member 210 thereby minimizing surge

pressures on the wellbore section 130. The fluid passage 235 is coupled to and positioned within the support member 250. The fluid passage is further fluidically coupled to the fluid passage 230.

[00082] The fluid passage 235 preferably includes a control valve for controllably opening and closing the fluid passage 235. In a preferred embodiment, the control valve is pressure activated in order to controllably minimize surge pressures. The fluid passage 235 is preferably positioned substantially orthogonal to the centerline of the apparatus 200.

[00083] The fluid passage 235 is preferably selected to convey fluidic materials at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to reduce the drag on the apparatus 200 during Insertion into the new section 130 of the wellbore 100 and to minimize surge pressures on the new wellbore section 130.

[00084] The fluid passage 240 permits fluidic materials to be transported to and from the region exterior to the tubular member 210 and shoe 215. The fluid passage 240 is coupled to and positioned within the shoe 215 in fluidic communication with the interior region of the tubular member 210 below the expandable mandrel 205. The fluid passage 240 preferably has a cross-sectional shape that permits a plug, or other similar device, to be placed in fluid passage 240 to thereby block further passage of fluidic materials. In this manner, the interior region of the tubular member 210 below the expandable mandrel 205 can be fluidically isolated from the region exterior to the tubular member 210. This permits the interior region of the tubular member 210 below the expandable mandrel 205 to be pressurized. The fluid passage 240 is preferably positioned substantially along the centerline of the apparatus 200.

[00085] The fluid passage 240 is preferably selected to convey materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to optimally fill the annular region between the tubular member 210 and the new section 130 of the wellbore 100 with fluidic materials. In a preferred embodiment, the fluid passage 240 includes an inlet geometry that can receive a dart and/or a ball sealing member. In this manner, the fluid passage 240 can be sealed off by introducing a plug, dart and/or ball sealing elements into the fluid passage 230.

[00086] The seals 245 are coupled to and supported by an end portion 260 of the tubular member 210. The seals 245 are further positioned on an outer surface 265 of the end portion 260 of the tubular member 210. The seals 245 permit the overlapping joint between the end portion 270 of the casing 115 and the portion 260 of the tubular member 210 to be fluidically sealed. The seals 245 may comprise any number of conventional commercially available seals such as, for example, lead, rubber, Teflon, or epoxy seals modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the seals 245 are molded from Stratalock epoxy available from Halliburton Energy Services in

Dallas, TX in order to optimally provide a load bearing interference fit between the end 260 of the tubular member 210 and the end 270 of the existing casing 115.

[00087] In a preferred embodiment, the seals 245 are selected to optimally provide a sufficient frictional force to support the expanded tubular member 210 from the existing casing 115. In a preferred embodiment, the frictional force optimally provided by the seals 245 ranges from about 1,000 to 1,000,000 lbf in order to optimally support the expanded tubular member 210.

[00088] The support member 250 is coupled to the expandable mandrel 205, tubular member 210, shoe 215, and seals 220 and 225. The support member 250 preferably comprises an annular member having sufficient strength to carry the apparatus 200 into the new section 130 of the wellbore 100. In a preferred embodiment, the support member 250 further includes one or more conventional centralizers (not illustrated) to help stabilize the apparatus 200.

[00089] In a preferred embodiment, a quantity of lubricant 275 is provided in the annular region above the expandable mandrel 205 within the interior of the tubular member 210. In this manner, the extrusion of the tubular member 210 off of the expandable mandrel 205 is facilitated. The lubricant 275 may comprise any number of conventional commercially available lubricants such as, for example, Lubriplate, chlorine based lubricants, oil based lubricants or Climax 1500 Antisieze (3100). In a preferred embodiment, the lubricant 275 comprises Climax 1500 Antisieze (3100) available from Climax Lubricants and Equipment Co. in Houston, TX in order to optimally provide optimum lubrication to facilitate the expansion process.

[00090] In a preferred embodiment, the support member 250 is thoroughly cleaned prior to assembly to the remaining portions of the apparatus 200. In this manner, the introduction of foreign material into the apparatus 200 is minimized. This minimizes the possibility of foreign material clogging the various flow passages and valves of the apparatus 200.

[00091] In a preferred embodiment, before or after positioning the apparatus 200 within the new section 130 of the wellbore 100, a couple of wellbore volumes are circulated in order to ensure that no foreign materials are located within the wellbore 100 that might clog up the various flow passages and valves of the apparatus 200 and to ensure that no foreign material interferes with the expansion process.

[00092] As illustrated in Fig. 3, the fluid passage 235 is then closed and a hardenable fluidic sealing material 305 is then pumped from a surface location into the fluid passage 230. The material 305 then passes from the fluid passage 230 into the interior region 310 of the tubular member 210 below the expandable mandrel 205. The material 305 then passes from the interior region 310 into the fluid passage 240. The material 305 then exits the

apparatus 200 and fills the annular region 315 between the exterior of the tubular member 210 and the interior wall of the new section 130 of the wellbore 100. Continued pumping of the material 305 causes the material 305 to fill up at least a portion of the annular region 315.

[00093] The material 305 is preferably pumped into the annular region 315 at pressures and flow rates ranging, for example, from about 0 to 5000 psi and 0 to 1,500 gallons/min, respectively. The optimum flow rate and operating pressures vary as a function of the casing and wellbore sizes, wellbore section length, available pumping equipment, and fluid properties of the fluidic material being pumped. The optimum flow rate and operating pressure are preferably determined using conventional empirical methods.

[00094] The hardenable fluidic sealing material 305 may comprise any number of conventional commercially available hardenable fluidic sealing materials such as, for example, slag mix, cement or epoxy. In a preferred embodiment, the hardenable fluidic sealing material 305 comprises a blended cement prepared specifically for the particular well section being drilled from Halliburton Energy Services in Dallas, TX in order to provide optimal support for tubular member 210 while also maintaining optimum flow characteristics so as to minimize difficulties during the displacement of cement in the annular region 315. The optimum blend of the blended cement is preferably determined using conventional empirical methods.

[00095] The annular region 315 preferably is filled with the material 305 in sufficient quantities to ensure that, upon radial expansion of the tubular member 210, the annular region 315 of the new section 130 of the wellbore 100 will be filled with material 305.

[00096] In a particularly preferred embodiment, as illustrated in Fig. 3a, the wall thickness and/or the outer diameter of the tubular member 210 is reduced in the region adjacent to the mandrel 205 in order optimally permit placement of the apparatus 200 in positions in the wellbore with tight clearances. Furthermore, in this manner, the initiation of the radial expansion of the tubular member 210 during the extrusion process is optimally facilitated.

[00097] As illustrated in Fig. 4, once the annular region 315 has been adequately filled with material 305, a plug 405, or other similar device, is introduced into the fluid passage 240 thereby fluidically isolating the interior region 310 from the annular region 315. In a preferred embodiment, a non-hardenable fluidic material 306 is then pumped into the interior region 310 causing the interior region to pressurize. In this manner, the interior of the expanded tubular member 210 will not contain significant amounts of cured material 305. This reduces and simplifies the cost of the entire process. Alternatively, the material 305 may be used during this phase of the process.

[00098] Once the interior region 310 becomes sufficiently pressurized, the tubular member 210 is extruded off of the expandable mandrel 205. During the extrusion process, the expandable mandrel 205 may be raised out of the expanded portion of the tubular member 210. In a preferred embodiment, during the extrusion process, the mandrel 205 is raised at approximately the same rate as the tubular member 210 is expanded in order to keep the tubular member 210 stationary relative to the new wellbore section 130. In an alternative preferred embodiment, the extrusion process is commenced with the tubular member 210 positioned above the bottom of the new wellbore section 130, keeping the mandrel 205 stationary, and allowing the tubular member 210 to extrude off of the mandrel 205 and fall down the new wellbore section 130 under the force of gravity.

[00099] The plug 405 is preferably placed into the fluid passage 240 by introducing the plug 405 into the fluid passage 230 at a surface location in a conventional manner. The plug 405 preferably acts to fluidically isolate the hardenable fluidic sealing material 305 from the non hardenable fluidic material 306.

[000100] The plug 405 may comprise any number of conventional commercially available devices from plugging a fluid passage such as, for example, Multiple Stage Cementer (MSC) latch-down plug, Omega latch-down plug or three-wiper latch-down plug modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the plug 405 comprises a MSC latch-down plug available from Halliburton Energy Services in Dallas, TX.

[000101] After placement of the plug 405 in the fluid passage 240, a non hardenable fluidic material 306 is preferably pumped into the interior region 310 at pressures and flow rates ranging, for example, from approximately 400 to 10,000 psi and 30 to 4,000 gallons/min. In this manner, the amount of hardenable fluidic sealing material within the interior 310 of the tubular member 210 is minimized. In a preferred embodiment, after placement of the plug 405 in the fluid passage 240, the non hardenable material 306 is preferably pumped into the interior region 310 at pressures and flow rates ranging from approximately 500 to 9,000 psi and 40 to 3,000 gallons/min in order to maximize the extrusion speed.

[000102] In a preferred embodiment, the apparatus 200 is adapted to minimize tensile, burst, and friction effects upon the tubular member 210 during the expansion process. These effects will be depend upon the geometry of the expansion mandrel 205, the material composition of the tubular member 210 and expansion mandrel 205, the inner diameter of the tubular member 210, the wall thickness of the tubular member 210, the type of lubricant, and the yield strength of the tubular member 210. In general, the thicker the wall thickness, the smaller the inner diameter, and the greater the yield strength of the tubular member 210,

then the greater the operating pressures required to extrude the tubular member 210 off of the mandrel 205.

[000103] For typical tubular members 210, the extrusion of the tubular member 210 off of the expandable mandrel will begin when the pressure of the interior region 310 reaches, for example, approximately 500 to 9,000 psi.

[000104] During the extrusion process, the expandable mandrel 205 may be raised out of the expanded portion of the tubular member 210 at rates ranging, for example, from about 0 to 5 ft/sec. In a preferred embodiment, during the extrusion process, the expandable mandrel 205 is raised out of the expanded portion of the tubular member 210 at rates ranging from about 0 to 2 ft/sec in order to minimize the time required for the expansion process while also permitting easy control of the expansion process.

[000105] When the end portion 260 of the tubular member 210 is extruded off of the expandable mandrel 205, the outer surface 265 of the end portion 260 of the tubular member 210 will preferably contact the interior surface 410 of the end portion 270 of the casing 115 to form an fluid tight overlapping joint. The contact pressure of the overlapping joint may range, for example, from approximately 50 to 20,000 psi. In a preferred embodiment, the contact pressure of the overlapping joint ranges from approximately 400 to 10,000 psi in order to provide optimum pressure to activate the annular sealing members 245 and optimally provide resistance to axial motion to accommodate typical tensile and compressive loads.

[000106] The overlapping joint between the section 410 of the existing casing 115 and the section 265 of the expanded tubular member 210 preferably provides a gaseous and fluidic seal. In a particularly preferred embodiment, the sealing members 245 optimally provide a fluidic and gaseous seal in the overlapping joint.

[000107] In a preferred embodiment, the operating pressure and flow rate of the non hardenable fluidic material 306 is controllably ramped down when the expandable mandrel 205 reaches the end portion 260 of the tubular member 210. In this manner, the sudden release of pressure caused by the complete extrusion of the tubular member 210 off of the expandable mandrel 205 can be minimized. In a preferred embodiment, the operating pressure is reduced in a substantially linear fashion from 100% to about 10% during the end of the extrusion process beginning when the mandrel 205 is within about 5 feet from completion of the extrusion process.

[000108] Alternatively, or in combination, a shock absorber is provided in the support member 250 in order to absorb the shock caused by the sudden release of pressure. The shock absorber may comprise, for example, any conventional commercially available shock absorber adapted for use in wellbore operations.

[000109] Alternatively, or in combination, a mandrel catching structure is provided in the end portion 260 of the tubular member 210 in order to catch or at least decelerate the mandrel 205.

[000110] Once the extrusion process is completed, the expandable mandrel 205 is removed from the wellbore 100. In a preferred embodiment, either before or after the removal of the expandable mandrel 205, the integrity of the fluidic seal of the overlapping joint between the upper portion 260 of the tubular member 210 and the lower portion 270 of the casing 115 is tested using conventional methods.

[000111] If the fluidic seal of the overlapping joint between the upper portion 260 of the tubular member 210 and the lower portion 270 of the casing 115 is satisfactory, then any uncured portion of the material 305 within the expanded tubular member 210 is then removed in a conventional manner such as, for example, circulating the uncured material out of the interior of the expanded tubular member 210. The mandrel 205 is then pulled out of the wellbore section 130 and a drill bit or mill is used in combination with a conventional drilling assembly 505 to drill out any hardened material 305 within the tubular member 210. The material 305 within the annular region 315 is then allowed to cure.

[000112] As illustrated in Fig. 5, preferably any remaining cured material 305 within the interior of the expanded tubular member 210 is then removed in a conventional manner using a conventional drill string 505. The resulting new section of casing 510 includes the expanded tubular member 210 and an outer annular layer 515 of cured material 305. The bottom portion of the apparatus 200 comprising the shoe 215 and dart 405 may then be removed by drilling out the shoe 215 and dart 405 using conventional drilling methods.

[000113] In a preferred embodiment, as illustrated in Fig. 6, the upper portion 260 of the tubular member 210 includes one or more sealing members 605 and one or more pressure relief holes 610. In this manner, the overlapping joint between the lower portion 270 of the casing 115 and the upper portion 260 of the tubular member 210 is pressure-tight and the pressure on the interior and exterior surfaces of the tubular member 210 is equalized during the extrusion process.

[000114] In a preferred embodiment, the sealing members 605 are seated within recesses 615 formed in the outer surface 265 of the upper portion 260 of the tubular member 210. In an alternative preferred embodiment, the sealing members 605 are bonded or molded onto the outer surface 265 of the upper portion 260 of the tubular member 210. The pressure relief holes 610 are preferably positioned in the last few feet of the tubular member 210. The pressure relief holes reduce the operating pressures required to expand the upper portion 260 of the tubular member 210. This reduction in required operating pressure in turn reduces the velocity of the mandrel 205 upon the completion of the extrusion process. This

reduction in velocity in turn minimizes the mechanical shock to the entire apparatus 200 upon the completion of the extrusion process.

[000115] Referring now to Fig. 7, a particularly preferred embodiment of an apparatus 700 for forming a casing within a wellbore preferably includes an expandable mandrel or pig 705, an expandable mandrel or pig container 710, a tubular member 715, a float shoe 720, a lower cup seal 725, an upper cup seal 730, a fluid passage 735, a fluid passage 740, a support member 745, a body of lubricant 750, an overshot connection 755, another support member 760, and a stabilizer 765.

[000116] The expandable mandrel 705 is coupled to and supported by the support member 745. The expandable mandrel 705 is further coupled to the expandable mandrel container 710. The expandable mandrel 705 is preferably adapted to controllably expand in a radial direction. The expandable mandrel 705 may comprise any number of conventional commercially available expandable mandrels modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the expandable mandrel 705 comprises a hydraulic expansion tool substantially as disclosed in U.S. Pat. No. 5,348,095, the contents of which are incorporated herein by reference, modified in accordance with the teachings of the present disclosure.

[000117] The expandable mandrel container 710 is coupled to and supported by the support member 745. The expandable mandrel container 710 is further coupled to the expandable mandrel 705. The expandable mandrel container 710 may be constructed from any number of conventional commercially available materials such as, for example, Oilfield Country Tubular Goods, stainless steel, titanium or high strength steels. In a preferred embodiment, the expandable mandrel container 710 is fabricated from material having a greater strength than the material from which the tubular member 715 is fabricated. In this manner, the container 710 can be fabricated from a tubular material having a thinner wall thickness than the tubular member 210. This permits the container 710 to pass through tight clearances thereby facilitating its placement within the wellbore.

[000118] In a preferred embodiment, once the expansion process begins, and the thicker, lower strength material of the tubular member 715 is expanded, the outside diameter of the tubular member 715 is greater than the outside diameter of the container 710.

[000119] The tubular member 715 is coupled to and supported by the expandable mandrel 705. The tubular member 715 is preferably expanded in the radial direction and extruded off of the expandable mandrel 705 substantially as described above with reference to Figs. 1-6. The tubular member 715 may be fabricated from any number of materials such as, for example, Oilfield Country Tubular Goods (OCTG), automotive grade steel or plastics. In a preferred embodiment, the tubular member 715 is fabricated from OCTG.

[000120] In a preferred embodiment, the tubular member 715 has a substantially annular cross-section. In a particularly preferred embodiment, the tubular member 715 has a substantially circular annular cross-section.

[000121] The tubular member 715 preferably includes an upper section 805, an intermediate section 810, and a lower section 815. The upper section 805 of the tubular member 715 preferably is defined by the region beginning in the vicinity of the mandrel container 710 and ending with the top section 820 of the tubular member 715. The intermediate section 810 of the tubular member 715 is preferably defined by the region beginning in the vicinity of the top of the mandrel container 710 and ending with the region in the vicinity of the mandrel 705. The lower section of the tubular member 715 is preferably defined by the region beginning in the vicinity of the mandrel 705 and ending at the bottom 825 of the tubular member 715.

[000122] In a preferred embodiment, the wall thickness of the upper section 805 of the tubular member 715 is greater than the wall thicknesses of the intermediate and lower sections 810 and 815 of the tubular member 715 in order to optimally facilitate the initiation of the extrusion process and optimally permit the apparatus 700 to be positioned in locations in the wellbore having tight clearances.

[000123] The outer diameter and wall thickness of the upper section 805 of the tubular member 715 may range, for example, from about 1.05 to 48 inches and 1/8 to 2 inches, respectively. In a preferred embodiment, the outer diameter and wall thickness of the upper section 805 of the tubular member 715 range from about 3.5 to 16 inches and 3/8 to 1.5 inches, respectively.

[000124] The outer diameter and wall thickness of the intermediate section 810 of the tubular member 715 may range, for example, from about 2.5 to 50 inches and 1/16 to 1.5 inches, respectively. In a preferred embodiment, the outer diameter and wall thickness of the intermediate section 810 of the tubular member 715 range from about 3.5 to 19 inches and 1/8 to 1.25 inches, respectively.

[000125] The outer diameter and wall thickness of the lower section 815 of the tubular member 715 may range, for example, from about 2.5 to 50 inches and 1/16 to 1.25 inches, respectively. In a preferred embodiment, the outer diameter and wall thickness of the lower section 810 of the tubular member 715 range from about 3.5 to 19 inches and 1/8 to 1.25 inches, respectively. In a particularly preferred embodiment, the wall thickness of the lower section 815 of the tubular member 715 is further increased to increase the strength of the shoe 720 when drillable materials such as, for example, aluminum are used.

[000126] The tubular member 715 preferably comprises a solid tubular member. In a preferred embodiment, the end portion 820 of the tubular member 715 is slotted, perforated,

or otherwise modified to catch or slow down the mandrel 705 when it completes the extrusion of tubular member 715. In a preferred embodiment, the length of the tubular member 715 is limited to minimize the possibility of buckling. For typical tubular member 715 materials, the length of the tubular member 715 is preferably limited to between about 40 to 20,000 feet in length.

[000127] The shoe 720 is coupled to the expandable mandrel 705 and the tubular member 715. The shoe 720 includes the fluid passage 740. In a preferred embodiment, the shoe 720 further includes an inlet passage 830, and one or more jet ports 835. In a particularly preferred embodiment, the cross-sectional shape of the inlet passage 830 is adapted to receive a latch-down dart, or other similar elements, for blocking the inlet passage 830. The interior of the shoe 720 preferably includes a body of solid material 840 for increasing the strength of the shoe 720. In a particularly preferred embodiment, the body of solid material 840 comprises aluminum.

[000128] The shoe 720 may comprise any number of conventional commercially available shoes such as, for example, Super Seal II Down-Jet float shoe, or guide shoe with a sealing sleeve for a latch down plug modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the shoe 720 comprises an aluminum down-jet guide shoe with a sealing sleeve for a latch-down plug available from Halliburton Energy Services in Dallas, TX, modified in accordance with the teachings of the present disclosure, in order to optimize guiding the tubular member 715 in the wellbore, optimize the seal between the tubular member 715 and an existing wellbore casing, and to optimally facilitate the removal of the shoe 720 by drilling it out after completion of the extrusion process.

[000129] The lower cup seal 725 is coupled to and supported by the support member 745. The lower cup seal 725 prevents foreign materials from entering the interior region of the tubular member 715 above the expandable mandrel 705. The lower cup seal 725 may comprise any number of conventional commercially available cup seals such as, for example, TP cups or Selective Injection Packer (SIP) cups modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the lower cup seal 725 comprises a SIP cup, available from Halliburton Energy Services in Dallas, TX in order to optimally provide a debris barrier and hold a body of lubricant.

[000130] The upper cup seal 730 is coupled to and supported by the support member 760. The upper cup seal 730 prevents foreign materials from entering the interior region of the tubular member 715. The upper cup seal 730 may comprise any number of conventional commercially available cup seals such as, for example, TP cups or Selective Injection Packer (SIP) cup modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the upper cup seal 730 comprises a SIP cup available from

Halliburton Energy Services in Dallas, TX in order to optimally provide a debris barrier and contain a body of lubricant.

[000131] The fluid passage 735 permits fluidic materials to be transported to and from the interior region of the tubular member 715 below the expandable mandrel 705. The fluid passage 735 is fluidically coupled to the fluid passage 740. The fluid passage 735 is preferably coupled to and positioned within the support member 760, the support member 745, the mandrel container 710, and the expandable mandrel 705. The fluid passage 735 preferably extends from a position adjacent to the surface to the bottom of the expandable mandrel 705. The fluid passage 735 is preferably positioned along a centerline of the apparatus 700. The fluid passage 735 is preferably selected to transport materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 40 to 3,000 gallons/minute and 500 to 9,000 psi in order to provide sufficient operating pressures to extrude the tubular member 715 off of the expandable mandrel 705.

[000132] As described above with reference to Figs. 1-6, during placement of the apparatus 700 within a new section of a wellbore, fluidic materials forced up the fluid passage 735 can be released into the wellbore above the tubular member 715. In a preferred embodiment, the apparatus 700 further includes a pressure release passage that is coupled to and positioned within the support member 260. The pressure release passage is further fluidically coupled to the fluid passage 735. The pressure release passage preferably includes a control valve for controllably opening and closing the fluid passage. In a preferred embodiment, the control valve is pressure activated in order to controllably minimize surge pressures. The pressure release passage is preferably positioned substantially orthogonal to the centerline of the apparatus 700. The pressure release passage is preferably selected to convey materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 0 to 500 gallons/minute and 0 to 1,000 psi in order to reduce the drag on the apparatus 700 during insertion into a new section of a wellbore and to minimize surge pressures on the new wellbore section.

[000133] The fluid passage 740 permits fluidic materials to be transported to and from the region exterior to the tubular member 715. The fluid passage 740 is preferably coupled to and positioned within the shoe 720 in fluidic communication with the interior region of the tubular member 715 below the expandable mandrel 705. The fluid passage 740 preferably has a cross-sectional shape that permits a plug, or other similar device, to be placed in the inlet 830 of the fluid passage 740 to thereby block further passage of fluidic materials. In this manner, the interior region of the tubular member 715 below the expandable mandrel 705 can be optimally fluidically isolated from the region exterior to the tubular member 715. This

permits the interior region of the tubular member 715 below the expandable mandrel 205 to be pressurized.

[000134] The fluid passage 740 is preferably positioned substantially along the centerline of the apparatus 700. The fluid passage 740 is preferably selected to convey materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to optimally fill an annular region between the tubular member 715 and a new section of a wellbore with fluidic materials. In a preferred embodiment, the fluid passage 740 includes an inlet passage 830 having a geometry that can receive a dart and/or a ball sealing member. In this manner, the fluid passage 240 can be sealed off by introducing a plug, dart and/or ball sealing elements into the fluid passage 230.

[000135] In a preferred embodiment, the apparatus 700 further includes one or more seals 845 coupled to and supported by the end portion 820 of the tubular member 715. The seals 845 are further positioned on an outer surface of the end portion 820 of the tubular member 715. The seals 845 permit the overlapping joint between an end portion of preexisting casing and the end portion 820 of the tubular member 715 to be fluidically sealed. The seals 845 may comprise any number of conventional commercially available seals such as, for example, lead, rubber, Teflon, or epoxy seals modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the seals 845 comprise seals molded from StrataLock epoxy available from Halliburton Energy Services in Dallas, TX in order to optimally provide a hydraulic seal and a load bearing interference fit in the overlapping joint between the tubular member 715 and an existing casing with optimal load bearing capacity to support the tubular member 715.

[000136] In a preferred embodiment, the seals 845 are selected to provide a sufficient frictional force to support the expanded tubular member 715 from the existing casing. In a preferred embodiment, the frictional force provided by the seals 845 ranges from about 1,000 to 1,000,000 lbf in order to optimally support the expanded tubular member 715.

[000137] The support member 745 is preferably coupled to the expandable mandrel 705 and the overshot connection 755. The support member 745 preferably comprises an annular member having sufficient strength to carry the apparatus 700 into a new section of a wellbore. The support member 745 may comprise any number of conventional commercially available support members such as, for example, steel drill pipe, coiled tubing or other high strength tubular modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the support member 745 comprises conventional drill pipe available from various steel mills in the United States.

[000138] In a preferred embodiment, a body of lubricant 750 is provided in the annular region above the expandable mandrel container 710 within the interior of the tubular member 715. In this manner, the extrusion of the tubular member 715 off of the expandable mandrel 705 is facilitated. The lubricant 705 may comprise any number of conventional commercially available lubricants such as, for example, Lubriplate, chlorine based lubricants, oil based lubricants, or Climax 1500 Antisieze (3100). In a preferred embodiment, the lubricant 750 comprises Climax 1500 Antisieze (3100) available from Halliburton Energy Services in Houston, TX in order to optimally provide lubrication to facilitate the extrusion process.

[000139] The overshot connection 755 is coupled to the support member 745 and the support member 760. The overshot connection 755 preferably permits the support member 745 to be removably coupled to the support member 760. The overshot connection 755 may comprise any number of conventional commercially available overshot connections such as, for example, Innerstring Sealing Adapter, Innerstring Flat-Face Sealing Adapter or EZ Drill Setting Tool Stinger. In a preferred embodiment, the overshot connection 755 comprises a Innerstring Adapter with an Upper Guide available from Halliburton Energy Services in Dallas, TX.

[000140] The support member 760 is preferably coupled to the overshot connection 755 and a surface support structure (not illustrated). The support member 760 preferably comprises an annular member having sufficient strength to carry the apparatus 700 into a new section of a wellbore. The support member 760 may comprise any number of conventional commercially available support members such as, for example, steel drill pipe, coiled tubing or other high strength tubulars modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the support member 760 comprises a conventional drill pipe available from steel mills in the United States.

[000141] The stabilizer 765 is preferably coupled to the support member 760. The stabilizer 765 also preferably stabilizes the components of the apparatus 700 within the tubular member 715. The stabilizer 765 preferably comprises a spherical member having an outside diameter that is about 80 to 99% of the interior diameter of the tubular member 715 in order to optimally minimize buckling of the tubular member 715. The stabilizer 765 may comprise any number of conventional commercially available stabilizers such as, for example, EZ Drill Star Guides, packer shoes or drag blocks modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the stabilizer 765 comprises a sealing adapter upper guide available from Halliburton Energy Services in Dallas, TX.

[000142] In a preferred embodiment, the support members 745 and 760 are thoroughly cleaned prior to assembly to the remaining portions of the apparatus 700. In this manner, the introduction of foreign material into the apparatus 700 is minimized. This minimizes the

possibility of foreign material clogging the various flow passages and valves of the apparatus 700.

[000143] In a preferred embodiment, before or after positioning the apparatus 700 within a new section of a wellbore, a couple of wellbore volumes are circulated through the various flow passages of the apparatus 700 in order to ensure that no foreign materials are located within the wellbore that might clog up the various flow passages and valves of the apparatus 700 and to ensure that no foreign material interferes with the expansion mandrel 705 during the expansion process.

[000144] In a preferred embodiment, the apparatus 700 is operated substantially as described above with reference to Figs. 1-7 to form a new section of casing within a wellbore.

[000145] As illustrated in Fig. 8, in an alternative preferred embodiment, the method and apparatus described herein is used to repair an existing wellbore casing 805 by forming a tubular liner 810 inside of the existing wellbore casing 805. In a preferred embodiment, an outer annular lining of cement is not provided in the repaired section. In the alternative preferred embodiment, any number of fluidic materials can be used to expand the tubular liner 810 into intimate contact with the damaged section of the wellbore casing such as, for example, cement, epoxy, slag mix, or drilling mud. In the alternative preferred embodiment, sealing members 815 are preferably provided at both ends of the tubular member in order to optimally provide a fluidic seal. In an alternative preferred embodiment, the tubular liner 810 is formed within a horizontally positioned pipeline section, such as those used to transport hydrocarbons or water, with the tubular liner 810 placed in an overlapping relationship with the adjacent pipeline section. In this manner, underground pipelines can be repaired without having to dig out and replace the damaged sections.

[000146] In another alternative preferred embodiment, the method and apparatus described herein is used to directly line a wellbore with a tubular liner 810. In a preferred embodiment, an outer annular lining of cement is not provided between the tubular liner 810 and the wellbore. In the alternative preferred embodiment, any number of fluidic materials can be used to expand the tubular liner 810 into intimate contact with the wellbore such as, for example, cement, epoxy, slag mix, or drilling mud.

[000147] Referring now to Figs. 9, 9a, 9b and 9c, a preferred embodiment of an apparatus 900 for forming a wellbore casing includes an expandable tubular member 902, a support member 904, an expandable mandrel or pig 906, and a shoe 908. In a preferred embodiment, the design and construction of the mandrel 906 and shoe 908 permits easy removal of those elements by drilling them out. In this manner, the assembly 900 can be

easily removed from a wellbore using a conventional drilling apparatus and corresponding drilling methods.

[000148] The expandable tubular member 902 preferably includes an upper portion 910, an intermediate portion 912 and a lower portion 914. During operation of the apparatus 900, the tubular member 902 is preferably extruded off of the mandrel 906 by pressurizing an interior region 966 of the tubular member 902. The tubular member 902 preferably has a substantially annular cross-section.

[000149] In a particularly preferred embodiment, an expandable tubular member 915 is coupled to the upper portion 910 of the expandable tubular member 902. During operation of the apparatus 900, the tubular member 915 is preferably extruded off of the mandrel 906 by pressurizing the interior region 966 of the tubular member 902. The tubular member 915 preferably has a substantially annular cross-section. In a preferred embodiment, the wall thickness of the tubular member 915 is greater than the wall thickness of the tubular member 902.

[000150] The tubular member 915 may be fabricated from any number of conventional commercially available materials such as, for example, oilfield tubulars, low alloy steels, titanium or stainless steels. In a preferred embodiment, the tubular member 915 is fabricated from oilfield tubulars in order to optimally provide approximately the same mechanical properties as the tubular member 902. In a particularly preferred embodiment, the tubular member 915 has a plastic yield point ranging from about 40,000 to 135,000 psi in order to optimally provide approximately the same yield properties as the tubular member 902. The tubular member 915 may comprise a plurality of tubular members coupled end to end.

[000151] In a preferred embodiment, the upper end portion of the tubular member 915 includes one or more sealing members for optimally providing a fluidic and/or gaseous seal with an existing section of wellbore casing.

[000152] In a preferred embodiment, the combined length of the tubular members 902 and 915 are limited to minimize the possibility of buckling. For typical tubular member materials, the combined length of the tubular members 902 and 915 are limited to between about 40 to 20,000 feet in length.

[000153] The lower portion 914 of the tubular member 902 is preferably coupled to the shoe 908 by a threaded connection 968. The intermediate portion 912 of the tubular member 902 preferably is placed in intimate sliding contact with the mandrel 906.

[000154] The tubular member 902 may be fabricated from any number of conventional commercially available materials such as, for example, oilfield tubulars, low alloy steels, titanium or stainless steels. In a preferred embodiment, the tubular member 902 is

fabricated from oilfield tubulars in order to optimally provide approximately the same mechanical properties as the tubular member 915. In a particularly preferred embodiment, the tubular member 902 has a plastic yield point ranging from about 40,000 to 135,000 psi in order to optimally provide approximately the same yield properties as the tubular member 915.

[000155] The wall thickness of the upper, intermediate, and lower portions, 910, 912 and 914 of the tubular member 902 may range, for example, from about 1/16 to 1.5 inches. In a preferred embodiment, the wall thickness of the upper, intermediate, and lower portions, 910, 912 and 914 of the tubular member 902 range from about 1/8 to 1.25 in order to optimally provide wall thickness that are about the same as the tubular member 915. In a preferred embodiment, the wall thickness of the lower portion 914 is less than or equal to the wall thickness of the upper portion 910 in order to optimally provide a geometry that will fit into tight clearances downhole.

[000156] The outer diameter of the upper, intermediate, and lower portions, 910, 912 and 914 of the tubular member 902 may range, for example, from about 1.05 to 48 inches. In a preferred embodiment, the outer diameter of the upper, intermediate, and lower portions, 910, 912 and 914 of the tubular member 902 range from about 3 ½ to 19 inches in order to optimally provide the ability to expand the most commonly used oilfield tubulars.

[000157] The length of the tubular member 902 is preferably limited to between about 2 to 5 feet in order to optimally provide enough length to contain the mandrel 906 and a body of lubricant.

[000158] The tubular member 902 may comprise any number of conventional commercially available tubular members modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the tubular member 902 comprises Oilfield Country Tubular Goods available from various U.S. steel mills. The tubular member 915 may comprise any number of conventional commercially available tubular members modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the tubular member 915 comprises Oilfield Country Tubular Goods available from various U.S. steel mills.

[000159] The various elements of the tubular member 902 may be coupled using any number of conventional process such as, for example, threaded connections, welding or machined from one piece. In a preferred embodiment, the various elements of the tubular member 902 are coupled using welding. The tubular member 902 may comprise a plurality of tubular elements that are coupled end to end. The various elements of the tubular member 915 may be coupled using any number of conventional process such as, for example, threaded connections, welding or machined from one piece. In a preferred

embodiment, the various elements of the tubular member 915 are coupled using welding. The tubular member 915 may comprise a plurality of tubular elements that are coupled end to end. The tubular members 902 and 915 may be coupled using any number of conventional process such as, for example, threaded connections, welding or machined from one piece.

[000160] The support member 904 preferably includes an innerstring adapter 916, a fluid passage 918, an upper guide 920, and a coupling 922. During operation of the apparatus 900, the support member 904 preferably supports the apparatus 900 during movement of the apparatus 900 within a wellbore. The support member 904 preferably has a substantially annular cross-section.

[000161] The support member 904 may be fabricated from any number of conventional commercially available materials such as, for example, oilfield tubulars, low alloy steel, coiled tubing or stainless steel. In a preferred embodiment, the support member 904 is fabricated from low alloy steel in order to optimally provide high yield strength.

[000162] The innerstring adaptor 916 preferably is coupled to and supported by a conventional drill string support from a surface location. The innerstring adaptor 916 may be coupled to a conventional drill string support 971 by a threaded connection 970.

[000163] The fluid passage 918 is preferably used to convey fluids and other materials to and from the apparatus 900. In a preferred embodiment, the fluid passage 918 is fluidically coupled to the fluid passage 952. In a preferred embodiment, the fluid passage 918 is used to convey hardenable fluidic sealing materials to and from the apparatus 900. In a particularly preferred embodiment, the fluid passage 918 may include one or more pressure relief passages (not illustrated) to release fluid pressure during positioning of the apparatus 900 within a wellbore. In a preferred embodiment, the fluid passage 918 is positioned along a longitudinal centerline of the apparatus 900. In a preferred embodiment, the fluid passage 918 is selected to permit the conveyance of hardenable fluidic materials at operating pressures ranging from about 0 to 9,000 psi.

[000164] The upper guide 920 is coupled to an upper portion of the support member 904. The upper guide 920 preferably is adapted to center the support member 904 within the tubular member 915. The upper guide 920 may comprise any number of conventional guide members modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the upper guide 920 comprises an innerstring adapter available from Halliburton Energy Services in Dallas, TX order to optimally guide the apparatus 900 within the tubular member 915.

[000165] The coupling 922 couples the support member 904 to the mandrel 906. The coupling 922 preferably comprises a conventional threaded connection.

[000166] The various elements of the support member 904 may be coupled using any number of conventional processes such as, for example, welding, threaded connections or machined from one piece. In a preferred embodiment, the various elements of the support member 904 are coupled using threaded connections.

[000167] The mandrel 906 preferably includes a retainer 924, a rubber cup 926, an expansion cone 928, a lower cone retainer 930, a body of cement 932, a lower guide 934, an extension sleeve 936, a spacer 938, a housing 940, a sealing sleeve 942, an upper cone retainer 944, a lubricator mandrel 946, a lubricator sleeve 948, a guide 950, and a fluid passage 952.

[000168] The retainer 924 is coupled to the lubricator mandrel 946, lubricator sleeve 948, and the rubber cup 926. The retainer 924 couples the rubber cup 926 to the lubricator sleeve 948. The retainer 924 preferably has a substantially annular cross-section. The retainer 924 may comprise any number of conventional commercially available retainers such as, for example, slotted spring pins or roll pin.

[000169] The rubber cup 926 is coupled to the retainer 924, the lubricator mandrel 946, and the lubricator sleeve 948. The rubber cup 926 prevents the entry of foreign materials into the interior region 972 of the tubular member 902 below the rubber cup 926. The rubber cup 926 may comprise any number of conventional commercially available rubber cups such as, for example, TP cups or Selective Injection Packer (SIP) cup. In a preferred embodiment, the rubber cup 926 comprises a SIP cup available from Halliburton Energy Services in Dallas, TX in order to optimally block foreign materials.

[000170] In a particularly preferred embodiment, a body of lubricant is further provided in the interior region 972 of the tubular member 902 in order to lubricate the interface between the exterior surface of the mandrel 902 and the interior surface of the tubular members 902 and 915. The lubricant may comprise any number of conventional commercially available lubricants such as, for example, Lubriplate, chlorine based lubricants, oil based lubricants or Climax 1500 Antiseize (3100). In a preferred embodiment, the lubricant comprises Climax 1500 Antiseize (3100) available from Climax Lubricants and Equipment Co. in Houston, TX in order to optimally provide lubrication to facilitate the extrusion process.

[000171] The expansion cone 928 is coupled to the lower cone retainer 930, the body of cement 932, the lower guide 934, the extension sleeve 936, the housing 940, and the upper cone retainer 944. In a preferred embodiment, during operation of the apparatus 900, the tubular members 902 and 915 are extruded off of the outer surface of the expansion cone 928. In a preferred embodiment, axial movement of the expansion cone 928 is prevented by the lower cone retainer 930, housing 940 and the upper cone retainer 944. Inner radial

movement of the expansion cone 928 is prevented by the body of cement 932, the housing 940, and the upper cone retainer 944.

[000172] The expansion cone 928 preferably has a substantially annular cross section. The outside diameter of the expansion cone 928 is preferably tapered to provide a cone shape. The wall thickness of the expansion cone 928 may range, for example, from about 0.125 to 3 inches. In a preferred embodiment, the wall thickness of the expansion cone 928 ranges from about 0.25 to 0.75 inches in order to optimally provide adequate compressive strength with minimal material. The maximum and minimum outside diameters of the expansion cone 928 may range, for example, from about 1 to 47 inches. In a preferred embodiment, the maximum and minimum outside diameters of the expansion cone 928 range from about 3.5 to 19 in order to optimally provide expansion of generally available oilfield tubulars

[000173] The expansion cone 928 may be fabricated from any number of conventional commercially available materials such as, for example, ceramic, tool steel, titanium or low alloy steel. In a preferred embodiment, the expansion cone 928 is fabricated from tool steel in order to optimally provide high strength and abrasion resistance. The surface hardness of the outer surface of the expansion cone 928 may range, for example, from about 50 Rockwell C to 70 Rockwell C. In a preferred embodiment, the surface hardness of the outer surface of the expansion cone 928 ranges from about 58 Rockwell C to 62 Rockwell C in order to optimally provide high yield strength. In a preferred embodiment, the expansion cone 928 is heat treated to optimally provide a hard outer surface and a resilient interior body in order to optimally provide abrasion resistance and fracture toughness.

[000174] The lower cone retainer 930 is coupled to the expansion cone 928 and the housing 940. In a preferred embodiment, axial movement of the expansion cone 928 is prevented by the lower cone retainer 930. Preferably, the lower cone retainer 930 has a substantially annular cross-section.

[000175] The lower cone retainer 930 may be fabricated from any number of conventional commercially available materials such as, for example, ceramic, tool steel, titanium or low alloy steel. In a preferred embodiment, the lower cone retainer 930 is fabricated from tool steel in order to optimally provide high strength and abrasion resistance. The surface hardness of the outer surface of the lower cone retainer 930 may range, for example, from about 50 Rockwell C to 70 Rockwell C. In a preferred embodiment, the surface hardness of the outer surface of the lower cone retainer 930 ranges from about 58 Rockwell C to 62 Rockwell C in order to optimally provide high yield strength. In a preferred embodiment, the lower cone retainer 930 is heat treated to optimally provide a hard outer surface and a

resilient interior body in order to optimally provide abrasion resistance and fracture toughness.

[000176] In a preferred embodiment, the lower cone retainer 930 and the expansion cone 928 are formed as an integral one-piece element in order to reduce the number of components and increase the overall strength of the apparatus. The outer surface of the lower cone retainer 930 preferably mates with the inner surfaces of the tubular members 902 and 915.

[000177] The body of cement 932 is positioned within the interior of the mandrel 906. The body of cement 932 provides an inner bearing structure for the mandrel 906. The body of cement 932 further may be easily drilled out using a conventional drill device. In this manner, the mandrel 906 may be easily removed using a conventional drilling device.

[000178] The body of cement 932 may comprise any number of conventional commercially available cement compounds. Alternatively, aluminum, cast iron or some other drillable metallic, composite, or aggregate material may be substituted for cement. The body of cement 932 preferably has a substantially annular cross-section.

[000179] The lower guide 934 is coupled to the extension sleeve 936 and housing 940. During operation of the apparatus 900, the lower guide 934 preferably helps guide the movement of the mandrel 906 within the tubular member 902. The lower guide 934 preferably has a substantially annular cross-section.

[000180] The lower guide 934 may be fabricated from any number of conventional commercially available materials such as, for example, oilfield tubulars, low alloy steel or stainless steel. In a preferred embodiment, the lower guide 934 is fabricated from low alloy steel in order to optimally provide high yield strength. The outer surface of the lower guide 934 preferably mates with the inner surface of the tubular member 902 to provide a sliding fit.

[000181] The extension sleeve 936 is coupled to the lower guide 934 and the housing 940. During operation of the apparatus 900, the extension sleeve 936 preferably helps guide the movement of the mandrel 906 within the tubular member 902. The extension sleeve 936 preferably has a substantially annular cross-section.

[000182] The extension sleeve 936 may be fabricated from any number of conventional commercially available materials such as, for example, oilfield tubulars, low alloy steel or stainless steel. In a preferred embodiment, the extension sleeve 936 is fabricated from low alloy steel in order to optimally provide high yield strength. The outer surface of the extension sleeve 936 preferably mates with the inner surface of the tubular member 902 to provide a sliding fit. In a preferred embodiment, the extension sleeve 936 and the lower guide 934 are formed as an integral one-piece element in order to minimize the number of components and increase the strength of the apparatus.

[000183] The spacer 938 is coupled to the sealing sleeve 942. The spacer 938 preferably includes the fluid passage 952 and is adapted to mate with the extension tube 960 of the shoe 908. In this manner, a plug or dart can be conveyed from the surface through the fluid passages 918 and 952 into the fluid passage 962. Preferably, the spacer 938 has a substantially annular cross-section.

[000184] The spacer 938 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a preferred embodiment, the spacer 938 is fabricated from aluminum in order to optimally provide drillability. The end of the spacer 938 preferably mates with the end of the extension tube 960. In a preferred embodiment, the spacer 938 and the sealing sleeve 942 are formed as an integral one-piece element in order to reduce the number of components and increase the strength of the apparatus.

[000185] The housing 940 is coupled to the lower guide 934, extension sleeve 936, expansion cone 928, body of cement 932, and lower cone retainer 930. During operation of the apparatus 900, the housing 940 preferably prevents inner radial motion of the expansion cone 928. Preferably, the housing 940 has a substantially annular cross-section.

[000186] The housing 940 may be fabricated from any number of conventional commercially available materials such as, for example, oilfield tubulars, low alloy steel or stainless steel. In a preferred embodiment, the housing 940 is fabricated from low alloy steel in order to optimally provide high yield strength. In a preferred embodiment, the lower guide 934, extension sleeve 936 and housing 940 are formed as an integral one-piece element in order to minimize the number of components and increase the strength of the apparatus.

[000187] In a particularly preferred embodiment, the interior surface of the housing 940 includes one or more protrusions to facilitate the connection between the housing 940 and the body of cement 932.

[000188] The sealing sleeve 942 is coupled to the support member 904, the body of cement 932, the spacer 938, and the upper cone retainer 944. During operation of the apparatus, the sealing sleeve 942 preferably provides support for the mandrel 906. The sealing sleeve 942 is preferably coupled to the support member 904 using the coupling 922. Preferably, the sealing sleeve 942 has a substantially annular cross-section.

[000189] The sealing sleeve 942 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a preferred embodiment, the sealing sleeve 942 is fabricated from aluminum in order to optimally provide drillability of the sealing sleeve 942.

[000190] In a particularly preferred embodiment, the outer surface of the sealing sleeve 942 includes one or more protrusions to facilitate the connection between the sealing sleeve 942 and the body of cement 932.

[000191] In a particularly preferred embodiment, the spacer 938 and the sealing sleeve 942 are integrally formed as a one-piece element in order to minimize the number of components.

[000192] The upper cone retainer 944 is coupled to the expansion cone 928, the sealing sleeve 942, and the body of cement 932. During operation of the apparatus 900, the upper cone retainer 944 preferably prevents axial motion of the expansion cone 928. Preferably, the upper cone retainer 944 has a substantially annular cross-section.

[000193] The upper cone retainer 944 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a preferred embodiment, the upper cone retainer 944 is fabricated from aluminum in order to optimally provide drillability of the upper cone retainer 944.

[000194] In a particularly preferred embodiment, the upper cone retainer 944 has a cross-sectional shape designed to provide increased rigidity. In a particularly preferred embodiment, the upper cone retainer 944 has a cross-sectional shape that is substantially I-shaped to provide increased rigidity and minimize the amount of material that would have to be drilled out.

[000195] The lubricator mandrel 946 is coupled to the retainer 924, the rubber cup 926, the upper cone retainer 944, the lubricator sleeve 948, and the guide 950. During operation of the apparatus 900, the lubricator mandrel 946 preferably contains the body of lubricant in the annular region 972 for lubricating the interface between the mandrel 906 and the tubular member 902. Preferably, the lubricator mandrel 946 has a substantially annular cross-section.

[000196] The lubricator mandrel 946 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a preferred embodiment, the lubricator mandrel 946 is fabricated from aluminum in order to optimally provide drillability of the lubricator mandrel 946.

[000197] The lubricator sleeve 948 is coupled to the lubricator mandrel 946, the retainer 924, the rubber cup 926, the upper cone retainer 944, the lubricator sleeve 948, and the guide 950. During operation of the apparatus 900, the lubricator sleeve 948 preferably supports the rubber cup 926. Preferably, the lubricator sleeve 948 has a substantially annular cross-section.

[000198] The lubricator sleeve 948 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a

preferred embodiment, the lubricator sleeve 948 is fabricated from aluminum in order to optimally provide drillability of the lubricator sleeve 948.

[000199] As illustrated in Fig. 9c, the lubricator sleeve 948 is supported by the lubricator mandrel 946. The lubricator sleeve 948 in turn supports the rubber cup 926. The retainer 924 couples the rubber cup 926 to the lubricator sleeve 948. In a preferred embodiment, seals 949a and 949b are provided between the lubricator mandrel 946, lubricator sleeve 948, and rubber cup 926 in order to optimally seal off the interior region 972 of the tubular member 902.

[000200] The guide 950 is coupled to the lubricator mandrel 946, the retainer 924, and the lubricator sleeve 948. During operation of the apparatus 900, the guide 950 preferably guides the apparatus on the support member 904. Preferably, the guide 950 has a substantially annular cross-section.

[000201] The guide 950 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a preferred embodiment, the guide 950 is fabricated from aluminum in order to optimally provide drillability of the guide 950.

[000202] The fluid passage 952 is coupled to the mandrel 906. During operation of the apparatus, the fluid passage 952 preferably conveys hardenable fluidic materials. In a preferred embodiment, the fluid passage 952 is positioned about the centerline of the apparatus 900. In a particularly preferred embodiment, the fluid passage 952 is adapted to convey hardenable fluidic materials at pressures and flow rate ranging from about 0 to 9,000 psi and 0 to 3,000 gallons/min in order to optimally provide pressures and flow rates to displace and circulate fluids during the installation of the apparatus 900.

[000203] The various elements of the mandrel 906 may be coupled using any number of conventional process such as, for example, threaded connections, welded connections or cementing. In a preferred embodiment, the various elements of the mandrel 906 are coupled using threaded connections and cementing.

[000204] The shoe 908 preferably includes a housing 954, a body of cement 956, a sealing sleeve 958, an extension tube 960, a fluid passage 962, and one or more outlet jets 964.

[000205] The housing 954 is coupled to the body of cement 956 and the lower portion 914 of the tubular member 902. During operation of the apparatus 900, the housing 954 preferably couples the lower portion of the tubular member 902 to the shoe 908 to facilitate the extrusion and positioning of the tubular member 902. Preferably, the housing 954 has a substantially annular cross-section.

[000206] The housing 954 may be fabricated from any number of conventional commercially available materials such as, for example, steel or aluminum. In a preferred

embodiment, the housing 954 is fabricated from aluminum in order to optimally provide drillability of the housing 954.

[000207] In a particularly preferred embodiment, the interior surface of the housing 954 includes one or more protrusions to facilitate the connection between the body of cement 956 and the housing 954.

[000208] The body of cement 956 is coupled to the housing 954, and the sealing sleeve 958. In a preferred embodiment, the composition of the body of cement 956 is selected to permit the body of cement to be easily drilled out using conventional drilling machines and processes.

[000209] The composition of the body of cement 956 may include any number of conventional cement compositions. In an alternative embodiment, a drillable material such as, for example, aluminum or iron may be substituted for the body of cement 956.

[000210] The sealing sleeve 958 is coupled to the body of cement 956, the extension tube 960, the fluid passage 962, and one or more outlet jets 964. During operation of the apparatus 900, the sealing sleeve 958 preferably is adapted to convey a hardenable fluidic material from the fluid passage 952 into the fluid passage 962 and then into the outlet jets 964 in order to inject the hardenable fluidic material into an annular region external to the tubular member 902. In a preferred embodiment, during operation of the apparatus 900, the sealing sleeve 958 further includes an inlet geometry that permits a conventional plug or dart 974 to become lodged in the inlet of the sealing sleeve 958. In this manner, the fluid passage 962 may be blocked thereby fluidically isolating the interior region 966 of the tubular member 902.

[000211] In a preferred embodiment, the sealing sleeve 958 has a substantially annular cross-section. The sealing sleeve 958 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a preferred embodiment, the sealing sleeve 958 is fabricated from aluminum in order to optimally provide drillability of the sealing sleeve 958.

[000212] The extension tube 960 is coupled to the sealing sleeve 958, the fluid passage 962, and one or more outlet jets 964. During operation of the apparatus 900, the extension tube 960 preferably is adapted to convey a hardenable fluidic material from the fluid passage 952 into the fluid passage 962 and then into the outlet jets 964 in order to inject the hardenable fluidic material into an annular region external to the tubular member 902. In a preferred embodiment, during operation of the apparatus 900, the sealing sleeve 960 further includes an inlet geometry that permits a conventional plug or dart 974 to become lodged in the inlet of the sealing sleeve 958. In this manner, the fluid passage 962 is blocked thereby fluidically isolating the interior region 966 of the tubular member 902. In a preferred

embodiment, one end of the extension tube 960 mates with one end of the spacer 938 in order to optimally facilitate the transfer of material between the two.

[000213] In a preferred embodiment, the extension tube 960 has a substantially annular cross-section. The extension tube 960 may be fabricated from any number of conventional commercially available materials such as, for example, steel, aluminum or cast iron. In a preferred embodiment, the extension tube 960 is fabricated from aluminum in order to optimally provide drillability of the extension tube 960.

[000214] The fluid passage 962 is coupled to the sealing sleeve 958, the extension tube 960, and one or more outlet jets 964. During operation of the apparatus 900, the fluid passage 962 is preferably conveys hardenable fluidic materials. In a preferred embodiment, the fluid passage 962 is positioned about the centerline of the apparatus 900. In a particularly preferred embodiment, the fluid passage 962 is adapted to convey hardenable fluidic materials at pressures and flow rate ranging from about 0 to 9,000 psi and 0 to 3,000 gallons/min in order to optimally provide fluids at operationally efficient rates.

[000215] The outlet jets 964 are coupled to the sealing sleeve 958, the extension tube 960, and the fluid passage 962. During operation of the apparatus 900, the outlet jets 964 preferably convey hardenable fluidic material from the fluid passage 962 to the region exterior of the apparatus 900. In a preferred embodiment, the shoe 908 includes a plurality of outlet jets 964.

[000216] In a preferred embodiment, the outlet jets 964 comprise passages drilled in the housing 954 and the body of cement 956 in order to simplify the construction of the apparatus 900.

[000217] The various elements of the shoe 908 may be coupled using any number of conventional process such as, for example, threaded connections, cement or machined from one piece of material. In a preferred embodiment, the various elements of the shoe 908 are coupled using cement.

[000218] In a preferred embodiment, the assembly 900 is operated substantially as described above with reference to Figs. 1-8 to create a new section of casing in a wellbore or to repair a wellbore casing or pipeline.

[000219] In particular, in order to extend a wellbore into a subterranean formation, a drill string is used in a well known manner to drill out material from the subterranean formation to form a new section.

[000220] The apparatus 900 for forming a wellbore casing in a subterranean formation is then positioned in the new section of the wellbore. In a particularly preferred embodiment, the apparatus 900 includes the tubular member 915. In a preferred embodiment, a hardenable fluidic sealing hardenable fluidic sealing material is then pumped from a surface

location into the fluid passage 918. The hardenable fluidic sealing material then passes from the fluid passage 918 into the interior region 966 of the tubular member 902 below the mandrel 906. The hardenable fluidic sealing material then passes from the interior region 966 into the fluid passage 962. The hardenable fluidic sealing material then exits the apparatus 900 via the outlet jets 964 and fills an annular region between the exterior of the tubular member 902 and the interior wall of the new section of the wellbore. Continued pumping of the hardenable fluidic sealing material causes the material to fill up at least a portion of the annular region.

[000221] The hardenable fluidic sealing material is preferably pumped into the annular region at pressures and flow rates ranging, for example, from about 0 to 5,000 psi and 0 to 1,500 gallons/min, respectively. In a preferred embodiment, the hardenable fluidic sealing material is pumped into the annular region at pressures and flow rates that are designed for the specific wellbore section in order to optimize the displacement of the hardenable fluidic sealing material while not creating high enough circulating pressures such that circulation might be lost and that could cause the wellbore to collapse. The optimum pressures and flow rates are preferably determined using conventional empirical methods.

[000222] The hardenable fluidic sealing material may comprise any number of conventional commercially available hardenable fluidic sealing materials such as, for example, slag mix, cement or epoxy. In a preferred embodiment, the hardenable fluidic sealing material comprises blended cements designed specifically for the well section being lined available from Halliburton Energy Services in Dallas, TX in order to optimally provide support for the new tubular member while also maintaining optimal flow characteristics so as to minimize operational difficulties during the displacement of the cement in the annular region. The optimum composition of the blended cements is preferably determined using conventional empirical methods.

[000223] The annular region preferably is filled with the hardenable fluidic sealing material in sufficient quantities to ensure that, upon radial expansion of the tubular member 902, the annular region of the new section of the wellbore will be filled with hardenable material.

[000224] Once the annular region has been adequately filled with hardenable fluidic sealing material, a plug or dart 974, or other similar device, preferably is introduced into the fluid passage 962 thereby fluidically isolating the interior region 966 of the tubular member 902 from the external annular region. In a preferred embodiment, a non hardenable fluidic material is then pumped into the interior region 966 causing the interior region 966 to pressurize. In a particularly preferred embodiment, the plug or dart 974, or other similar device, preferably is introduced into the fluid passage 962 by introducing the plug or dart 974, or other similar device into the non hardenable fluidic material. In this manner, the

amount of cured material within the interior of the tubular members 902 and 915 is minimized.

[000225] Once the interior region 966 becomes sufficiently pressurized, the tubular members 902 and 915 are extruded off of the mandrel 906. The mandrel 906 may be fixed or it may be expandable. During the extrusion process, the mandrel 906 is raised out of the expanded portions of the tubular members 902 and 915 using the support member 904. During this extrusion process, the shoe 908 is preferably substantially stationary.

[000226] The plug or dart 974 is preferably placed into the fluid passage 962 by introducing the plug or dart 974 into the fluid passage 918 at a surface location in a conventional manner. The plug or dart 974 may comprise any number of conventional commercially available devices for plugging a fluid passage such as, for example, Multiple Stage Cementer (MSC) latch-down plug, Omega latch-down plug or three-wiper latch down plug modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the plug or dart 974 comprises a MSC latch-down plug available from Halliburton Energy Services in Dallas, TX.

[000227] After placement of the plug or dart 974 in the fluid passage 962, the non hardenable fluidic material is preferably pumped into the interior region 966 at pressures and flow rates ranging from approximately 500 to 9,000 psi and 40 to 3,000 gallons/min in order to optimally extrude the tubular members 902 and 915 off of the mandrel 906.

[000228] For typical tubular members 902 and 915, the extrusion of the tubular members 902 and 915 off of the expandable mandrel will begin when the pressure of the interior region 966 reaches approximately 500 to 9,000 psi. In a preferred embodiment, the extrusion of the tubular members 902 and 915 off of the mandrel 906 begins when the pressure of the interior region 966 reaches approximately 1,200 to 8,500 psi with a flow rate of about 40 to 1250 gallons/minute.

[000229] During the extrusion process, the mandrel 906 may be raised out of the expanded portions of the tubular members 902 and 915 at rates ranging, for example, from about 0 to 5 ft/sec. In a preferred embodiment, during the extrusion process, the mandrel 906 is raised out of the expanded portions of the tubular members 902 and 915 at rates ranging from about 0 to 2 ft/sec in order to optimally provide pulling speed fast enough to permit efficient operation and permit full expansion of the tubular members 902 and 915 prior to curing of the hardenable fluidic sealing material; but not so fast that timely adjustment of operating parameters during operation is prevented.

[000230] When the upper end portion of the tubular member 915 is extruded off of the mandrel 906, the outer surface of the upper end portion of the tubular member 915 will preferably contact the interior surface of the lower end portion of the existing casing to form

an fluid tight overlapping joint. The contact pressure of the overlapping joint may range, for example, from approximately 50 to 20,000 psi. In a preferred embodiment, the contact pressure of the overlapping joint between the upper end of the tubular member 915 and the existing section of wellbore casing ranges from approximately 400 to 10,000 psi in order to optimally provide contact pressure to activate the sealing members and provide optimal resistance such that the tubular member 915 and existing wellbore casing will carry typical tensile and compressive loads.

[000231] In a preferred embodiment, the operating pressure and flow rate of the non hardenable fluidic material will be controllably ramped down when the mandrel 906 reaches the upper end portion of the tubular member 915. In this manner, the sudden release of pressure caused by the complete extrusion of the tubular member 915 off of the expandable mandrel 906 can be minimized. In a preferred embodiment, the operating pressure is reduced in a substantially linear fashion from 100% to about 10% during the end of the extrusion process beginning when the mandrel 906 has completed approximately all but about the last 5 feet of the extrusion process.

[000232] In an alternative preferred embodiment, the operating pressure and/or flow rate of the hardenable fluidic sealing material and/or the non hardenable fluidic material are controlled during all phases of the operation of the apparatus 900 to minimize shock.

[000233] Alternatively, or in combination, a shock absorber is provided in the support member 904 in order to absorb the shock caused by the sudden release of pressure.

[000234] Alternatively, or in combination, a mandrel catching structure is provided above the support member 904 in order to catch or at least decelerate the mandrel 906.

[000235] Once the extrusion process is completed, the mandrel 906 is removed from the wellbore. In a preferred embodiment, either before or after the removal of the mandrel 906, the integrity of the fluidic seal of the overlapping joint between the upper portion of the tubular member 915 and the lower portion of the existing casing is tested using conventional methods. If the fluidic seal of the overlapping joint between the upper portion of the tubular member 915 and the lower portion of the existing casing is satisfactory, then the uncured portion of any of the hardenable fluidic sealing material within the expanded tubular member 915 is then removed in a conventional manner. The hardenable fluidic sealing material within the annular region between the expanded tubular member 915 and the existing casing and new section of wellbore is then allowed to cure.

[000236] Preferably any remaining cured hardenable fluidic sealing material within the interior of the expanded tubular members 902 and 915 is then removed in a conventional manner using a conventional drill string. The resulting new section of casing preferably includes the expanded tubular members 902 and 915 and an outer annular layer of cured

hardenable fluidic sealing material. The bottom portion of the apparatus 900 comprising the shoe 908 may then be removed by drilling out the shoe 908 using conventional drilling methods.

[000237] In an alternative embodiment, during the extrusion process, it may be necessary to remove the entire apparatus 900 from the interior of the wellbore due to a malfunction. In this circumstance, a conventional drill string is used to drill out the interior sections of the apparatus 900 in order to facilitate the removal of the remaining sections. In a preferred embodiment, the interior elements of the apparatus 900 are fabricated from materials such as, for example, cement and aluminum, that permit a conventional drill string to be employed to drill out the interior components.

[000238] In particular, in a preferred embodiment, the composition of the interior sections of the mandrel 906 and shoe 908, including one or more of the body of cement 932, the spacer 938, the sealing sleeve 942, the upper cone retainer 944, the lubricator mandrel 946, the lubricator sleeve 948, the guide 950, the housing 954, the body of cement 956, the sealing sleeve 958, and the extension tube 960, are selected to permit at least some of these components to be drilled out using conventional drilling methods and apparatus. In this manner, in the event of a malfunction downhole, the apparatus 900 may be easily removed from the wellbore.

[000239] Referring now to Figs. 10a, 10b, 10c, 10d, 10e, 10f, and 10g a method and apparatus for creating a tie-back liner in a wellbore will now be described. As illustrated in Fig. 10a, a wellbore 1000 positioned in a subterranean formation 1002 includes a first casing 1004 and a second casing 1006.

[000240] The first casing 1004 preferably includes a tubular liner 1008 and a cement annulus 1010. The second casing 1006 preferably includes a tubular liner 1012 and a cement annulus 1014. In a preferred embodiment, the second casing 1006 is formed by expanding a tubular member substantially as described above with reference to Figs. 1-9c or below with reference to Figs. 11a-11f.

[000241] In a particularly preferred embodiment, an upper portion of the tubular liner 1012 overlaps with a lower portion of the tubular liner 1008. In a particularly preferred embodiment, an outer surface of the upper portion of the tubular liner 1012 includes one or more sealing members 1016 for providing a fluidic seal between the tubular liners 1008 and 1012.

[000242] Referring to Fig. 10b, in order to create a tie-back liner that extends from the overlap between the first and second casings, 1004 and 1006, an apparatus 1100 is preferably provided that includes an expandable mandrel or pig 1105, a tubular member

1110, a shoe 1115, one or more cup seals 1120, a fluid passage 1130, a fluid passage 1135, one or more fluid passages 1140, seals 1145, and a support member 1150.

[000243] The expandable mandrel or pig 1105 is coupled to and supported by the support member 1150. The expandable mandrel 1105 is preferably adapted to controllably expand in a radial direction. The expandable mandrel 1105 may comprise any number of conventional commercially available expandable mandrels modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the expandable mandrel 1105 comprises a hydraulic expansion tool substantially as disclosed in U.S. Pat. No. 5,348,095, the disclosure of which is incorporated herein by reference, modified in accordance with the teachings of the present disclosure.

[000244] The tubular member 1110 is coupled to and supported by the expandable mandrel 1105. The tubular member 1105 is expanded in the radial direction and extruded off of the expandable mandrel 1105. The tubular member 1110 may be fabricated from any number of materials such as, for example, Oilfield Country Tubular Goods, 13 chromium tubing or plastic piping. In a preferred embodiment, the tubular member 1110 is fabricated from Oilfield Country Tubular Goods.

[000245] The inner and outer diameters of the tubular member 1110 may range, for example, from approximately 0.75 to 47 inches and 1.05 to 48 inches, respectively. In a preferred embodiment, the inner and outer diameters of the tubular member 1110 range from about 3 to 15.5 inches and 3.5 to 16 inches, respectively in order to optimally provide coverage for typical oilfield casing sizes. The tubular member 1110 preferably comprises a solid member.

[000246] In a preferred embodiment, the upper end portion of the tubular member 1110 is slotted, perforated, or otherwise modified to catch or slow down the mandrel 1105 when it completes the extrusion of tubular member 1110. In a preferred embodiment, the length of the tubular member 1110 is limited to minimize the possibility of buckling. For typical tubular member 1110 materials, the length of the tubular member 1110 is preferably limited to between about 40 to 20,000 feet in length.

[000247] The shoe 1115 is coupled to the expandable mandrel 1105 and the tubular member 1110. The shoe 1115 includes the fluid passage 1135. The shoe 1115 may comprise any number of conventional commercially available shoes such as, for example, Super Seal II float shoe, Super Seal II Down-Jet float shoe or a guide shoe with a sealing sleeve for a latch down plug modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the shoe 1115 comprises an aluminum down-jet guide shoe with a sealing sleeve for a latch-down plug with side ports radiating off of the exit flow port available from Halliburton Energy Services in Dallas, TX, modified in accordance

with the teachings of the present disclosure, in order to optimally guide the tubular member 1100 to the overlap between the tubular member 1100 and the casing 1012, optimally fluidically isolate the interior of the tubular member 1100 after the latch down plug has seated, and optimally permit drilling out of the shoe 1115 after completion of the expansion and cementing operations.

[000248] In a preferred embodiment, the shoe 1115 includes one or more side outlet ports 1140 in fluidic communication with the fluid passage 1135. In this manner, the shoe 1115 injects hardenable fluidic sealing material into the region outside the shoe 1115 and tubular member 1110. In a preferred embodiment, the shoe 1115 includes one or more of the fluid passages 1140 each having an inlet geometry that can receive a dart and/or a ball sealing member. In this manner, the fluid passages 1140 can be sealed off by introducing a plug, dart and/or ball sealing elements into the fluid passage 1130.

[000249] The cup seal 1120 is coupled to and supported by the support member 1150. The cup seal 1120 prevents foreign materials from entering the interior region of the tubular member 1110 adjacent to the expandable mandrel 1105. The cup seal 1120 may comprise any number of conventional commercially available cup seals such as, for example, TP cups or Selective Injection Packer (SIP) cups modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the cup seal 1120 comprises a SIP cup, available from Halliburton Energy Services in Dallas, TX in order to optimally provide a barrier to debris and contain a body of lubricant.

[000250] The fluid passage 1130 permits fluidic materials to be transported to and from the interior region of the tubular member 1110 below the expandable mandrel 1105. The fluid passage 1130 is coupled to and positioned within the support member 1150 and the expandable mandrel 1105. The fluid passage 1130 preferably extends from a position adjacent to the surface to the bottom of the expandable mandrel 1105. The fluid passage 1130 is preferably positioned along a centerline of the apparatus 1100. The fluid passage 1130 is preferably selected to transport materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to optimally provide sufficient operating pressures to circulate fluids at operationally efficient rates.

[000251] The fluid passage 1135 permits fluidic materials to be transmitted from fluid passage 1130 to the interior of the tubular member 1110 below the mandrel 1105.

[000252] The fluid passages 1140 permits fluidic materials to be transported to and from the region exterior to the tubular member 1110 and shoe 1115. The fluid passages 1140 are coupled to and positioned within the shoe 1115 in fluidic communication with the interior region of the tubular member 1110 below the expandable mandrel 1105. The fluid passages

1140 preferably have a cross-sectional shape that permits a plug, or other similar device, to be placed in the fluid passages 1140 to thereby block further passage of fluidic materials. In this manner, the interior region of the tubular member 1110 below the expandable mandrel 1105 can be fluidically isolated from the region exterior to the tubular member 1105. This permits the interior region of the tubular member 1110 below the expandable mandrel 1105 to be pressurized.

[000253] The fluid passages 1140 are preferably positioned along the periphery of the shoe 1115. The fluid passages 1140 are preferably selected to convey materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to optimally fill the annular region between the tubular member 1110 and the tubular liner 1008 with fluidic materials. In a preferred embodiment, the fluid passages 1140 include an inlet geometry that can receive a dart and/or a ball sealing member. In this manner, the fluid passages 1140 can be sealed off by introducing a plug, dart and/or ball sealing elements into the fluid passage 1130. In a preferred embodiment, the apparatus 1100 includes a plurality of fluid passage 1140.

[000254] In an alternative embodiment, the base of the shoe 1115 includes a single inlet passage coupled to the fluid passages 1140 that is adapted to receive a plug, or other similar device, to permit the interior region of the tubular member 1110 to be fluidically isolated from the exterior of the tubular member 1110.

[000255] The seals 1145 are coupled to and supported by a lower end portion of the tubular member 1110. The seals 1145 are further positioned on an outer surface of the lower end portion of the tubular member 1110. The seals 1145 permit the overlapping joint between the upper end portion of the casing 1012 and the lower end portion of the tubular member 1110 to be fluidically sealed.

[000256] The seals 1145 may comprise any number of conventional commercially available seals such as, for example, lead, rubber, Teflon or epoxy seals modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the seals 1145 comprise seals molded from Stratalock epoxy available from Halliburton Energy Services in Dallas, TX in order to optimally provide a hydraulic seal in the overlapping joint and optimally provide load carrying capacity to withstand the range of typical tensile and compressive loads.

[000257] In a preferred embodiment, the seals 1145 are selected to optimally provide a sufficient frictional force to support the expanded tubular member 1110 from the tubular liner 1008. In a preferred embodiment, the frictional force provided by the seals 1145 ranges from about 1,000 to 1,000,000 lbf in tension and compression in order to optimally support the expanded tubular member 1110.

[000258] The support member 1150 is coupled to the expandable mandrel 1105, tubular member 1110, shoe 1115, and seal 1120. The support member 1150 preferably comprises an annular member having sufficient strength to carry the apparatus 1100 into the wellbore 1000. In a preferred embodiment, the support member 1150 further includes one or more conventional centralizers (not illustrated) to help stabilize the tubular member 1110.

[000259] In a preferred embodiment, a quantity of lubricant 1150 is provided in the annular region above the expandable mandrel 1105 within the interior of the tubular member 1110. In this manner, the extrusion of the tubular member 1110 off of the expandable mandrel 1105 is facilitated. The lubricant 1150 may comprise any number of conventional commercially available lubricants such as, for example, Lubriplate, chlorine based lubricants or Climax 1500 Antiseize (3100). In a preferred embodiment, the lubricant 1150 comprises Climax 1500 Antiseize (3100) available from Climax Lubricants and Equipment Co. in Houston, TX in order to optimally provide lubrication for the extrusion process.

[000260] In a preferred embodiment, the support member 1150 is thoroughly cleaned prior to assembly to the remaining portions of the apparatus 1100. In this manner, the introduction of foreign material into the apparatus 1100 is minimized. This minimizes the possibility of foreign material clogging the various flow passages and valves of the apparatus 1100 and to ensure that no foreign material interferes with the expansion mandrel 1105 during the extrusion process.

[000261] In a particularly preferred embodiment, the apparatus 1100 includes a packer 1155 coupled to the bottom section of the shoe 1115 for fluidically isolating the region of the wellbore 1000 below the apparatus 1100. In this manner, fluidic materials are prevented from entering the region of the wellbore 1000 below the apparatus 1100. The packer 1155 may comprise any number of conventional commercially available packers such as, for example, EZ Drill Packer, EZ SV Packer or a drillable cement retainer. In a preferred embodiment, the packer 1155 comprises an EZ Drill Packer available from Halliburton Energy Services in Dallas, TX. In an alternative embodiment, a high gel strength pill may be set below the tie-back in place of the packer 1155. In another alternative embodiment, the packer 1155 may be omitted.

[000262] In a preferred embodiment, before or after positioning the apparatus 1100 within the wellbore 1100, a couple of wellbore volumes are circulated in order to ensure that no foreign materials are located within the wellbore 1000 that might clog up the various flow passages and valves of the apparatus 1100 and to ensure that no foreign material interferes with the operation of the expansion mandrel 1105.

[000263] As illustrated in Fig. 10c, a hardenable fluidic sealing material 1160 is then pumped from a surface location into the fluid passage 1130. The material 1160 then passes

from the fluid passage 1130 into the interior region of the tubular member 1110 below the expandable mandrel 1105. The material 1160 then passes from the interior region of the tubular member 1110 into the fluid passages 1140. The material 1160 then exits the apparatus 1100 and fills the annular region between the exterior of the tubular member 1110 and the interior wall of the tubular liner 1008. Continued pumping of the material 1160 causes the material 1160 to fill up at least a portion of the annular region.

[000264] The material 1160 may be pumped into the annular region at pressures and flow rates ranging, for example, from about 0 to 5,000 psi and 0 to 1,500 gallons/min, respectively. In a preferred embodiment, the material 1160 is pumped into the annular region at pressures and flow rates specifically designed for the casing sizes being run, the annular spaces being filled, the pumping equipment available, and the properties of the fluid being pumped. The optimum flow rates and pressures are preferably calculated using conventional empirical methods.

[000265] The hardenable fluidic sealing material 1160 may comprise any number of conventional commercially available hardenable fluidic sealing materials such as, for example, slag mix, cement or epoxy. In a preferred embodiment, the hardenable fluidic sealing material 1160 comprises blended cements specifically designed for well section being tied-back, available from Halliburton Energy Services in Dallas, TX in order to optimally provide proper support for the tubular member 1110 while maintaining optimum flow characteristics so as to minimize operational difficulties during the displacement of cement in the annular region. The optimum blend of the blended cements are preferably determined using conventional empirical methods.

[000266] The annular region may be filled with the material 1160 in sufficient quantities to ensure that, upon radial expansion of the tubular member 1110, the annular region will be filled with material 1160.

[000267] As illustrated in Fig. 10d, once the annular region has been adequately filled with material 1160, one or more plugs 1165, or other similar devices, preferably are introduced into the fluid passages 1140 thereby fluidically isolating the interior region of the tubular member 1110 from the annular region external to the tubular member 1110. In a preferred embodiment, a non hardenable fluidic material 1161 is then pumped into the interior region of the tubular member 1110 below the mandrel 1105 causing the interior region to pressurize. In a particularly preferred embodiment, the one or more plugs 1165, or other similar devices, are introduced into the fluid passage 1140 with the introduction of the non hardenable fluidic material. In this manner, the amount of hardenable fluidic material within the interior of the tubular member 1110 is minimized.

[000268] As illustrated in Fig. 10e, once the interior region becomes sufficiently pressurized, the tubular member 1110 is extruded off of the expandable mandrel 1105. During the extrusion process, the expandable mandrel 1105 is raised out of the expanded portion of the tubular member 1110.

[000269] The plugs 1165 are preferably placed into the fluid passages 1140 by introducing the plugs 1165 into the fluid passage 1130 at a surface location in a conventional manner. The plugs 1165 may comprise any number of conventional commercially available devices from plugging a fluid passage such as, for example, brass balls, plugs, rubber balls, or darts modified in accordance with the teachings of the present disclosure.

[000270] In a preferred embodiment, the plugs 1165 comprise low density rubber balls. In an alternative embodiment, for a shoe 1105 having a common central inlet passage, the plugs 1165 comprise a single latch down dart.

[000271] After placement of the plugs 1165 in the fluid passages 1140, the non hardenable fluidic material 1161 is preferably pumped into the interior region of the tubular member 1110 below the mandrel 1105 at pressures and flow rates ranging from approximately 500 to 9,000 psi and 40 to 3,000 gallons/min.

[000272] In a preferred embodiment, after placement of the plugs 1165 in the fluid passages 1140, the non hardenable fluidic material 1161 is preferably pumped into the interior region of the tubular member 1110 below the mandrel 1105 at pressures and flow rates ranging from approximately 1200 to 8500 psi and 40 to 1250 gallons/min in order to optimally provide extrusion of typical tubulars.

[000273] For typical tubular members 1110, the extrusion of the tubular member 1110 off of the expandable mandrel 1105 will begin when the pressure of the interior region of the tubular member 1110 below the mandrel 1105 reaches, for example, approximately 1200 to 8500 psi. In a preferred embodiment, the extrusion of the tubular member 1110 off of the expandable mandrel 1105 begins when the pressure of the interior region of the tubular member 1110 below the mandrel 1105 reaches approximately 1200 to 8500 psi.

[000274] During the extrusion process, the expandable mandrel 1105 may be raised out of the expanded portion of the tubular member 1110 at rates ranging, for example, from about 0 to 5 ft/sec. In a preferred embodiment, during the extrusion process, the expandable mandrel 1105 is raised out of the expanded portion of the tubular member 1110 at rates ranging from about 0 to 2 ft/sec in order to optimally provide permit adjustment of operational parameters, and optimally ensure that the extrusion process will be completed before the material 1160 cures.

[000275] In a preferred embodiment, at least a portion 1180 of the tubular member 1110 has an internal diameter less than the outside diameter of the mandrel 1105. In this manner,

when the mandrel 1105 expands the section 1180 of the tubular member 1110, at least a portion of the expanded section 1180 effects a seal with at least the wellbore casing 1012. In a particularly preferred embodiment, the seal is effected by compressing the seals 1016 between the expanded section 1180 and the wellbore casing 1012. In a preferred embodiment, the contact pressure of the joint between the expanded section 1180 of the tubular member 1110 and the casing 1012 ranges from about 500 to 10,000 psi in order to optimally provide pressure to activate the sealing members 1145 and provide optimal resistance to ensure that the joint will withstand typical extremes of tensile and compressive loads.

[000276] In an alternative preferred embodiment, substantially all of the entire length of the tubular member 1110 has an internal diameter less than the outside diameter of the mandrel 1105. In this manner, extrusion of the tubular member 1110 by the mandrel 1105 results in contact between substantially all of the expanded tubular member 1110 and the existing casing 1008. In a preferred embodiment, the contact pressure of the joint between the expanded tubular member 1110 and the casings 1008 and 1012 ranges from about 500 to 10,000 psi in order to optimally provide pressure to activate the sealing members 1145 and provide optimal resistance to ensure that the joint will withstand typical extremes of tensile and compressive loads.

[000277] In a preferred embodiment, the operating pressure and flow rate of the material 1161 is controllably ramped down when the expandable mandrel 1105 reaches the upper end portion of the tubular member 1110. In this manner, the sudden release of pressure caused by the complete extrusion of the tubular member 1110 off of the expandable mandrel 1105 can be minimized. In a preferred embodiment, the operating pressure of the fluidic material 1161 is reduced in a substantially linear fashion from 100% to about 10% during the end of the extrusion process beginning when the mandrel 1105 has completed approximately all but about 5 feet of the extrusion process.

[000278] Alternatively, or in combination, a shock absorber is provided in the support member 1150 in order to absorb the shock caused by the sudden release of pressure.

[000279] Alternatively, or in combination, a mandrel catching structure is provided in the upper end portion of the tubular member 1110 in order to catch or at least decelerate the mandrel 1105.

[000280] Referring to Fig. 10f, once the extrusion process is completed, the expandable mandrel 1105 is removed from the wellbore 1000. In a preferred embodiment, either before or after the removal of the expandable mandrel 1105, the integrity of the fluidic seal of the joint between the upper portion of the tubular member 1110 and the upper portion of the tubular liner 1108 is tested using conventional methods. If the fluidic seal of the joint

between the upper portion of the tubular member 1110 and the upper portion of the tubular liner 1008 is satisfactory, then the uncured portion of the material 1160 within the expanded tubular member 1110 is then removed in a conventional manner. The material 1160 within the annular region between the tubular member 1110 and the tubular liner 1008 is then allowed to cure.

[000281] As illustrated in Fig. 10f, preferably any remaining cured material 1160 within the interior of the expanded tubular member 1110 is then removed in a conventional manner using a conventional drill string. The resulting tie-back liner of casing 1170 includes the expanded tubular member 1110 and an outer annular layer 1175 of cured material 1160.

[000282] As illustrated in Fig. 10g, the remaining bottom portion of the apparatus 1100 comprising the shoe 1115 and packer 1155 is then preferably removed by drilling out the shoe 1115 and packer 1155 using conventional drilling methods.

[000283] In a particularly preferred embodiment, the apparatus 1100 incorporates the apparatus 900.

[000284] Referring now to Figs. 11a-11f, an embodiment of an apparatus and method for hanging a tubular liner off of an existing wellbore casing will now be described. As illustrated in Fig. 11a, a wellbore 1200 is positioned in a subterranean formation 1205. The wellbore 1200 includes an existing cased section 1210 having a tubular casing 1215 and an annular outer layer of cement 1220.

[000285] In order to extend the wellbore 1200 into the subterranean formation 1205, a drill string 1225 is used in a well known manner to drill out material from the subterranean formation 1205 to form a new section 1230.

[000286] As illustrated in Fig. 11b, an apparatus 1300 for forming a wellbore casing in a subterranean formation is then positioned in the new section 1230 of the wellbore 100. The apparatus 1300 preferably includes an expandable mandrel or pig 1305, a tubular member 1310, a shoe 1315, a fluid passage 1320, a fluid passage 1330, a fluid passage 1335, seals 1340, a support member 1345, and a wiper plug 1350.

[000287] The expandable mandrel 1305 is coupled to and supported by the support member 1345. The expandable mandrel 1305 is preferably adapted to controllably expand in a radial direction. The expandable mandrel 1305 may comprise any number of conventional commercially available expandable mandrels modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the expandable mandrel 1305 comprises a hydraulic expansion tool substantially as disclosed in U.S. Pat. No. 5,348,095, the disclosure of which is incorporated herein by reference, modified in accordance with the teachings of the present disclosure.

[000288] The tubular member 1310 is coupled to and supported by the expandable mandrel 1305. The tubular member 1310 is preferably expanded in the radial direction and extruded off of the expandable mandrel 1305. The tubular member 1310 may be fabricated from any number of materials such as, for example, Oilfield Country Tubular Goods (OCTG), 13 chromium steel tubing/casing or plastic casing. In a preferred embodiment, the tubular member 1310 is fabricated from OCTG. The inner and outer diameters of the tubular member 1310 may range, for example, from approximately 0.75 to 47 inches and 1.05 to 48 inches, respectively. In a preferred embodiment, the inner and outer diameters of the tubular member 1310 range from about 3 to 15.5 inches and 3.5 to 16 inches, respectively in order to optimally provide minimal telescoping effect in the most commonly encountered wellbore sizes.

[000289] In a preferred embodiment, the tubular member 1310 includes an upper portion 1355, an intermediate portion 1360, and a lower portion 1365. In a preferred embodiment, the wall thickness and outer diameter of the upper portion 1355 of the tubular member 1310 range from about 3/8 to 1 1/2 inches and 3 1/2 to 16 inches, respectively. In a preferred embodiment, the wall thickness and outer diameter of the intermediate portion 1360 of the tubular member 1310 range from about 0.625 to 0.75 inches and 3 to 19 inches, respectively. In a preferred embodiment, the wall thickness and outer diameter of the lower portion 1365 of the tubular member 1310 range from about 3/8 to 1.5 inches and 3.5 to 16 inches, respectively.

[000290] In a particularly preferred embodiment, the wall thickness of the intermediate section 1360 of the tubular member 1310 is less than or equal to the wall thickness of the upper and lower sections, 1355 and 1365, of the tubular member 1310 in order to optimally facilitate the initiation of the extrusion process and optimally permit the placement of the apparatus in areas of the wellbore having tight clearances.

[000291] The tubular member 1310 preferably comprises a solid member. In a preferred embodiment, the upper end portion 1355 of the tubular member 1310 is slotted, perforated, or otherwise modified to catch or slow down the mandrel 1305 when it completes the extrusion of tubular member 1310. In a preferred embodiment, the length of the tubular member 1310 is limited to minimize the possibility of buckling. For typical tubular member 1310 materials, the length of the tubular member 1310 is preferably limited to between about 40 to 20,000 feet in length.

[000292] The shoe 1315 is coupled to the tubular member 1310. The shoe 1315 preferably includes fluid passages 1330 and 1335. The shoe 1315 may comprise any number of conventional commercially available shoes such as, for example, Super Seal II float shoe, Super Seal II Down-Jet float shoe or guide shoe with a sealing sleeve for a latch-

down plug modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the shoe 1315 comprises an aluminum down-jet guide shoe with a sealing sleeve for a latch-down plug available from Halliburton Energy Services in Dallas, TX, modified in accordance with the teachings of the present disclosure, in order to optimally guide the tubular member 1310 into the wellbore 1200, optimally fluidically isolate the interior of the tubular member 1310, and optimally permit the complete drill out of the shoe 1315 upon the completion of the extrusion and cementing operations.

[000293] In a preferred embodiment, the shoe 1315 further includes one or more side outlet ports in fluidic communication with the fluid passage 1330. In this manner, the shoe 1315 preferably injects hardenable fluidic sealing material into the region outside the shoe 1315 and tubular member 1310. In a preferred embodiment, the shoe 1315 includes the fluid passage 1330 having an inlet geometry that can receive a fluidic sealing member. In this manner, the fluid passage 1330 can be sealed off by introducing a plug, dart and/or ball sealing elements into the fluid passage 1330.

[000294] The fluid passage 1320 permits fluidic materials to be transported to and from the interior region of the tubular member 1310 below the expandable mandrel 1305. The fluid passage 1320 is coupled to and positioned within the support member 1345 and the expandable mandrel 1305. The fluid passage 1320 preferably extends from a position adjacent to the surface to the bottom of the expandable mandrel 1305. The fluid passage 1320 is preferably positioned along a centerline of the apparatus 1300. The fluid passage 1320 is preferably selected to transport materials such as cement, drilling mud, or epoxies at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to optimally provide sufficient operating pressures to circulate fluids at operationally efficient rates.

[000295] The fluid passage 1330 permits fluidic materials to be transported to and from the region exterior to the tubular member 1310 and shoe 1315. The fluid passage 1330 is coupled to and positioned within the shoe 1315 in fluidic communication with the interior region 1370 of the tubular member 1310 below the expandable mandrel 1305. The fluid passage 1330 preferably has a cross-sectional shape that permits a plug, or other similar device, to be placed in fluid passage 1330 to thereby block further passage of fluidic materials. In this manner, the interior region 1370 of the tubular member 1310 below the expandable mandrel 1305 can be fluidically isolated from the region exterior to the tubular member 1310. This permits the interior region 1370 of the tubular member 1310 below the expandable mandrel 1305 to be pressurized. The fluid passage 1330 is preferably positioned substantially along the centerline of the apparatus 1300.

[000296] The fluid passage 1330 is preferably selected to convey materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to optimally fill the annular region between the tubular member 1310 and the new section 1230 of the wellbore 1200 with fluidic materials. In a preferred embodiment, the fluid passage 1330 includes an inlet geometry that can receive a dart and/or a ball sealing member. In this manner, the fluid passage 1330 can be sealed off by introducing a plug, dart and/or ball sealing elements into the fluid passage 1320.

[000297] The fluid passage 1335 permits fluidic materials to be transported to and from the region exterior to the tubular member 1310 and shoe 1315. The fluid passage 1335 is coupled to and positioned within the shoe 1315 in fluidic communication with the fluid passage 1330. The fluid passage 1335 is preferably positioned substantially along the centerline of the apparatus 1300. The fluid passage 1335 is preferably selected to convey materials such as cement, drilling mud or epoxies at flow rates and pressures ranging from about 0 to 3,000 gallons/minute and 0 to 9,000 psi in order to optimally fill the annular region between the tubular member 1310 and the new section 1230 of the wellbore 1200 with fluidic materials.

[000298] The seals 1340 are coupled to and supported by the upper end portion 1355 of the tubular member 1310. The seals 1340 are further positioned on an outer surface of the upper end portion 1355 of the tubular member 1310. The seals 1340 permit the overlapping joint between the lower end portion of the casing 1215 and the upper portion 1355 of the tubular member 1310 to be fluidically sealed. The seals 1340 may comprise any number of conventional commercially available seals such as, for example, lead, rubber, Teflon, or epoxy seals modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the seals 1340 comprise seals molded from Stratalock epoxy available from Halliburton Energy Services in Dallas, TX in order to optimally provide a hydraulic seal in the annulus of the overlapping joint while also creating optimal load bearing capability to withstand typical tensile and compressive loads.

[000299] In a preferred embodiment, the seals 1340 are selected to optimally provide a sufficient frictional force to support the expanded tubular member 1310 from the existing casing 1215. In a preferred embodiment, the frictional force provided by the seals 1340 ranges from about 1,000 to 1,000,000 lbf in order to optimally support the expanded tubular member 1310.

[000300] The support member 1345 is coupled to the expandable mandrel 1305, tubular member 1310, shoe 1315, and seals 1340. The support member 1345 preferably comprises an annular member having sufficient strength to carry the apparatus 1300 into the new

section 1230 of the wellbore 1200. In a preferred embodiment, the support member 1345 further includes one or more conventional centralizers (not illustrated) to help stabilize the tubular member 1310.

[000301] In a preferred embodiment, the support member 1345 is thoroughly cleaned prior to assembly to the remaining portions of the apparatus 1300. In this manner, the introduction of foreign material into the apparatus 1300 is minimized. This minimizes the possibility of foreign material clogging the various flow passages and valves of the apparatus 1300 and to ensure that no foreign material interferes with the expansion process.

[000302] The wiper plug 1350 is coupled to the mandrel 1305 within the interior region 1370 of the tubular member 1310. The wiper plug 1350 includes a fluid passage 1375 that is coupled to the fluid passage 1320. The wiper plug 1350 may comprise one or more conventional commercially available wiper plugs such as, for example, Multiple Stage Cementer latch-down plugs, Omega latch-down plugs or three-wiper latch-down plug modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the wiper plug 1350 comprises a Multiple Stage Cementer latch-down plug available from Halliburton Energy Services in Dallas, TX modified in a conventional manner for releasable attachment to the expansion mandrel 1305.

[000303] In a preferred embodiment, before or after positioning the apparatus 1300 within the new section 1230 of the wellbore 1200, a couple of wellbore volumes are circulated in order to ensure that no foreign materials are located within the wellbore 1200 that might clog up the various flow passages and valves of the apparatus 1300 and to ensure that no foreign material interferes with the extrusion process.

[000304] As illustrated in Fig. 11c, a hardenable fluidic sealing material 1380 is then pumped from a surface location into the fluid passage 1320. The material 1380 then passes from the fluid passage 1320, through the fluid passage 1375, and into the interior region 1370 of the tubular member 1310 below the expandable mandrel 1305. The material 1380 then passes from the interior region 1370 into the fluid passage 1330. The material 1380 then exits the apparatus 1300 via the fluid passage 1335 and fills the annular region 1390 between the exterior of the tubular member 1310 and the interior wall of the new section 1230 of the wellbore 1200. Continued pumping of the material 1380 causes the material 1380 to fill up at least a portion of the annular region 1390.

[000305] The material 1380 may be pumped into the annular region 1390 at pressures and flow rates ranging, for example, from about 0 to 5000 psi and 0 to 1,500 gallons/min, respectively. In a preferred embodiment, the material 1380 is pumped into the annular region 1390 at pressures and flow rates ranging from about 0 to 5000 psi and 0 to 1,500 gallons/min, respectively, in order to optimally fill the annular region between the tubular

member 1310 and the new section 1230 of the wellbore 1200 with the hardenable fluidic sealing material 1380.

[000306] The hardenable fluidic sealing material 1380 may comprise any number of conventional commercially available hardenable fluidic sealing materials such as, for example, slag mix, cement or epoxy. In a preferred embodiment, the hardenable fluidic sealing material 1380 comprises blended cements designed specifically for the well section being drilled and available from Halliburton Energy Services in order to optimally provide support for the tubular member 1310 during displacement of the material 1380 in the annular region 1390. The optimum blend of the cement is preferably determined using conventional empirical methods.

[000307] The annular region 1390 preferably is filled with the material 1380 in sufficient quantities to ensure that, upon radial expansion of the tubular member 1310, the annular region 1390 of the new section 1230 of the wellbore 1200 will be filled with material 1380.

[000308] As illustrated in Fig. 11d, once the annular region 1390 has been adequately filled with material 1380, a wiper dart 1395, or other similar device, is introduced into the fluid passage 1320. The wiper dart 1395 is preferably pumped through the fluid passage 1320 by a non hardenable fluidic material 1381. The wiper dart 1395 then preferably engages the wiper plug 1350.

[000309] As illustrated in Fig. 11e, in a preferred embodiment, engagement of the wiper dart 1395 with the wiper plug 1350 causes the wiper plug 1350 to decouple from the mandrel 1305. The wiper dart 1395 and wiper plug 1350 then preferably will lodge in the fluid passage 1330, thereby blocking fluid flow through the fluid passage 1330, and fluidically isolating the interior region 1370 of the tubular member 1310 from the annular region 1390. In a preferred embodiment, the non hardenable fluidic material 1381 is then pumped into the interior region 1370 causing the interior region 1370 to pressurize. Once the interior region 1370 becomes sufficiently pressurized, the tubular member 1310 is extruded off of the expandable mandrel 1305. During the extrusion process, the expandable mandrel 1305 is raised out of the expanded portion of the tubular member 1310 by the support member 1345.

[000310] The wiper dart 1395 is preferably placed into the fluid passage 1320 by introducing the wiper dart 1395 into the fluid passage 1320 at a surface location in a conventional manner. The wiper dart 1395 may comprise any number of conventional commercially available devices from plugging a fluid passage such as, for example, Multiple Stage Cementer latch-down plugs, Omega latch-down plugs or three wiper latch-down plug/dart modified in accordance with the teachings of the present disclosure. In a preferred embodiment, the wiper dart 1395 comprises a three wiper latch-down plug modified to latch

and seal in the Multiple Stage Cementer latch down plug 1350. The three wiper latch-down plug is available from Halliburton Energy Services in Dallas, TX.

[000311] After blocking the fluid passage 1330 using the wiper plug 1330 and wiper dart 1395, the non hardenable fluidic material 1381 may be pumped into the interior region 1370 at pressures and flow rates ranging, for example, from approximately 0 to 5000 psi and 0 to 1,500 gallons/min in order to optimally extrude the tubular member 1310 off of the mandrel 1305. In this manner, the amount of hardenable fluidic material within the interior of the tubular member 1310 is minimized.

[000312] In a preferred embodiment, after blocking the fluid passage 1330, the non hardenable fluidic material 1381 is preferably pumped into the interior region 1370 at pressures and flow rates ranging from approximately 500 to 9,000 psi and 40 to 3,000 gallons/min in order to optimally provide operating pressures to maintain the expansion process at rates sufficient to permit adjustments to be made in operating parameters during the extrusion process.

[000313] For typical tubular members 1310, the extrusion of the tubular member 1310 off of the expandable mandrel 1305 will begin when the pressure of the interior region 1370 reaches, for example, approximately 500 to 9,000 psi. In a preferred embodiment, the extrusion of the tubular member 1310 off of the expandable mandrel 1305 is a function of the tubular member diameter, wall thickness of the tubular member, geometry of the mandrel, the type of lubricant, the composition of the shoe and tubular member, and the yield strength of the tubular member. The optimum flow rate and operating pressures are preferably determined using conventional empirical methods.

[000314] During the extrusion process, the expandable mandrel 1305 may be raised out of the expanded portion of the tubular member 1310 at rates ranging, for example, from about 0 to 5 ft/sec. In a preferred embodiment, during the extrusion process, the expandable mandrel 1305 may be raised out of the expanded portion of the tubular member 1310 at rates ranging from about 0 to 2 ft/sec in order to optimally provide an efficient process, optimally permit operator adjustment of operation parameters, and ensure optimal completion of the extrusion process before curing of the material 1380.

[000315] When the upper end portion 1355 of the tubular member 1310 is extruded off of the expandable mandrel 1305, the outer surface of the upper end portion 1355 of the tubular member 1310 will preferably contact the interior surface of the lower end portion of the casing 1215 to form an fluid tight overlapping joint. The contact pressure of the overlapping joint may range, for example, from approximately 50 to 20,000 psi. In a preferred embodiment, the contact pressure of the overlapping joint ranges from approximately 400 to 10,000 psi in order to optimally provide contact pressure sufficient to ensure annular sealing

and provide enough resistance to withstand typical tensile and compressive loads. In a particularly preferred embodiment, the sealing members 1340 will ensure an adequate fluidic and gaseous seal in the overlapping joint.

[000316] In a preferred embodiment, the operating pressure and flow rate of the non hardenable fluidic material 1381 is controllably ramped down when the expandable mandrel 1305 reaches the upper end portion 1355 of the tubular member 1310. In this manner, the sudden release of pressure caused by the complete extrusion of the tubular member 1310 off of the expandable mandrel 1305 can be minimized. In a preferred embodiment, the operating pressure is reduced in a substantially linear fashion from 100% to about 10% during the end of the extrusion process beginning when the mandrel 1305 has completed approximately all but about 5 feet of the extrusion process.

[000317] Alternatively, or in combination, a shock absorber is provided in the support member 1345 in order to absorb the shock caused by the sudden release of pressure.

[000318] Alternatively, or in combination, a mandrel catching structure is provided in the upper end portion 1355 of the tubular member 1310 in order to catch or at least decelerate the mandrel 1305.

[000319] Once the extrusion process is completed, the expandable mandrel 1305 is removed from the wellbore 1200. In a preferred embodiment, either before or after the removal of the expandable mandrel 1305, the integrity of the fluidic seal of the overlapping joint between the upper portion 1355 of the tubular member 1310 and the lower portion of the casing 1215 is tested using conventional methods. If the fluidic seal of the overlapping joint between the upper portion 1355 of the tubular member 1310 and the lower portion of the casing 1215 is satisfactory, then the uncured portion of the material 1380 within the expanded tubular member 1310 is then removed in a conventional manner. The material 1380 within the annular region 1390 is then allowed to cure.

[000320] As illustrated in Fig. 11f, preferably any remaining cured material 1380 within the interior of the expanded tubular member 1310 is then removed in a conventional manner using a conventional drill string. The resulting new section of casing 1400 includes the expanded tubular member 1310 and an outer annular layer 1405 of cured material 305. The bottom portion of the apparatus 1300 comprising the shoe 1315 may then be removed by drilling out the shoe 1315 using conventional drilling methods.

[000321] Referring now to Figs. 12a and 12b, an expansion device 1500 is illustrated. Expansion device 1500 includes an elongated base member 1502 having a first end 1502a, a second end 1502b positioned opposite the first end 1502a, and a base diameter D_B . An expansion member 1504 extends circumferentially from the base member 1502 to an expansion diameter D_E . A plurality of expansion surfaces 1506a and 1506b are positioned

on opposite sides of the expansion member 1504 and increase in diameter from the base diameter D_B to the expansion diameter D_E . A coupling channel 1508 is defined by the base member 1502 about the circumference of the base member 1502 and positioned between expansion surface 1506a and first end 1502a of base member 1502. A sealing volume 1510 is defined by an outer circumferential edge of the base member 1502 and the first end 1502a of the base member 1502 and is positioned adjacent the first end 1502a of the base member 1502. A fluid passageway 1512 is defined by the base member 1502 and extends along the length of the base member 1502 from the first end 1502a to the second end 1502b. In an exemplary embodiment, an angle X between the expansion surface 1506a and the base member 1502 and an angle Y between the expansion surface 1506b and the base member 1502 are substantially equal. In an exemplary embodiment, the expansion device 1500 may be a conventional expansion device known in the art and/or an expansion device described in (1) U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (2) U.S. patent application serial no. 09/510,913, attorney docket no. 25791.7.02, filed on 2/23/2000, which claims priority from provisional application 60/121,702, filed on 2/25/99, (3) U.S. patent application serial no. 09/502,350, attorney docket no. 25791.8.02, filed on 2/10/2000, which claims priority from provisional application 60/119,611, filed on 2/11/99, (4) U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (5) U.S. patent application serial no. 10/169,434, attorney docket no. 25791.10.04, filed on 7/1/02, which claims priority from provisional application 60/183,546, filed on 2/18/00, (6) U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (7) U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (8) U.S. patent number 6,575,240, which was filed as patent application serial no. 09/511,941, attorney docket no. 25791.16.02, filed on 2/24/2000, which claims priority from provisional application 60/121,907, filed on 2/26/99, (9) U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (10) U.S. patent application serial no. 09/981,916, attorney docket no. 25791.18, filed on 10/18/01 as a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338,

attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (11) U.S. patent number 6,604,763, which was filed as application serial no. 09/559,122, attorney docket no. 25791.23.02, filed on 4/26/2000, which claims priority from provisional application 60/131,106, filed on 4/26/99, (12) U.S. patent application serial no. 10/030,593, attorney docket no. 25791.25.08, filed on 1/8/02, which claims priority from provisional application 60/146,203, filed on 7/29/99, (13) U.S. provisional patent application serial no. 60/143,039, attorney docket no. 25791.26, filed on 7/9/99, (14) U.S. patent application serial no. 10/111,982, attorney docket no. 25791.27.08, filed on 4/30/02, which claims priority from provisional patent application serial no. 60/162,671, attorney docket no. 25791.27, filed on 11/1/1999, (15) U.S. provisional patent application serial no. 60/154,047, attorney docket no. 25791.29, filed on 9/16/1999, (16) U.S. provisional patent application serial no. 60/438,828, attorney docket no. 25791.31, filed on 1/9/03, (17) U.S. patent number 6,564,875, which was filed as application serial no. 09/679,907, attorney docket no. 25791.34.02, on 10/5/00, which claims priority from provisional patent application serial no. 60/159,082, attorney docket no. 25791.34, filed on 10/12/1999, (18) U.S. patent application serial no. 10/089,419, filed on 3/27/02, attorney docket no. 25791.36.03, which claims priority from provisional patent application serial no. 60/159,039, attorney docket no. 25791.36, filed on 10/12/1999, (19) U.S. patent application serial no. 09/679,906, filed on 10/5/00, attorney docket no. 25791.37.02, which claims priority from provisional patent application serial no. 60/159,033, attorney docket no. 25791.37, filed on 10/12/1999, (20) U.S. patent application serial no. 10/303,992, filed on 11/22/02, attorney docket no. 25791.38.07, which claims priority from provisional patent application serial no. 60/212,359, attorney docket no. 25791.38, filed on 6/19/2000, (21) U.S. provisional patent application serial no. 60/165,228, attorney docket no. 25791.39, filed on 11/12/1999, (22) U.S. provisional patent application serial no. 60/455,051, attorney docket no. 25791.40, filed on 3/14/03, (23) PCT application US02/2477, filed on 6/26/02, attorney docket no. 25791.44.02, which claims priority from U.S. provisional patent application serial no. 60/303,711, attorney docket no. 25791.44, filed on 7/6/01, (24) U.S. patent application serial no. 10/311,412, filed on 12/12/02, attorney docket no. 25791.45.07, which claims priority from provisional patent application serial no. 60/221,443, attorney docket no. 25791.45, filed on 7/28/2000, (25) U.S. patent application serial no. 10/, filed on 12/18/02, attorney docket no. 25791.46.07, which claims priority from provisional patent application serial no. 60/221,645, attorney docket no. 25791.46, filed on 7/28/2000, (26) U.S. patent application serial no. 10/322,947, filed on 1/22/03, attorney docket no. 25791.47.03, which claims priority from provisional patent application serial no. 60/233,638, attorney docket no. 25791.47, filed on 9/18/2000, (27) U.S. patent application serial no. 10/406,648, filed on

3/31/03, attorney docket no. 25791.48.06, which claims priority from provisional patent application serial no. 60/237,334, attorney docket no. 25791.48, filed on 10/2/2000, (28) PCT application US02/04353, filed on 2/14/02, attorney docket no. 25791.50.02, which claims priority from U.S. provisional patent application serial no. 60/270,007, attorney docket no. 25791.50, filed on 2/20/2001, (29) U.S. patent application serial no. 10/465,835, filed on 6/13/03, attorney docket no. 25791.51.06, which claims priority from provisional patent application serial no. 60/262,434, attorney docket no. 25791.51, filed on 1/17/2001, (30) U.S. patent application serial no. 10/465,831, filed on 6/13/03, attorney docket no. 25791.52.06, which claims priority from U.S. provisional patent application serial no. 60/259,486, attorney docket no. 25791.52, filed on 1/3/2001, (31) U.S. provisional patent application serial no. 60/452,303, filed on 3/5/03, attorney docket no. 25791.53, (32) U.S. patent number 6,470,966, which was filed as patent application serial number 09/850,093, filed on 5/7/01, attorney docket no. 25791.55, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (33) U.S. patent number 6,561,227, which was filed as patent application serial number 09/852,026, filed on 5/9/01, attorney docket no. 25791.56, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (34) U.S. patent application serial number 09/852,027, filed on 5/9/01, attorney docket no. 25791.57, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (35) PCT Application US02/25608, attorney docket no. 25791.58.02, filed on 8/13/02, which claims priority from provisional application 60/318,021, filed on 9/7/01, attorney docket no. 25791.58, (36) PCT Application US02/24399, attorney docket no. 25791.59.02, filed on 8/1/02, which claims priority from U.S. provisional patent application serial no. 60/313,453, attorney docket no. 25791.59, filed on 8/20/2001, (37) PCT Application US02/29856, attorney docket no. 25791.60.02, filed on 9/19/02, which claims priority from U.S. provisional patent application serial no. 60/326,886, attorney docket no. 25791.60, filed on 10/3/2001, (38) PCT Application US02/20256, attorney docket no. 25791.61.02, filed on 6/26/02, which claims priority from U.S. provisional patent application serial no. 60/303,740, attorney docket no. 25791.61, filed on 7/6/2001, (39) U.S. patent application serial no. 09/962,469, filed on 9/25/01, attorney docket no. 25791.62, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent

6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (40) U.S. patent application serial no. 09/962,470, filed on 9/25/01, attorney docket no. 25791.63, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (41) U.S. patent application serial no. 09/962,471, filed on 9/25/01, attorney docket no. 25791.64, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (42) U.S. patent application serial no. 09/962,467, filed on 9/25/01, attorney docket no. 25791.65, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (43) U.S. patent application serial no. 09/962,468, filed on 9/25/01, attorney docket no. 25791.66, which is a divisional of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (44) PCT application US 02/25727, filed on 8/14/02, attorney docket no. 25791.67.03, which claims priority from U.S. provisional patent application serial no. 60/317,985, attorney docket no. 25791.67, filed on 9/6/2001, and U.S. provisional patent application serial no. 60/318,386, attorney docket no. 25791.67.02, filed on 9/10/2001, (45) PCT application US 02/39425, filed on 12/10/02, attorney docket no. 25791.68.02, which claims priority from U.S. provisional patent application serial no. 60/343,674, attorney docket no. 25791.68, filed on 12/27/2001, (46) U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001, (now U.S. Patent 6,634,431 which issued 10/21/2003), which is a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (47) U.S. utility patent application serial no. 10/516,467, attorney docket no. 25791.70, filed on 12/10/01, which is a continuation application of U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001, (now U.S. Patent 6,634,431 which issued 10/21/2003), which is a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (48) PCT application US 03/00609, filed on 1/9/03, attorney docket no. 25791.71.02, which

claims priority from U.S. provisional patent application serial no. 60/357,372, attorney docket no. 25791.71, filed on 2/15/02, (49) U.S. patent application serial no. 10/074,703, attorney docket no. 25791.74, filed on 2/12/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (50) U.S. patent application serial no. 10/074,244, attorney docket no. 25791.75, filed on 2/12/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (51) U.S. patent application serial no. 10/076,660, attorney docket no. 25791.76, filed on 2/15/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (52) U.S. patent application serial no. 10/076,661, attorney docket no. 25791.77, filed on 2/15/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (53) U.S. patent application serial no. 10/076,659, attorney docket no. 25791.78, filed on 2/15/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (54) U.S. patent application serial no. 10/078,928, attorney docket no. 25791.79, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (55) U.S. patent application serial no. 10/078,922, attorney docket no. 25791.80, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (56) U.S. patent application serial no. 10/078,921, attorney docket no. 25791.81, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (57) U.S. patent application serial no. 10/261,928, attorney docket no. 25791.82, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no.

25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (58) U.S. patent application serial no. 10/079,276, attorney docket no. 25791.83, filed on 2/20/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (59) U.S. patent application serial no. 10/262,009, attorney docket no. 25791.84, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (60) U.S. patent application serial no. 10/092,481, attorney docket no. 25791.85, filed on 3/7/02, which is a divisional of U.S. patent number 6,568,471, which was filed as patent application serial no. 09/512,895, attorney docket no. 25791.12.02, filed on 2/24/2000, which claims priority from provisional application 60/121,841, filed on 2/26/99, (61) U.S. patent application serial no. 10/261,926, attorney docket no. 25791.86, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (62) PCT application US 02/36157, filed on 11/12/02, attorney docket no. 25791.87.02, which claims priority from U.S. provisional patent application serial no. 60/338,996, attorney docket no. 25791.87, filed on 11/12/01, (63) PCT application US 02/36267, filed on 11/12/02, attorney docket no. 25791.88.02, which claims priority from U.S. provisional patent application serial no. 60/339,013, attorney docket no. 25791.88, filed on 11/12/01, (64) PCT application US 03/11765, filed on 4/16/03, attorney docket no. 25791.89.02, which claims priority from U.S. provisional patent application serial no. 60/383,917, attorney docket no. 25791.89, filed on 5/29/02, (65) PCT application US 03/15020, filed on 5/12/03, attorney docket no. 25791.90.02, which claims priority from U.S. provisional patent application serial no. 60/391,703, attorney docket no. 25791.90, filed on 6/26/02, (66) PCT application US 02/39418, filed on 12/10/02, attorney docket no. 25791.92.02, which claims priority from U.S. provisional patent application serial no. 60/346,309, attorney docket no. 25791.92, filed on 1/7/02, (67) PCT application US 03/06544, filed on 3/4/03, attorney docket no. 25791.93.02, which claims priority from U.S. provisional patent application serial no. 60/372,048, attorney docket no. 25791.93, filed on 4/12/02, (68) U.S. patent application serial no. 10/331,718, attorney docket no. 25791.94, filed on 12/30/02, which is a divisional U.S. patent application serial no. 09/679,906, filed on 10/5/00, attorney docket no. 25791.37.02, which claims priority from provisional patent application serial no. 60/159,033, attorney docket no. 25791.37, filed on 10/12/1999, (69) PCT application US 03/04837, filed on 2/29/03, attorney docket no. 25791.95.02, which

claims priority from U.S. provisional patent application serial no. 60/363,829, attorney docket no. 25791.95, filed on 3/13/02, (70) U.S. patent application serial no. 10/261,927, attorney docket no. 25791.97, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (71) U.S. patent application serial no. 10/262,008, attorney docket no. 25791.98, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (72) U.S. patent application serial no. 10/261,925, attorney docket no. 25791.99, filed on 10/1/02, which is a divisional of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (73) U.S. patent application serial no. 10/199,524, attorney docket no. 25791.100, filed on 7/19/02, which is a continuation of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (74) PCT application US 03/10144, filed on 3/28/03, attorney docket no. 25791.101.02, which claims priority from U.S. provisional patent application serial no. 60/372,632, attorney docket no. 25791.101, filed on 4/15/02, (75) U.S. provisional patent application serial no. 60/412,542, attorney docket no. 25791.102, filed on 9/20/02, (76) PCT application US 03/14153, filed on 5/6/03, attorney docket no. 25791.104.02, which claims priority from U.S. provisional patent application serial no. 60/380,147, attorney docket no. 25791.104, filed on 5/6/02, (77) PCT application US 03/19993, filed on 6/24/03, attorney docket no. 25791.106.02, which claims priority from U.S. provisional patent application serial no. 60/397,284, attorney docket no. 25791.106, filed on 7/19/02, (78) PCT application US 03/13787, filed on 5/5/03, attorney docket no. 25791.107.02, which claims priority from U.S. provisional patent application serial no. 60/387,486, attorney docket no. 25791.107, filed on 6/10/02, (79) PCT application US 03/18530, filed on 6/11/03, attorney docket no. 25791.108.02, which claims priority from U.S. provisional patent application serial no. 60/387,961, attorney docket no. 25791.108, filed on 6/12/02, (80) PCT application US 03/20694, filed on 7/1/03, attorney docket no. 25791.110.02, which claims priority from U.S. provisional patent application serial no. 60/398,061, attorney docket no. 25791.110, filed on 7/24/02, (81) PCT application US 03/20870, filed on 7/2/03, attorney docket no. 25791.111.02, which claims priority from U.S. provisional patent application serial no. 60/399,240, attorney docket no. 25791.111, filed on 7/29/02, (82) U.S. provisional patent application serial no. 60/412,487, attorney docket no.

25791.112, filed on 9/20/02, (83) U.S. provisional patent application serial no. 60/412,488, attorney docket no. 25791.114, filed on 9/20/02, (84) U.S. patent application serial no. 10/280,356, attorney docket no. 25791.115, filed on 10/25/02, which is a continuation of U.S. patent number 6,470,966, which was filed as patent application serial number 09/850,093, filed on 5/7/01, attorney docket no. 25791.55, as a divisional application of U.S. Patent Number 6,497,289, which was filed as U.S. Patent Application serial no. 09/454,139, attorney docket no. 25791.03.02, filed on 12/3/1999, which claims priority from provisional application 60/111,293, filed on 12/7/98, (85) U.S. provisional patent application serial no. 60/412,177, attorney docket no. 25791.117, filed on 9/20/02, (86) U.S. provisional patent application serial no. 60/412,653, attorney docket no. 25791.118, filed on 9/20/02, (87) U.S. provisional patent application serial no. 60/405,610, attorney docket no. 25791.119, filed on 8/23/02, (88) U.S. provisional patent application serial no. 60/405,394, attorney docket no. 25791.120, filed on 8/23/02, (89) U.S. provisional patent application serial no. 60/412,544, attorney docket no. 25791.121, filed on 9/20/02, (90) PCT application US 03/24779, filed on 8/8/03, attorney docket no. 25791.125.02, which claims priority from U.S. provisional patent application serial no. 60/407,442, attorney docket no. 25791.125, filed on 8/30/02, (91) U.S. provisional patent application serial no. 60/423,363, attorney docket no. 25791.126, filed on 12/10/02, (92) U.S. provisional patent application serial no. 60/412,196, attorney docket no. 25791.127, filed on 9/20/02, (93) U.S. provisional patent application serial no. 60/412,187, attorney docket no. 25791.128, filed on 9/20/02, (94) U.S. provisional patent application serial no. 60/412,371, attorney docket no. 25791.129, filed on 9/20/02, (95) U.S. patent application serial no. 10/382,325, attorney docket no. 25791.145, filed on 3/5/03, which is a continuation of U.S. patent number 6,557,640, which was filed as patent application serial no. 09/588,946, attorney docket no. 25791.17.02, filed on 6/7/2000, which claims priority from provisional application 60/137,998, filed on 6/7/99, (96) U.S. patent application serial no. 10/624,842, attorney docket no. 25791.151, filed on 7/22/03, which is a divisional of U.S. patent application serial no. 09/502,350, attorney docket no. 25791.8.02, filed on 2/10/2000, which claims priority from provisional application 60/119,611, filed on 2/11/99, (97) U.S. provisional patent application serial no. 60/431,184, attorney docket no. 25791.157, filed on 12/5/02, (98) U.S. provisional patent application serial no. 60/448,526, attorney docket no. 25791.185, filed on 2/18/03, (99) U.S. provisional patent application serial no. 60/461,539, attorney docket no. 25791.186, filed on 4/9/03, (100) U.S. provisional patent application serial no. 60/462,750, attorney docket no. 25791.193, filed on 4/14/03, (101) U.S. provisional patent application serial no. 60/436,106, attorney docket no. 25791.200, filed on 12/23/02, (102) U.S. provisional patent application serial no. 60/442,942, attorney docket no. 25791.213, filed on 1/27/03, (103) U.S. provisional patent application

serial no. 60/442,938, attorney docket no. 25791.225, filed on 1/27/03, (104) U.S. provisional patent application serial no. 60/418,687, attorney docket no. 25791.228, filed on 4/18/03, (105) U.S. provisional patent application serial no. 60/454,896, attorney docket no. 25791.236, filed on 3/14/03, (106) U.S. provisional patent application serial no. 60/450,504, attorney docket no. 25791.238, filed on 2/26/03, (107) U.S. provisional patent application serial no. 60/451,152, attorney docket no. 25791.239, filed on 3/9/03, (108) U.S. provisional patent application serial no. 60/455,124, attorney docket no. 25791.241, filed on 3/17/03, (109) U.S. provisional patent application serial no. 60/453,678, attorney docket no. 25791.253, filed on 3/11/03, (110) U.S. patent application serial no. 10/421,682, attorney docket no. 25791.256, filed on 4/23/03, which is a continuation of U.S. patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application 60/124,042, filed on 3/11/99, (111) U.S. provisional patent application serial no. 60/457,965, attorney docket no. 25791.260, filed on 3/27/03, (112) U.S. provisional patent application serial no. 60/455,718, attorney docket no. 25791.262, filed on 3/18/03, (113) U.S. patent number 6,550,821, which was filed as patent application serial no. 09/811,734, filed on 3/19/01, (114) U.S. patent application serial no. 10/436,467, attorney docket no. 25791.268, filed on 5/12/03, which is a continuation of U.S. patent number 6,604,763, which was filed as application serial no. 09/559,122, attorney docket no. 25791.23.02, filed on 4/26/2000, which claims priority from provisional application 60/131,106, filed on 4/26/99, (115) U.S. provisional patent application serial no. 60/459,776, attorney docket no. 25791.270, filed on 4/2/03, (116) U.S. provisional patent application serial no. 60/461,094, attorney docket no. 25791.272, filed on 4/8/03, (117) U.S. provisional patent application serial no. 60/461,038, attorney docket no. 25791.273, filed on 4/7/03, (118) U.S. provisional patent application serial no. 60/463,586, attorney docket no. 25791.277, filed on 4/17/03, (119) U.S. provisional patent application serial no. 60/472,240, attorney docket no. 25791.286, filed on 5/20/03, (120) U.S. patent application serial no. 10/619,285, attorney docket no. 25791.292, filed on 7/14/03, which is a continuation-in-part of U.S. utility patent application serial no. 09/969,922, attorney docket no. 25791.69, filed on 10/3/2001, (now U.S. Patent 6,634,431 which issued 10/21/2003), which is a continuation-in-part application of U.S. patent no. 6,328,113, which was filed as U.S. Patent Application serial number 09/440,338, attorney docket number 25791.9.02, filed on 11/15/99, which claims priority from provisional application 60/108,558, filed on 11/16/98, (121) U.S. utility patent application serial no. 10/418,688, attorney docket no. 25791.257, which was filed on 4/18/03, as a division of U.S. utility patent application serial no. 09/523,468, attorney docket no. 25791.11.02, filed on 3/10/2000, (now U.S. Patent 6,640,903 which issued 11/4/2003), which claims priority from provisional application

60/124,042, filed on 3/11/99; (122) PCT patent application serial no. PCT/US2004/06246, attorney docket no. 25791.238.02, filed on 2/26/2004; (123) PCT patent application serial number PCT/US2004/08170, attorney docket number 25791.40.02, filed on 3/15/04; (124) PCT patent application serial number PCT/US2004/08171, attorney docket number 25791.236.02, filed on 3/15/04; (125) PCT patent application serial number PCT/US2004/08073, attorney docket number 25791.262.02, filed on 3/18/04; (126) PCT patent application serial number PCT/US2004/07711, attorney docket number 25791.253.02, filed on 3/11/2004; (127) PCT patent application serial number PCT/US2004/029025, attorney docket number 25791.260.02, filed on 3/26/2004; (128) PCT patent application serial number PCT/US2004/010317, attorney docket number 25791.270.02, filed on 4/2/2004; (129) PCT patent application serial number PCT/US2004/010712, attorney docket number 25791.272.02, filed on 4/6/2004; (130) PCT patent application serial number PCT/US2004/010762, attorney docket number 25791.273.02, filed on 4/6/2004; (131) PCT patent application serial number PCT/US2004/011973, attorney docket number 25791.277.02, filed on 4/15/2004; (132) U.S. provisional patent application serial number 60/495056, attorney docket number 25791.301, filed on 8/14/2003; (133) U.S. provisional patent application serial number 60/600679, attorney docket number 25791.194, filed on 8/11/2004; (134) PCT patent application serial number PCT/US2005/027318, attorney docket number 25791.329.02, filed on 7/29/2005; (135) PCT patent application serial number PCT/US2005/028936, attorney docket number 25791.338.02, filed on 8/12/2005; (136) PCT patent application serial number PCT/US2005/028669, attorney docket number 25791.194.02, filed on 8/11/2005; (137) PCT patent application serial number PCT/US2005/028453, attorney docket number 25791.371, filed on 8/11/2005; (138) PCT patent application serial number PCT/US2005/028641, attorney docket number 25791.372, filed on 8/11/2005; (139) PCT patent application serial number PCT/US2005/028819, attorney docket number 25791.373, filed on 8/11/2005; (140) PCT patent application serial number PCT/US2005/028446, attorney docket number 25791.374, filed on 8/11/2005; (141) PCT patent application serial number PCT/US2005/028642, attorney docket number 25791.375, filed on 8/11/2005; (142) PCT patent application serial number PCT/US2005/028451, attorney docket number 25791.376, filed on 8/11/2005, and (143) PCT patent application serial number PCT/US2005/028473, attorney docket number 25791.377, filed on 8/11/2005, (144) U.S. utility patent application serial number 10/546082, attorney docket number 25791.378, filed on 8/16/2005, (145) U.S. utility patent application serial number 10/546076, attorney docket number 25791.379, filed on 8/16/2005, (146) U.S. utility patent application serial number 10/545936, attorney docket number 25791.380, filed on 8/16/2005, (147) U.S. utility patent application serial number

10/546079, attorney docket number 25791.381, filed on 8/16/2005 (148) U.S. utility patent application serial number 10/545941, attorney docket number 25791.382, filed on 8/16/2005, (149) U.S. utility patent application serial number 546078, attorney docket number 25791.383, filed on 8/16/2005, filed on 8/11/2005., (150) U.S. utility patent application serial number 10/545941, attorney docket number 25791.185.05, filed on 8/16/2005, (151) U.S. utility patent application serial number 11/249967, attorney docket number 25791.384, filed on 10/13/2005, (152) U.S. provisional patent application serial number 60/734302, attorney docket number 25791.24, filed on 11/7/2005, (153) U.S. provisional patent application serial number 60/725181, attorney docket number 25791.184, filed on 10/11/2005, (154) PCT patent application serial number PCT/US2005/023391, attorney docket number 25791.299.02 filed 6/29/2005 which claims priority from U.S. provisional patent application serial number 60/585370, attorney docket number 25791.299, filed on 7/2/2004, (155) U.S. provisional patent application serial number 60/721579, attorney docket number 25791.327, filed on 9/28/2005, (156) U.S. provisional patent application serial number 60/717391, attorney docket number 25791.214, filed on 9/15/2005, (157) U.S. provisional patent application serial number 60/702935, attorney docket number 25791.133, filed on 7/27/2005, (158) U.S. provisional patent application serial number 60/663913, attorney docket number 25791.32, filed on 3/21/2005, (159) U.S. provisional patent application serial number 60/652564, attorney docket number 25791.348, filed on 2/14/2005, (160) U.S. provisional patent application serial number 60/645840, attorney docket number 25791.324, filed on 1/21/2005, (161) PCT patent application serial number PCT/US2005/_____, attorney docket number 25791.326.02, filed on 11/29/2005 which claims priority from U.S. provisional patent application serial number 60/631703, attorney docket number 25791.326, filed on 11/30/2004, and (162) U.S. provisional patent application serial number _____, attorney docket number 25791.339, filed on 12/22/2005, the disclosures of which are incorporated herein by reference.

[000322] Referring now to Figs. 13a and 13b, a tubular sealing member 1600 is illustrated. Sealing member 1600 includes a front end 1602a, a rear end 1602b positioned opposite the front end 1602a, and defines a passageway 1602c along its length having a passageway diameter D_p . An outer surface 1604 of sealing member 1600 increases from substantially the passageway diameter D_p adjacent the front end 1602a to a sealing diameter D_s at a seal contact 1606. A beveled surface 1608 is positioned between the seal contact 1606 and the rear end 1602b of sealing member 1600. An annular coupling member 1610 extends from the sealing member 1600 and into the passageway 1602c. In an exemplary embodiment, sealing member 1600 includes a compressible sealing material operable to compress under pressure and provide a seal between itself and the body which is compressing it. In an

exemplary embodiment, the sealing member 1600 may include an HNBR compound, an elastomer compound, a teflon compound, a TFE compound, or a variety of equivalent compounds known in the art.

[000323] Referring now to Fig. 14, a tubular member 1700 is illustrated. Tubular member 1700 includes an inner wall 1702a, defines a passageway 1702b along its length, and has an initial inner tube diameter D_i . In an exemplary embodiment, the tubular member 1700 may be, for example, a well bore casing, a structural support, and/or a pipeline. In an exemplary embodiment, the tubular member 1700 may be a conventional tubular member known in the art, and/or a tubular member described in This application is related to the following co-pending applications.

[000324] Referring now to Fig. 15, an expansion apparatus 1800, which may be the apparatus 200, 700, and/or 900 for forming a wellbore casing described above with reference to Figs. 2, 3, 3a, 4, 7, 9, is illustrated. Expansion apparatus 1800 is assembled by coupling the sealing member 1600 to the expansion device 1500 by positioning coupling member 1610 on sealing member 1600 in coupling channel 1508 on expansion device 1500. In an exemplary embodiment, the sealing member 1600 may be coupled to the expansion device 1500 in an alternative manner such as, for example, bonding the sealing member 1600 including the coupling member 1610 to the expansion device 1500 including the coupling channel 1508, removing the coupling member 1610 from the sealing member 1600 and the coupling channel 1508 from the expansion device 1500 and bonding the sealing member 1600 to a flat surface on the expansion device 1500, and/or a variety of other equivalent methods known in the art.

[000325] With the sealing member 1600 coupled to the expansion device 1500, front end 1602a of sealing member 1600 is positioned adjacent expansion surface 1506a. Passageway diameter D_P is substantially equal to or slightly smaller than base diameter D_B such that sealing member 1600 is securely coupled to the expansion device 1600. Sealing member 1600 extends out past the first end 1502a of expansion device 1500 and is positioned adjacent sealing volume 1510 such that a portion of sealing volume 1510 and the passageway 1602c occupy the same space and are positioned adjacent an end of fluid passageway 1512. The sealing diameter D_S at seal contact 1606 is greater than the expansion diameter D_E and is positioned out past the first end 1502a of expansion device 1500.

[000326] Referring now to Figs. 14 and 16a, in operation, a method 1900 for expanding a tubular member such as, for example, the tubular member 1700 is illustrated. The method 1900 begins at step 1902 where the tubular member 1700 is provided. The tubular member 1700 may be provided positioned in a well bore 1902a.

[000327] Referring now to Figs. 15, 16a and 16b, the method 1900 proceeds to step 1904 where the expansion apparatus 1800 is positioned in the tubular member 1700. Expansion device 1500 and sealing member 1600 are positioned in passageway 1702b in tubular member 1700 in an orientation A_1 . Expansion diameter D_E of expansion member 1504 on expansion device 1500 is greater than the initial inner tube diameter D_I of tubular member 1700, resulting in an expansion of the inner diameter of the tubular member 1700 from initial inner tube diameter D_I to substantially the expansion diameter D_E .

[000328] The method 1900 proceeds to step 1906 where the expansion apparatus 1800 is sealed with the tubular member 1700. Upon positioning the expansion apparatus 1800 in the tubular member 1700, seal contact 1606 engages inner wall 1702a of tubular member 1700. In response to engagement between seal contact 1606 and inner wall 1702a, a portion of sealing member 1600 including rear end 1602b deflects around the first end 1502a of base member 1502 on expansion device 1500, resulting in the sealing volume 1510 containing a portion of the sealing member 1600. This results in a portion of the outer surface 1604, the seal contact 1606, and a portion of the beveled surface 1608 planarizing against the inner wall 1702a of the tubular member 1700 and forming a cup seal which seals the expansion apparatus 1800 with the tubular member 1700. In an exemplary embodiment, the planarization of the sealing member 1600 results in a larger seal surface between the sealing member 1600 and the tubular member 1700 than would exist without the cup seal, which allows the seal to withstand a higher pressure than conventional seals.

[000329] The method 1900 proceeds to step 1908 where the tubular member 1700 is expanded. A drill string 1908a is sealingly coupled to the second end 1502b such that it is positioned co-axially with fluid passageway 1512. With the expansion apparatus 1800 sealed with the tubular member 1700 by the sealing member 1600, a pressurized fluid may be supplied through the drill string 1908a and fluid passageway 1512 such that it accumulates adjacent the first end 1502a of the expansion device 1500 on expansion apparatus 1800. In response to the pressurized fluid being supplied, a pressure drop will occur across the expansion apparatus 1800 due to the seal between the expansion apparatus 1800 and the tubular member 1700 that will result in the expansion apparatus 1800 moving in a direction A_2 through the tubular member 1700. Moving expansion apparatus 1800 through the tubular member 1700 in direction A_2 expands the inner diameter of the tubular member 1700 through contact with the expansion surface 1506b from the initial inner tube diameter D_I to substantially the expansion diameter D_E and places the tubular member 1700 in abutment with the well bore 1902a.

[000330] Referring now to Figs. 17a and 17b, an alternative embodiment of a method 2000 for expanding a tubular member such as, for example, the tubular member 1700 illustrated in

Fig. 3, is substantially identical in operation to the method 1900 described above with reference to Figs. 12a, 12b, 13a, 13b, 14, 15, 16a, and 16b with the provision of modified steps 2002, 2004, and 2006 replacing steps 1904, 1906, and 1908, respectively.

[000331] At step 2002, the expansion apparatus 1800 is positioned in the tubular member 1700. Expansion device 1500 and sealing member 1600 are positioned in passageway 1702b in tubular member 1700 in an orientation B_1 , which is opposite the orientation A_1 described above with reference to Fig. 16b. Expansion diameter D_E of expansion member 1504 on expansion device 1500 is greater than the initial inner tube diameter D_I of tubular member 1700, resulting in an expansion of the inner diameter of the tubular member 1700 from initial inner tube diameter D_I to substantially the expansion diameter D_E .

[000332] At step 2004, the expansion apparatus 1800 is sealed with the tubular member 1700. Upon positioning the expansion apparatus 1800 in the tubular member 1700, seal contact 1606 engages with inner wall 1702a of tubular member 1700. In response to engagement between seal contact 1606 and inner wall 1702a, a portion of sealing member 1600 including rear end 1602b deflects around the first end 1502a of base member 1502 on expansion device 1500, resulting in the sealing volume 1510 containing a portion of the sealing member 1600. This results in a portion of the outer surface 1604, the seal contact 1606, and a portion of the beveled surface 1608 planarizing against the inner wall 1702a of the tubular member 1700 and forming a cup seal which seals the expansion apparatus 1800 with the tubular member 1700. In an exemplary embodiment, the planarization of the sealing member 1600 results in a larger seal surface between the sealing member 1600 and the tubular member 1700 than would exist without the cup seal, which allows the seal to withstand a higher pressure than conventional seals.

[000333] At step 2006, the tubular member 1700 is expanded. A drill string 2006a is sealingly coupled to the first end 1502a such that it is positioned co-axially with fluid passageway 1512 and in passageway 1602c on sealing member 1600. With the expansion apparatus 1800 sealed with the tubular member 1700 by the sealing member 1600, a pressurized fluid may be supplied through the drill string 2006a and fluid passageway 1512 such that it accumulates adjacent the second end 1502b of the expansion device 1500 on expansion apparatus 1800. In response to the pressurized fluid being supplied, a pressure drop will occur across the expansion apparatus 1800 due to the seal between the expansion apparatus 1800 and the tubular member 1700 that will result in the expansion apparatus 1800 moving in a direction B_2 through the tubular member 1700. Moving expansion apparatus 1800 through the tubular member 1700 in direction B_2 expands the inner diameter of the tubular member 1700 through contact with the expansion surface 1506a from the initial inner tube diameter D_I to substantially the expansion diameter D_E and places the

tubular member 1700 in abutment with the well bore 1902a. Thus, using methods 1900 and 2000, an expansion apparatus 1800 is provided which may be used to expand a tubular member 1700 by moving the expansion apparatus 1800 through the tubular member 1700 in a plurality of directions.

[000334] Referring now to Figs. 18a and 18b, an alternative embodiment of an expansion apparatus 2100, which may be the apparatus 200, 700, and/or 900 for forming a wellbore casing described above with reference to Figs. 2, 3, 3a, 4, 7, 9, is substantially identical in design and operation to the expansion apparatus 1800 described above with reference to Figs. 12a, 12b, 13a, 13b, 14, 15, 16a, 16b, 17a, and 17b, with the provision of a modified second end 2102 of base member 1502. A coupling channel 2104 is defined by the base member 1502 and positioned between expansion surface 1506b and the second end 2102. A sealing volume 2106 is defined by an outer circumferential edge of the base member 1502 and the second end 2102 of the base member 1502 and is positioned adjacent the second end 2102 of the base member 1502.

[000335] Referring now to Fig. 19, the expansion apparatus 2100 is assembled by coupling a plurality of the sealing members 1600 to opposite ends of the expansion device 1500 by positioning coupling member 1610 on a first sealing member 1600 in coupling channel 1508 on expansion device 1500, and positioning coupling member 1610 on a second sealing member 1600 in coupling channel 2104 on expansion device 1500. In an exemplary embodiment, the plurality of sealing member 1600 may be coupled to the expansion device 1500 in an alternative manner such as, for example, bonding the sealing member 1600 including the coupling members 1610 to the expansion device 1500 including the coupling channels 1508 and 2104, removing the coupling members 1610 from the sealing members 1600 and the coupling channels 1508 and 2104 from the expansion device 1500 and bonding the sealing members 1600 to a flat surface on the expansion device 1500, and/or a variety of other equivalent methods known in the art.

[000336] Referring now to Figs. 20a and 20b, an alternative embodiment of a method 2200 for expanding a tubular member such as, for example, the tubular member 1700 illustrated in Fig. 14, is substantially identical in operation to the method 1900 described above with reference to Figs. 12a, 12b, 13a, 13b, 14, 15, 16a, and 16b with the provision of modified steps 2202, 2204, and 2206 replacing steps 1904, 1906, and 1908, respectively.

[000337] At step 2202, the expansion apparatus 1800 is positioned in the tubular member 1700. Expansion device 1500 and the plurality of sealing members 1600 are positioned in passageway 1702b in tubular member 1700. Expansion diameter D_E of expansion member 1504 on expansion device 1500 is greater than the initial inner tube diameter D_I of tubular

member 1700, resulting in an expansion of the inner diameter of the tubular member 1700 from initial inner tube diameter D_i to substantially the expansion diameter D_E .

[000338] At step 2204, the expansion apparatus 1800 is sealed with the tubular member 1700. Upon positioning the expansion apparatus 1800 in the tubular member 1700, seal contacts 1606 on the plurality of sealing members 1600 engage the inner wall 1702a of tubular member 1700. In response to engagement between seal contacts 1606 and inner wall 1702a, a portion of the plurality of sealing members 1600 including rear ends 1602b deflect around the first end 1502a and the second end 2102 of base member 1502 on expansion device 1500, resulting in the sealing volumes 1510 and 2106 containing a portion of each of the plurality of sealing members 1600. This results in a portion of the outer surface 1604, the seal contact 1606, and a portion of the beveled surface 1608 planarizing against the inner wall 1702a of the tubular member 1700 and forming a cup seal which seals the expansion apparatus 1800 with the tubular member 1700. In an exemplary embodiment, the planarization of the sealing member 1600 results in a larger seal surface between the sealing member 1600 and the tubular member 1700 than would exist without the cup seal, which allows the seal to withstand a higher pressure than conventional seals. In an exemplary embodiment, the plurality of sealing members 1600 provide a redundant seal for sealing the expansion apparatus 1800 with the tubular member 1700 in the event the other sealing member 1600 fails.

[000339] At step 2206, the tubular member 1700 is expanded. A drill string 2206a is sealingly coupled to the first end 1502a such that it is positioned co-axially with fluid passageway 1512. With the expansion apparatus 1800 sealed with the tubular member 1700 the plurality of sealing members 1600, a pressurized fluid may be supplied through the drill string 2206a and fluid passageway 1512 such that it accumulates adjacent the second end 1502b of the expansion device 1500 on expansion apparatus 1800. In response to the pressurized fluid being supplied, a pressure drop will occur across the expansion apparatus 1800 due to the seal between the expansion apparatus 1800 and the tubular member 1700 that will result in the expansion apparatus 1800 moving in a direction C through the tubular member 1700. Moving expansion apparatus 1800 through the tubular member 1700 in direction C expands the inner diameter of the tubular member 1700 through contact with the expansion surface 1506a from the initial inner tube diameter D_i to substantially the expansion diameter D_E and places the tubular member 1700 in abutment with the well bore 1902a. In an exemplary embodiment, the expansion apparatus 2100 may be moved through the tubular member 1700 in a direction opposite the direction C using the method 2200. Thus, using methods 2200, an expansion apparatus 2100 is provided which may be used to

expand a tubular member 1700 by moving the expansion apparatus 2100 through the tubular member 1700 in a plurality of directions.

[000340] A method of creating a casing in a borehole located in a subterranean formation has been described that includes installing a tubular liner and a mandrel in the borehole. A body of fluidic material is then injected into the borehole. The tubular liner is then radially expanded by extruding the liner off of the mandrel. The injecting preferably includes injecting a hardenable fluidic sealing material into an annular region located between the borehole and the exterior of the tubular liner; and a non hardenable fluidic material into an interior region of the tubular liner below the mandrel. The method preferably includes fluidically isolating the annular region from the interior region before injecting the second quantity of the non hardenable sealing material into the interior region. The injecting the hardenable fluidic sealing material is preferably provided at operating pressures and flow rates ranging from about 0 to 5000 psi and 0 to 1,500 gallons/min. The injecting of the non hardenable fluidic material is preferably provided at operating pressures and flow rates ranging from about 500 to 9000 psi and 40 to 3,000 gallons/min. The injecting of the non hardenable fluidic material is preferably provided at reduced operating pressures and flow rates during an end portion of the extruding. The non hardenable fluidic material is preferably injected below the mandrel. The method preferably includes pressurizing a region of the tubular liner below the mandrel. The region of the tubular liner below the mandrel is preferably pressurized to pressures ranging from about 500 to 9,000 psi. The method preferably includes fluidically isolating an interior region of the tubular liner from an exterior region of the tubular liner. The method further preferably includes curing the hardenable sealing material, and removing at least a portion of the cured sealing material located within the tubular liner. The method further preferably includes overlapping the tubular liner with an existing wellbore casing. The method further preferably includes sealing the overlap between the tubular liner and the existing wellbore casing. The method further preferably includes supporting the extruded tubular liner using the overlap with the existing wellbore casing. The method further preferably includes testing the integrity of the seal in the overlap between the tubular liner and the existing wellbore casing. The method further preferably includes removing at least a portion of the hardenable fluidic sealing material within the tubular liner before curing. The method further preferably includes lubricating the surface of the mandrel. The method further preferably includes absorbing shock. The method further preferably includes catching the mandrel upon the completion of the extruding.

[000341] An apparatus for creating a casing in a borehole located in a subterranean formation has been described that includes a support member, a mandrel, a tubular member, and a shoe. The support member includes a first fluid passage. The mandrel is

coupled to the support member and includes a second fluid passage. The tubular member is coupled to the mandrel. The shoe is coupled to the tubular liner and includes a third fluid passage. The first, second and third fluid passages are operably coupled. The support member preferably further includes a pressure relief passage, and a flow control valve coupled to the first fluid passage and the pressure relief passage. The support member further preferably includes a shock absorber. The support member preferably includes one or more sealing members adapted to prevent foreign material from entering an interior region of the tubular member. The mandrel is preferably expandable. The tubular member is preferably fabricated from materials selected from the group consisting of Oilfield Country Tubular Goods, 13 chromium steel tubing/casing, and plastic casing. The tubular member preferably has inner and outer diameters ranging from about 3 to 15.5 inches and 3.5 to 16 inches, respectively. The tubular member preferably has a plastic yield point ranging from about 40,000 to 135,000 psi. The tubular member preferably includes one or more sealing members at an end portion. The tubular member preferably includes one or more pressure relief holes at an end portion. The tubular member preferably includes a catching member at an end portion for slowing down the mandrel. The shoe preferably includes an inlet port coupled to the third fluid passage, the inlet port adapted to receive a plug for blocking the inlet port. The shoe preferably is drillable.

[000342] A method of joining a second tubular member to a first tubular member, the first tubular member having an inner diameter greater than an outer diameter of the second tubular member, has been described that includes positioning a mandrel within an interior region of the second tubular member, positioning the first and second tubular members in an overlapping relationship, pressurizing a portion of the interior region of the second tubular member; and extruding the second tubular member off of the mandrel into engagement with the first tubular member. The pressurizing of the portion of the interior region of the second tubular member is preferably provided at operating pressures ranging from about 500 to 9,000 psi. The pressurizing of the portion of the interior region of the second tubular member is preferably provided at reduced operating pressures during a latter portion of the extruding. The method further preferably includes sealing the overlap between the first and second tubular members. The method further preferably includes supporting the extruded first tubular member using the overlap with the second tubular member. The method further preferably includes lubricating the surface of the mandrel. The method further preferably includes absorbing shock.

[000343] A liner for use in creating a new section of wellbore casing in a subterranean formation adjacent to an already existing section of wellbore casing has been described that includes an annular member. The annular member includes one or more sealing members

at an end portion of the annular member, and one or more pressure relief passages at an end portion of the annular member.

[000344] A wellbore casing has been described that includes a tubular liner and an annular body of a cured fluidic sealing material. The tubular liner is formed by the process of extruding the tubular liner off of a mandrel. The tubular liner is preferably formed by the process of placing the tubular liner and mandrel within the wellbore, and pressurizing an interior portion of the tubular liner. The annular body of the cured fluidic sealing material is preferably formed by the process of injecting a body of hardenable fluidic sealing material into an annular region external of the tubular liner. During the pressurizing, the interior portion of the tubular liner is preferably fluidically isolated from an exterior portion of the tubular liner. The interior portion of the tubular liner is preferably pressurized to pressures ranging from about 500 to 9,000 psi. The tubular liner preferably overlaps with an existing wellbore casing. The wellbore casing preferably further includes a seal positioned in the overlap between the tubular liner and the existing wellbore casing. Tubular liner is preferably supported the overlap with the existing wellbore casing.

[000345] A method of repairing an existing section of a wellbore casing within a borehole has been described that includes installing a tubular liner and a mandrel within the wellbore casing, injecting a body of a fluidic material into the borehole, pressurizing a portion of an interior region of the tubular liner, and radially expanding the liner in the borehole by extruding the liner off of the mandrel. In a preferred embodiment, the fluidic material is selected from the group consisting of slag mix, cement, drilling mud, and epoxy. In a preferred embodiment, the method further includes fluidically isolating an interior region of the tubular liner from an exterior region of the tubular liner. In a preferred embodiment, the injecting of the body of fluidic material is provided at operating pressures and flow rates ranging from about 500 to 9,000 psi and 40 to 3,000 gallons/min. In a preferred embodiment, the injecting of the body of fluidic material is provided at reduced operating pressures and flow rates during an end portion of the extruding. In a preferred embodiment, the fluidic material is injected below the mandrel. In a preferred embodiment, a region of the tubular liner below the mandrel is pressurized. In a preferred embodiment, the region of the tubular liner below the mandrel is pressurized to pressures ranging from about 500 to 9,000 psi. In a preferred embodiment, the method further includes overlapping the tubular liner with the existing wellbore casing. In a preferred embodiment, the method further includes sealing the interface between the tubular liner and the existing wellbore casing. In a preferred embodiment, the method further includes supporting the extruded tubular liner using the existing wellbore casing. In a preferred embodiment, the method further includes testing the integrity of the seal in the interface between the tubular liner and the existing

wellbore casing. In a preferred embodiment, method further includes lubricating the surface of the mandrel. In a preferred embodiment, the method further includes absorbing shock. In a preferred embodiment, the method further includes catching the mandrel upon the completion of the extruding. In a preferred embodiment, the method further includes expanding the mandrel in a radial direction.

[000346] A tie-back liner for lining an existing wellbore casing has been described that includes a tubular liner and an annular body of a cured fluidic sealing material. The tubular liner is formed by the process of extruding the tubular liner off of a mandrel. The annular body of a cured fluidic sealing material is coupled to the tubular liner. In a preferred embodiment, the tubular liner is formed by the process of placing the tubular liner and mandrel within the wellbore, and pressurizing an interior portion of the tubular liner. In a preferred embodiment, during the pressurizing, the interior portion of the tubular liner is fluidly isolated from an exterior portion of the tubular liner. In a preferred embodiment, the interior portion of the tubular liner is pressurized at pressures ranging from about 500 to 9,000 psi. In a preferred embodiment, the annular body of a cured fluidic sealing material is formed by the process of injecting a body of hardenable fluidic sealing material into an annular region between the existing wellbore casing and the tubular liner. In a preferred embodiment, the tubular liner overlaps with another existing wellbore casing. In a preferred embodiment, the tie-back liner further includes a seal positioned in the overlap between the tubular liner and the other existing wellbore casing. In a preferred embodiment, tubular liner is supported by the overlap with the other existing wellbore casing.

[000347] An apparatus for expanding a tubular member has been described that includes a support member, a mandrel, a tubular member, and a shoe. The support member includes a first fluid passage. The mandrel is coupled to the support member. The mandrel includes a second fluid passage operably coupled to the first fluid passage, an interior portion, and an exterior portion. The interior portion of the mandrel is drillable. The tubular member is coupled to the mandrel. The shoe is coupled to the tubular member. The shoe includes a third fluid passage operably coupled to the second fluid passage, an interior portion, and an exterior portion. The interior portion of the shoe is drillable. Preferably, the interior portion of the mandrel includes a tubular member and a load bearing member. Preferably, the load bearing member comprises a drillable body. Preferably, the interior portion of the shoe includes a tubular member, and a load bearing member. Preferably, the load bearing member comprises a drillable body. Preferably, the exterior portion of the mandrel comprises an expansion cone. Preferably, the expansion cone is fabricated from materials selected from the group consisting of tool steel, titanium, and ceramic. Preferably,

the expansion cone has a surface hardness ranging from about 58 to 62 Rockwell C. Preferably at least a portion of the apparatus is drillable.

[000348] An expansion apparatus has been described that includes an elongated base member comprising a first end, a second end opposite the first end, and an expansion member comprising an expansion diameter and extending from the base member between the first and second end, and a first sealing member coupled to the base member and extending out past the first end of the base member, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter. In an exemplary embodiment, the base member comprises a first channel operable to couple the first sealing member to the base member. In an exemplary embodiment, the base member is substantially cylindrical. In an exemplary embodiment, a plurality of expansion surfaces are positioned on opposite sides of the expansion member. In an exemplary embodiment, the plurality of expansion surfaces increase in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter. In an exemplary embodiment, the first sealing member is substantially tubular. In an exemplary embodiment, the first sealing member comprises a first coupling member operable to couple the first sealing member to the base member. In an exemplary embodiment, the first sealing member is bonded to the base member. In an exemplary embodiment, the first sealing member is operable to deflect around the first end of the base member. In an exemplary embodiment, a first sealing volume is defined by the base member and is adjacent the first end of the base member, whereby the first sealing volume is operable to contain a portion of the first sealing member when the first sealing member deflects around the first end of the base member. In an exemplary embodiment, a second sealing member is coupled to the base member and extends out past the second end of the base member, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter. In an exemplary embodiment, the base member comprises a second channel operable to couple the second sealing member to the base member. In an exemplary embodiment, the second sealing member is substantially tubular. In an exemplary embodiment, the second sealing member comprises a second coupling member operable to couple the second sealing member to the base member. In an exemplary embodiment, the second sealing member is bonded to the base member. In an exemplary embodiment, the second sealing member is operable to deflect around the second end of the base member. In an exemplary embodiment, a second sealing volume is defined by the base member and is adjacent the second end of the base member, whereby the second sealing volume is operable to contain a portion of the second sealing member when the second sealing member deflects around the second end of the base member. In an exemplary embodiment, the first sealing member

is operable to seal the apparatus with a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions. In an exemplary embodiment, the second sealing member is operable to seal the apparatus with a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions. In an exemplary embodiment, the first sealing member defines a cylindrical volume extending out past the first end of the base member. In an exemplary embodiment, the second sealing member defines a cylindrical volume extending out past the second end of the base member.

[000349] An expandable tubular member has been described that includes a tubular member comprising an initial diameter, and an expansion apparatus positioned in the tubular member, the expansion apparatus including an elongated base member comprising a first end, a second end opposite the first end, and an expansion member comprising an expansion diameter and extending from the base member between the first and second end, and a first sealing member coupled to the base member and extending out past the first end of the base member, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter. In an exemplary embodiment, the base member comprises a first channel operable to couple the first sealing member to the base member. In an exemplary embodiment, the base member is substantially cylindrical. In an exemplary embodiment, a plurality of expansion surfaces are positioned on opposite sides of the expansion member, the plurality of expansion surfaces operable to expand the tubular member from the initial diameter to substantially the expansion diameter. In an exemplary embodiment, the plurality of expansion surfaces increase in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter. In an exemplary embodiment, the first sealing member is substantially tubular. In an exemplary embodiment, the first sealing member comprises a first coupling member operable to couple the first sealing member to the base member. In an exemplary embodiment, the first sealing member is bonded to the base member. In an exemplary embodiment, the first sealing member is deflected around the first end of the base member by the tubular member. In an exemplary embodiment, a first sealing volume is defined by the base member and the tubular member and is positioned adjacent the first end of the base member, whereby the first sealing volume contains a portion of the first sealing member which is deflected around the first end of the base member by the tubular member. In an exemplary embodiment, a second sealing member is coupled to the base member and extends out past the second end of the base member, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter. In an exemplary embodiment, the base member comprises a second channel operable to couple the second sealing member to the

base member. In an exemplary embodiment, the second sealing member is substantially tubular. In an exemplary embodiment, the second sealing member comprises a second coupling member operable to couple the second sealing member to the base member. In an exemplary embodiment, the second sealing member is bonded to the base member. In an exemplary embodiment, the second sealing member is deflected around the second end of the base member by the tubular member. In an exemplary embodiment, a second sealing volume is defined by the base member and the tubular member and is positioned adjacent the second end of the base member, whereby the second sealing volume contains a portion of the second sealing member which is deflected around the second end of the base member by the tubular member. In an exemplary embodiment, the first sealing member is operable to seal the expansion apparatus with the tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions. In an exemplary embodiment, the second sealing member is operable to seal the expansion apparatus with the tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions. In an exemplary embodiment, the first sealing member defines a cylindrical volume extending out past the first end of the base member. In an exemplary embodiment, the second sealing member defines a cylindrical volume extending out past the second end of the base member. In an exemplary embodiment, the first sealing member forms a cup seal with the tubular member. In an exemplary embodiment, the second sealing member forms a cup seal with the tubular member. In an exemplary embodiment, the tubular member is positioned in a well bore. In an exemplary embodiment, the tubular member is a wellbore casing. In an exemplary embodiment, the tubular member is a structural support. In an exemplary embodiment, the tubular member is a pipeline.

[000350] An expansion apparatus has been described that includes an elongated base member comprising a first end and a second end opposite the first end, means for expanding a tubular member extending from the base member between the first and second end, and first means for providing a seal, the first means for providing a seal extending out past the first end of the base member. In an exemplary embodiment, the base member comprises a means for coupling the first means for providing a seal to the base member. In an exemplary embodiment, the first means for providing a seal comprises a means for coupling the first means for providing a seal to the base member. In an exemplary embodiment, the first means for providing a seal is operable to deflect around the first end of the base member. In an exemplary embodiment, the apparatus further includes first means for containing a portion of the first means for providing a seal when the first means for providing a seal deflects around the first end of the base member. In an exemplary

embodiment, the apparatus further includes second means for providing a seal, the second means for providing a seal extending out past the second end of the base member. In an exemplary embodiment, the base member comprises a means for coupling the second means for providing a seal to the base member. In an exemplary embodiment, the second means for providing a seal comprises a means for coupling the second means for providing a seal to the base member. In an exemplary embodiment, the second means for providing a seal is operable to deflect around the second end of the base member. In an exemplary embodiment, the apparatus further includes second means for containing a portion of the second means for providing a seal when the second means for providing a seal deflects around the second end of the base member. In an exemplary embodiment, the first means for providing a seal is operable to seal the expansion apparatus with a tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions. In an exemplary embodiment, the second means for providing a seal is operable to seal the expansion apparatus with the tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions.

[000351] A method for expanding a tubular member has been described that includes providing a tubular member, positioning an expansion apparatus in the tubular member, the expansion apparatus comprising a first end, a second end opposite the first end, and a first sealing member extending out past the first end of the expansion apparatus, sealing the expansion apparatus with the tubular member, whereby the sealing comprises deflecting a portion of the first sealing member around the first end of the expansion apparatus by the tubular member, and expanding the tubular member by moving the expansion apparatus axially through the tubular member. In an exemplary embodiment, the expanding comprises moving the expansion apparatus axially through the tubular member in a plurality of directions, whereby the first sealing member provides a seal between the expansion apparatus and the tubular member in each of the plurality of directions. In an exemplary embodiment, the method further includes a second sealing member extending out past the second end of the expansion apparatus. In an exemplary embodiment, the sealing comprises deflecting a portion of the second sealing member around the second end of the expansion apparatus by the tubular member. In an exemplary embodiment, the expanding comprises moving the expansion apparatus axially through the tubular member in a plurality of directions, whereby the first sealing member and the second sealing member provide a seal between the expansion apparatus and the tubular member in each of the plurality of directions. In an exemplary embodiment, the sealing comprises forming a cup seal between the tubular member and the expansion apparatus.

[000352] An expansion apparatus has been described that includes a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing volume defined by the base member and adjacent the first end of the base member, an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter, and a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

[000353] An expansion apparatus has been described that includes a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing volume defined by the base member and adjacent the first end of the base member, a second sealing volume defined by the base member and adjacent the second end of the base member, an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter, a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions, and a substantially tubular second sealing member coupled to the base member and extending out past the second end, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter and operable to deflect around the second end of the base member and partially into the second sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

[000354] An expandable tubular member has been described that includes a tubular member comprising an initial diameter, and an expansion apparatus positioned in the tubular member, the expansion apparatus including a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing

volume defined by the base member and tubular member and adjacent the first end of the base member, an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter and operable to expand the tubular member from the initial diameter to a diameter which is substantially equal to the expansion diameter, and a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

[000355] An expandable tubular member has been described that includes a tubular member comprising an initial diameter, and an expansion apparatus positioned in the tubular member, the expansion apparatus including a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end, a first sealing volume defined by the base member and tubular member and adjacent the first end of the base member, a second sealing volume defined by the base member and tubular member and adjacent the second end of the base member, an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter and operable to expand the tubular member from the initial diameter to a diameter which is substantially equal to the expansion diameter, a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions, and a substantially tubular second sealing member coupled to the base member and extending out past the second end, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter and operable to deflect around the second end of the base member and partially into the second sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

[000356] It is understood that variations may be made in the foregoing without departing from the scope of the disclosed embodiments. Furthermore, the elements and teachings of the various illustrative embodiments may be combined in whole or in part some or all of the illustrated embodiments.

[000357] Although illustrative embodiments have been shown and described, a wide range of modification, change and substitution is contemplated in the foregoing disclosure and in some instances, some features of the embodiments may be employed without a corresponding use of other features. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the embodiments disclosed herein.

CLAIMS

What is claimed is:

1. A method for expanding tubulars, comprising:
providing an expandable tubing and a larger diameter tubing, wherein the larger diameter tubing has an expandable, tapering end portion;
coupling an end portion of the expandable tubing to the expandable tapering end portion of the larger diameter tubing;
running the connected tubing into a bore; and
expanding the expandable tubing;
wherein, prior to the expanding of the expandable tubing, a wall thickness of the end portion of the expandable tubing coupled to the expandable tapering end portion of the larger diameter tubing is less than a wall thickness of another end portion of the expandable tubing.
2. The method of claim 1, wherein the expandable tubing is expanded to provide a borehole liner or support.
3. The method of claim 1, wherein the expandable tubing is expanded to provide at least part of an expandable well screen or sand screen.
4. The method of claim 1, wherein the other end portion of the expandable tubing includes one or more radial pressure relief passages.
5. The method of claim 1, wherein the other end portion of the expandable tubing includes one or more sealing members for sealingly engaging the bore.
6. The method of claim 1, wherein, prior to the expanding of the expandable tubing, a wall thickness of the larger diameter tubing is less than the wall thickness of the other end portion of the expandable tubing.
7. A method of providing a downhole seal in a drilled bore between inner tubing and outer tubing, the method comprising:
providing an intermediate tubing section coupled to the inner tubing; and
plastically deforming the intermediate tubing section downhole to form an annular extension, the extension creating a sealing contact with the outer tubing.

8. The method of claim 7, wherein the inner tubing comprises a tie back liner; and wherein the outer tubing comprises a wellbore casing.
9. The method of claim 7, wherein the deformation of the intermediate tubing section is at least partially as a result of compressive yield.
10. The method of claim 9, wherein the deformation of the intermediate tubing section is by radial expansion to cause compressive plastic deformation of the tubing section and a localized reduction in wall thickness resulting in a subsequent increase in diameter.
11. The method of claim 7, wherein the intermediate tubing section comprises a metal and deforming the tubing section creates a metal-to-metal seal between the intermediate tubing section and the outer tubing.
12. The method of claim 7, wherein the outer tubing is elastically deformed to grip the extension.
13. The method of claim 12, wherein the outer tubing is deformed from contact with the extension as the extension is formed.
14. The method of claim 12, wherein the outer tubing is plastically deformed.
15. The method of claim 7, wherein the inner tubing comprises production tubing.
16. The method of claim 7, wherein the outer tubing comprises a bore-lining casing.
17. The method of claim 7, wherein ductile material is provided between the intermediate tubing section and the outer tubing.
18. The method of claim 17, wherein the ductile material is provided in the form of a plurality of axially spaced bands, between areas of the intermediate tubing section which are intended to be subject to greatest deformation.
19. The method of claim 7, wherein relatively hard material is provided between the intermediate tubing section and the outer tubing, such that on deformation of the

intermediate tubing section the softer material of one or both of the intermediate tubing section and the outer tubing deforms to accommodate the harder material and thus facilitates in securing the coupling against relative axial or rotational movement.

20. The method of claim 7, further comprising the step of running an expander device into the bore within the intermediate tubing section and energizing the expander device to radially deform at least the intermediate tubing section.

21. The method of claim 20, wherein the device is run into the bore together with the intermediate tubing section.

22. The method of claim 7, wherein the intermediate tubing section is deformed such that an inner thickness of the tubing section wall is in compression, and an outer thickness of the wall is in tension.

23. The method of claim 7, wherein, prior to plastically deforming the intermediate tubing section, a wall thickness of the intermediate tubing section is greater than a wall thickness of the inner tubing.

24. A method of providing a downhole seal in a drilled bore between inner tubing and outer tubing, the method comprising: coupling an intermediate tubing section to the inner tubing; and deforming a portion of the intermediate tubing section downhole by radial expansion with a localized reduction in wall thickness resulting in a subsequent increase in the diameter of the intermediate tubing section to form an annular extension, the extension forming a sealing contact with the outer tubing.

25. A packer for providing a downhole seal in a drilled bore between inner tubing and outer tubing, the packer comprising an intermediate tubing section coupled to the inner tubing and a radially plastically deformed annular extension coupled to the intermediate tubing section comprising one or more ductile sealing elements disposed on the annular extension for sealing contact with the outer tubing.

26. A method of providing a downhole seal in a drilled bore between inner tubing and outer tubing, the method comprising: plastically deforming an intermediate portion of the inner tubing downhole to form an annular extension, the annular extension creating a sealing contact with the outer tubing.

27. The method of claim 26, wherein the deformation of the inner tubing is at least partially as a result of compressive yield.
28. The method of claim 27, wherein the deformation of the inner tubing is by radial expansion to cause compressive plastic deformation of the inner tubing and a localized reduction in wall thickness resulting in a subsequent increase in diameter.
29. The method of claim 26, wherein the outer tubing is elastically deformed to grip the extension.
30. The method of claim 29, wherein the outer tubing is deformed from contact with the extension as the extension is formed.
31. The method of claim 29, wherein the outer tubing is plastically deformed.
32. The method of claim 26, wherein the inner tubing comprises a production tubing.
33. The method of claim 26, wherein the outer tubing comprises a bore-lining casing.
34. The method of claim 26, wherein the inner tubing is plastically deformed at a plurality of axially spaced locations to form a plurality of annular extensions.
35. A packer arrangement comprising outer and inner tubing for location downhole, the inner tubing comprising a radially plastically deformed annular extension for sealing contact with the outer tubing; wherein one or more ductile elements are disposed on the outer surface of the annular extension for sealingly engaging the outer tubing.
36. An apparatus for providing a sealing connection with outer tubing in a drilled bore, the apparatus comprising a tubing section having a radially plastically deformed annular extension for sealing contact with the outer tubing and a non-deformed section; wherein one or more ductile elements are disposed on the outer surface of the annular extension.
37. A method of sealing an annular area in a wellbore comprising:
providing a tubular member; and

deforming the tubular member in a manner whereby an outer surface of the tubular member assumes a shape of a non uniform inner surface of an outer tubular therearound and forms a seal therebetween;

wherein one or more ductile elements are disposed on the outer surface of the tubular member for sealingly engaging the non uniform inner surface of the outer tubular member.

38. A method of isolating a section of downhole tubing, comprising:
running a length of expandable tubing into a tubing-lined borehole and positioning the expandable tubing across a section of tubing to be isolated, wherein the expandable tubing comprises an outer face having ductile sealing elements disposed thereon; and
deforming at least one portion of the expandable tubing to increase the diameter of the portion to sealingly engage the tubing to be isolated by displacing an expansion device therethrough in the longitudinal direction.
39. The method of claim 38, wherein the expandable tubing is deformed at least in part by compressive plastic deformation creating a localized reduction in wall thickness and an increase in diameter.
40. The method of claim 39, wherein the deformation is achieved by radial expansion.
41. The method of claim 38, wherein the deformation of the expandable tubing creates an annular extension.
42. The method of claim 41, wherein the annular extension extends over a substantial portion of the expandable tubing.
43. The method of claim 42, wherein the annular extension extends over selected portions of the expandable tubing on either side of the section of tubing to be isolated.
44. The method of claim 38, wherein the expandable tubing includes relatively ductile portions corresponding to the portions of the tubing to be expanded.
45. The method of claim 38, wherein the expandable tubing is initially cylindrical.

46. The method of claim 38, wherein seal bands are provided on an outer face of the expandable tubing and are compressed between the deformed portions of the expandable tubing and the surrounding tubing.
47. The method of claim 38, wherein grip bands comprising the ductile elements are disposed on the outer face of the expandable tubing to engage the deformed portions of the expandable tubing with the surrounding tubing.
48. A method of isolating a section of downhole tubing, comprising:
running expandable tubing into a wellbore;
positioning the expandable tubing across a section of tubing to be isolated, wherein the expandable tubing comprises an outer face having ductile elements and one or more seal bands disposed thereon; and

deforming the expandable tubing to increase a diameter thereof to sealingly engage the tubing to be isolated by displacing an expansion device therethrough in the longitudinal direction.
49. The method of claim 48, wherein one or more grip bands comprising the ductile elements are disposed on the outer face of the expandable tubing.
50. The method of claim 48, wherein the outer face comprises at least two grip bands and the one or more seal bands are disposed about the face between the grip bands.
51. The method of claim 48, wherein the one or more seal bands comprise an elastomer.
52. The method of claim 48, wherein the one or more seal bands comprise lead.
53. A method of isolating a section of downhole tubing, comprising:
running expandable tubing into a wellbore;
positioning the expandable tubing across a section of tubing to be isolated, wherein the expandable tubing comprises an outer face having ductile elements and one or more seal bands disposed thereon; and
deforming a first end of the expandable tubing to form a fluid-tight seal between the expandable tubing and the tubing to be isolated by displacing an expansion device therethrough in the longitudinal direction; and

deforming a second end of the expandable tubing to form a fluid-tight seal between the expandable tubing and the tubing to be isolated by displacing the expansion device therethrough in the longitudinal direction.

54. The method of claim 53, further comprising deforming an entire length of the expandable tubing.
55. The method of claim 53, wherein one or more grip bands comprising the ductile elements are disposed on the outer face of the expandable tubing.
56. The method of claim 53, wherein the outer face comprises at least two grip bands and the one or more seal bands are disposed about the face between the grip bands.
57. The method of claim 53, wherein the one or more seal bands comprise an elastomer.
58. The method of claim 53, wherein the one or more seal bands comprise lead.
59. An expansion apparatus comprising:
an elongated base member comprising a first end, a second end opposite the first end, and an expansion member comprising an expansion diameter and extending from the base member between the first and second end; and
a first sealing member coupled to the base member and extending out past the first end of the base member, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter.
60. The apparatus of claim 59 wherein the base member comprises a first channel operable to couple the first sealing member to the base member.
61. The apparatus of claim 59 wherein the base member is substantially cylindrical.
62. The apparatus of claim 59 further comprising:
a plurality of expansion surfaces positioned on opposite sides of the expansion member.

63. The apparatus of claim 62 wherein the plurality of expansion surfaces increase in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter.
64. The apparatus of claim 59 wherein the first sealing member is substantially tubular.
65. The apparatus of claim 59 wherein the first sealing member comprises a first coupling member operable to couple the first sealing member to the base member.
66. The apparatus of claim 59 wherein the first sealing member is bonded to the base member.
67. The apparatus of claim 59 wherein the first sealing member is operable to deflect around the first end of the base member.
68. The apparatus of claim 59 further comprising:
 - a first sealing volume defined by the base member and adjacent the first end of the base member, whereby the first sealing volume is operable to contain a portion of the first sealing member when the first sealing member deflects around the first end of the base member.
69. The apparatus of claim 59 further comprising:
 - a second sealing member coupled to the base member and extending out past the second end of the base member, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter.
70. The apparatus of claim 69 wherein the base member comprises a second channel operable to couple the second sealing member to the base member.
71. The apparatus of claim 69 wherein the second sealing member is substantially tubular.
72. The apparatus of claim 69 wherein the second sealing member comprises a second coupling member operable to couple the second sealing member to the base member.

73. The apparatus of claim 69 wherein the second sealing member is bonded to the base member.
74. The apparatus of claim 69 wherein the second sealing member is operable to deflect around the second end of the base member.
75. The apparatus of claim 69 further comprising:
 - a second sealing volume defined by the base member and adjacent the second end of the base member, whereby the second sealing volume is operable to contain a portion of the second sealing member when the second sealing member deflects around the second end of the base member.
76. The apparatus of claim 59 wherein the first sealing member is operable to seal the apparatus with a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.
77. The apparatus of claim 69 wherein the second sealing member is operable to seal the apparatus with a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.
78. The apparatus of claim 59 wherein the first sealing member defines a cylindrical volume extending out past the first end of the base member.
79. The apparatus of claim 69 wherein the second sealing member defines a cylindrical volume extending out past the second end of the base member.
80. An expandable tubular member comprising:
 - a tubular member comprising an initial diameter; and
 - an expansion apparatus positioned in the tubular member, the expansion apparatus comprising:
 - an elongated base member comprising a first end, a second end opposite the first end, and an expansion member comprising an expansion diameter and extending from the base member between the first and second end; and

a first sealing member coupled to the base member and extending out past the first end of the base member, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter.

81. The expandable tubular member of claim 80 wherein the base member comprises a first channel operable to couple the first sealing member to the base member.
82. The expandable tubular member of claim 80 wherein the base member is substantially cylindrical.
83. The expandable tubular member of claim 80 further comprising:
a plurality of expansion surfaces positioned on opposite sides of the expansion member, the plurality of expansion surfaces operable to expand the tubular member from the initial diameter to substantially the expansion diameter.
84. The expandable tubular member of claim 83 wherein the plurality of expansion surfaces increase in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter.
85. The expandable tubular member of claim 80 wherein the first sealing member is substantially tubular.
86. The expandable tubular member of claim 80 wherein the first sealing member comprises a first coupling member operable to couple the first sealing member to the base member.
87. The expandable tubular member of claim 80 wherein the first sealing member is bonded to the base member.
88. The expandable tubular member of claim 80 wherein the first sealing member is deflected around the first end of the base member by the tubular member.
89. The expandable tubular member of claim 80 further comprising:
a first sealing volume defined by the base member and the tubular member and positioned adjacent the first end of the base member, whereby the first sealing

volume contains a portion of the first sealing member which is deflected around the first end of the base member by the tubular member.

90. The expandable tubular member of claim 80 further comprising:
a second sealing member coupled to the base member and extending out past the second end of the base member, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter.
91. The expandable tubular member of claim 90 wherein the base member comprises a second channel operable to couple the second sealing member to the base member.
92. The expandable tubular member of claim 90 wherein the second sealing member is substantially tubular.
93. The expandable tubular member of claim 90 wherein the second sealing member comprises a second coupling member operable to couple the second sealing member to the base member.
94. The expandable tubular member of claim 90 wherein the second sealing member is bonded to the base member.
95. The expandable tubular member of claim 90 wherein the second sealing member is deflected around the second end of the base member by the tubular member.
96. The expandable tubular member of claim 90 further comprising:
a second sealing volume defined by the base member and the tubular member and positioned adjacent the second end of the base member, whereby the second sealing volume contains a portion of the second sealing member which is deflected around the second end of the base member by the tubular member.
97. The expandable tubular member of claim 80 wherein the first sealing member is operable to seal the expansion apparatus with the tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions.

98. The expandable tubular member of claim 90 wherein the second sealing member is operable to seal the expansion apparatus with the tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions.
99. The expandable tubular member of claim 80 wherein the first sealing member defines a cylindrical volume extending out past the first end of the base member.
100. The expandable tubular member of claim 90 wherein the second sealing member defines a cylindrical volume extending out past the second end of the base member.
101. The expandable tubular member of claim 80 wherein the first sealing member forms a cup seal with the tubular member.
102. The expandable tubular member of claim 90 wherein the second sealing member forms a cup seal with the tubular member.
103. The expandable tubular member of claim 80 wherein the tubular member is positioned in a well bore.
104. The expandable tubular member of claim 80 wherein the tubular member is a wellbore casing.
105. The expandable tubular member of claim 80 wherein the tubular member is a structural support.
106. The expandable tubular member of claim 80 wherein the tubular member is a pipeline.
107. An expansion apparatus comprising:
 - an elongated base member comprising a first end and a second end opposite the first end;
 - means for expanding a tubular member extending from the base member between the first and second end; and
 - first means for providing a seal, the first means for providing a seal extending out past the first end of the base member.

108. The apparatus of claim 107 wherein the base member comprises a means for coupling the first means for providing a seal to the base member.
109. The apparatus of claim 107 wherein the first means for providing a seal comprises a means for coupling the first means for providing a seal to the base member.
110. The apparatus of claim 107 wherein the first means for providing a seal is operable to deflect around the first end of the base member.
111. The apparatus of claim 107 further comprising:
first means for containing a portion of the first means for providing a seal when the first means for providing a seal deflects around the first end of the base member.
112. The apparatus of claim 107 further comprising:
second means for providing a seal, the second means for providing a seal extending out past the second end of the base member.
113. The apparatus of claim 112 wherein the base member comprises a means for coupling the second means for providing a seal to the base member.
114. The apparatus of claim 112 wherein the second means for providing a seal comprises a means for coupling the second means for providing a seal to the base member.
115. The apparatus of claim 112 wherein the second means for providing a seal is operable to deflect around the second end of the base member.
116. The apparatus of claim 112 further comprising:
second means for containing a portion of the second means for providing a seal when the second means for providing a seal deflects around the second end of the base member.

117. The apparatus of claim 107 wherein the first means for providing a seal is operable to seal the expansion apparatus with a tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions.
118. The apparatus of claim 112 wherein the second means for providing a seal is operable to seal the expansion apparatus with the tubular member when the expansion apparatus is moved axially through the tubular member in each of a plurality of directions.
119. A method for expanding a tubular member comprising:
providing a tubular member;
positioning an expansion apparatus in the tubular member, the expansion apparatus comprising a first end, a second end opposite the first end, and a first sealing member extending out past the first end of the expansion apparatus;
sealing the expansion apparatus with the tubular member, whereby the sealing comprises deflecting a portion of the first sealing member around the first end of the expansion apparatus by the tubular member; and
expanding the tubular member by moving the expansion apparatus axially through the tubular member.
120. The method of claim 119 wherein the expanding comprises moving the expansion apparatus axially through the tubular member in a plurality of directions, whereby the first sealing member provides a seal between the expansion apparatus and the tubular member in each of the plurality of directions.
121. The method of claim 119 wherein the expansion apparatus further comprises:
a second sealing member extending out past the second end of the expansion apparatus.
122. The method of claim 121 wherein the sealing comprises deflecting a portion of the second sealing member around the second end of the expansion apparatus by the tubular member.
123. The method of claim 122 wherein the expanding comprises moving the expansion apparatus axially through the tubular member in a plurality of directions, whereby the

first sealing member and the second sealing member provide a seal between the expansion apparatus and the tubular member in each of the plurality of directions.

124. The method of claim 119 wherein the sealing comprises forming a cup seal between the tubular member and the expansion apparatus.
125. An expansion apparatus comprising:
- a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end;
 - a first sealing volume defined by the base member and adjacent the first end of the base member;
 - an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter; and
 - a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.
126. An expansion apparatus comprising:
- a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end;
 - a first sealing volume defined by the base member and adjacent the first end of the base member;
 - a second sealing volume defined by the base member and adjacent the second end of the base member;
 - an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter;

a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions; and

a substantially tubular second sealing member coupled to the base member and extending out past the second end, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter and operable to deflect around the second end of the base member and partially into the second sealing volume to seal the apparatus to a tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

127. An expandable tubular member comprising:

a tubular member comprising an initial diameter; and

an expansion apparatus positioned in the tubular member, the expansion apparatus comprising:

a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end;

a first sealing volume defined by the base member and tubular member and adjacent the first end of the base member;

an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter and operable to expand the tubular member from the initial diameter to a diameter which is substantially equal to the expansion diameter; and

a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.

128. An expandable tubular member comprising:
- a tubular member comprising an initial diameter; and
 - an expansion apparatus positioned in the tubular member, the expansion apparatus comprising:
 - a substantially cylindrical elongated base member comprising a first end and a second end opposite the first end;
 - a first sealing volume defined by the base member and tubular member and adjacent the first end of the base member;
 - a second sealing volume defined by the base member and tubular member and adjacent the second end of the base member;
 - an expansion member extending from the base member between the first and second end and comprising an expansion diameter and a plurality of expansion surfaces positioned on opposite sides of the expansion member, the expansion surfaces increasing in diameter along their lengths from a base diameter to a diameter equal to the expansion diameter and operable to expand the tubular member from the initial diameter to a diameter which is substantially equal to the expansion diameter;
 - a substantially tubular first sealing member coupled to the base member and extending out past the first end, the first sealing member comprising a first sealing diameter which is greater than the expansion diameter and operable to deflect around the first end of the base member and partially into the first sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions; and
 - a substantially tubular second sealing member coupled to the base member and extending out past the second end, the second sealing member comprising a second sealing diameter which is greater than the expansion diameter and operable to deflect around the second end of the base member and partially into the second sealing volume to seal the apparatus to the tubular member when the apparatus is moved axially through the tubular member in each of a plurality of directions.




FIGURE 1a




FIGURE 1b




FIGURE 2a




FIGURE 2b




FIGURE 3




FIGURE 4




FIGURE 5a




FIGURE 5b




FIGURE 6a




FIGURE 6b




FIGURE 7a




FIGURE 79




FIGURE 8




FIGURE 9a




FIGURE 9b

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☒ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.